View NSN Online: https://aerobasegroup.com/nsn/7930-01-328-2030 P-T TECHNOLOGIES INC -- PF -- 7930-01-328-2030 ============= Product Identification ======================== Product ID:PF MSDS Date:10/21/1994 FSC:7930 NIIN:01-328-2030 MSDS Number: BXYYT === Responsible Party === Company Name:P-T TECHNOLOGIES INC Address:108 4TH AVENUE, SOUTH City:SAFETY HARBOR State:FL ZIP:34695 Country:US Info Phone Num:800-441-7874/813-726-4644 Emergency Phone Num:813-726-4644 CAGE:0JVH6 === Contracto r Identification === Company Name:P-T TECHNOLOGIES INC Address:108 4TH AVENUE, SOUTH Box:City:SAFETY HARBOR State:FL ZIP:34695 Country:US Phone:813-726-4644 CAGE:0JVH6 ======= Composition/Information on Ingredients ======== Ingred Name: TRADE SECRET. THIS FORMULATION IS A TRADE SECRET AND COMPLIES WITH 29CFR1910.1200, SECTION (I) TRADE SECRET. Other REC Limits: NONE RECOMMENDED ============= Hazards Identification ========================

LD50 LC50 Mixture:LD50 (ORAL, R

AT) IS >3.4 G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES-CAN CAUSE IRRITATION.
SKIN-PROLONGED/REPEATED CONTACT CAN CAUSE DEFATTING, DRYNESS &
DERMATITIS. INHALED-EXCESSIVE VAPORS CAN CAUSE IRRITATION OF THE
RESPIRATORY TRACT. INGESTED-IF LARGE QUANTITI ES INGESTED, MAY
CAUSE GASTROINTESTINL IRRITATION.
Explanation of Carcinogenicity:NOT EXPECT IT TO BE CARCINOGENIC.
Effects
of Overexposure:EYES-TEARING & REDNESS. INHALED-NAUSEA,
DIZZINESS, HEADACHE. INGESTED-NAUSEA, VOMITING.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure. NONE SPECIFIED BY MANUFACTURER.
======================================
======================================
First Aid:EYE:FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS,
SEE PHYSICIAN. SKIN:WASH THOROUGHLY WITH SOAP & WATER. REMOVE
CONTAMINATED CLOTHING. INHALATION: REMOVE TO FRESH AIR. IF BREATHING
IS DIFFIC ULT, SEE A PHYSICIAN. INGESTI ON:DO NOT INDUCE VOMITING.
PRODUCT CONTAINS HYDROCARBON. CONSULT PHYSICIAN.
PRODUCT CONTAINS HTDROCARBON. CONSULT PHTSICIAN.
======================================
Flook Doint Mathadi TOO
Flash Point Method: 10.0.
Flash Point Method:TCC Flash Point:144F 62C
Flash Point:144F,62C
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES.
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT.
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT.
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER.
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================
Flash Point:144F,62C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:1.3 Upper Limits:8.9 Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM CONBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explo sion Hazard:NONE SPECIFIED BY MANUFACTURER. ==================================

Other Precautions:KEEP OUT OF REACH OF CHILDREN.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE SPECIFIED BY MANUFACTURER. Ventilation:NORMAL ROOM VENTILATION IS ADEQUATE.USE FANS/OTHER MECHANICAL VENTILATION IN ENCLOSED AREAS WHERE LARGE QUANTITY IS USED
Protective Gloves:SOLVENT RESISTANT GLOVES RECOMMENDED. Eye Protection:SAFETY GLASSES RECOMMENDED. Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hy
gienic Practices:WASH THOROUGHLY BEFORE EATING OR DRINKING Supplemental Safety and Health THIS PRODUCT IS DEFINED AS AN OSHA HAZARD COMBUSTIBLE PER 29CFR1910.1200.
========= Physical/Chemical Properties ==========
HCC:V4 Boiling Pt:B.P. Text:380-430F Vapor Pres:< 1 MM Vapor Density:> 1 Spec Gravity:0.76 Evaporation Rate & amp; Reference:3.2 (N-BUAC = 1) Solubility in Water:NON-SOLUBLE Appearance and Odor:COLORLESS LIQUID WITH FAINT CITRUS ODOR Percent Volatiles by Volume: 100
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:THIS PRODUCT IS STABLE. Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND SMOKE. Conditions to Avoid Polymerization:HAZARDOUS POLYMERIZATION WILL NOT OCCUR.
======= Disposal Considerations ==========
Waste Disposal Methods:SOAK UP WITH ABSORBENT MATERIAL FOR INCINERATION

BIENT TEMPERATURES.

OR BURIAL IN APPROVED LANDFILL. OBSERVE FEDERAL, STATE & LOCAL REGULATIONS. REMOVE FROM WATER BY SKIMMING OR USE OF SUITABLE ABSORBENT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document s

hould seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.