

DEL PAINT MANUFACTURING COMPANY -- F0201 -- 8010-00-298-2293

===== Product Identification =====

Product ID:F0201

MSDS Date:08/30/1993

FSC:8010

NIIN:00-298-2293

MSDS Number: BYCLL

=== Responsible Party ===

Company Name:DEL PAINT MANUFACTURING COMPANY

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431/FAX 405-672-0804

Emergency Phone Num:800-424-9300 2

4 HRS

Preparer's Name:ONEY FLEMING

CAGE:EO522

=== Contractor Identification ===

Company Name:DEL PAINT MANUFACTURING CORP

CAGE:EO522

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM (COAL OIL)

CAS:8002-05-9

RTECS #:SE7175000

Fraction by Wt: 44.89%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingre

d Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 0.33%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NONHAZARDOUS INGREDIENTS

Fraction by Wt: 54.78%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

Ingred Name:VOLATILE ORGANIC COMPOUNDS 3.25 LBS/GL, 390 G/LTR

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION, REDNESS, TEARING,  
BLURRED VISION. SKIN: POSSIBLE IRRITATION, DEFATTING, DERMATITIS  
W/PROLONGED/REPEATED EXPOSURE. INHALATION: NASAL/RESPIRATORY  
IRRITATION, DIZZINESS, NAUSEA, HEADACH E. INGESTION: POSSIBLE  
GASTROINTESTINALIRRITATION, NAUSEA, VOMITING.

E

ffects of Overexposure:IF TLV'S EXCEEDED, SKIN CONTACT PRODUCES  
REDNESS. EYES: REDNESS/PAIN. INHALATION: LABORED BREATHING,  
DULLNESS, DROWSINESS. INGESTION: ABDOMINAL PAIN, NAUSEA.

Medical Cond Aggravated by Exposure:RESPIRATORY DISEASES.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMOUNT WATER 15 MINUTES OCCASIONALLY  
LIFTING EYELIDS. GET MEDICAL AID. SKIN: REMOVE CONTAMINATED  
CLOTHING. WASH W/SOAP & WATER. INHALATION: GET

FRESH AIR, GIVE

OXYGEN IF NECESSARY. GET MEDICAL AID. INGESTION: KEEP WARM, QUIET.

GET MEDICAL AID. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:100F,38C

Lower Limits:1.1

Upper Limits:6.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. WATER MAY SPREAD FIRE, USE WATER SPRAY ONLY TO COOL CONTAINERS EXPOSED TO FIRE.

Fire Fighting Procedures:SCBA (MSHA/NIOSH OR EQUIV.) & FULL PROTECTIVE

GEAR. PREVENT POSSIBLE PRESSURE BUILD-UP, AUTOIGNITION, EXPLOSION TO EXTREME HEAT BY COOLING W/WATER SPRAY.

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR. MAY TRAVEL & BE IGNITED BY PILET LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, OTHER REMOTE IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. COVER SPILL W/INERT ABSORBENT MATERIAL & SHOVEL W/NON-SPARKING TOOLS INTO CONTAINER. REMOVE CO

NTAINER TO SAFE AREA & SEAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLEAN, DRY AREA. KEEP AWAY FROM SPARKS, FIRE, REMOTE IGNITION SOURCES.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM CHILDREN. ALL EQUIPMENT SHOULD BE GROUNDED TO REDUCE STATIC ELECTRICITY HAZARD. USE NONSPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Pro

tection:IF TLV OF PRODUCT OR ANY COMPONENT EXCEEDED, USE  
RESPIRATOR W/APPROPRIATE CARTRIDGES (NIOSH APPROVED). ENGINEERING  
OR MANAGEMENT CONTROL SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.  
Ventilation:LOCAL EXHAUST MUST BE SUFFICIENT TO KEEP AIRBORNE VAPOR  
CONCENTRATION BELOW TLV.  
Protective Gloves:CHEMICAL RESISTANT  
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.  
Other Protective Equipment:CLEAN FLUSHING WATER SOURCE SUGGESTED.  
IMPERVIOUS CLOTHING AS NEEDED.  
Supplemental Safety and  
Health  
NK

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:303F,151C  
Melt/Freeze Pt:M.P/F.P Text:NA  
Decomp Temp:Decomp Text:752F,400C  
Vapor Pres:2.58  
Vapor Density:>AIR  
Spec Gravity:1.23  
pH:NA  
Viscosity:77-86KU  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:NO  
Appearance and Odor:MAROON LIQUID W/SLIGHT ODOR  
Percent Volatiles by Volume:45.97  
Corrosion Rate:NA

===== Stability and Reactivity Data =====  
===

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:DO NOT STORE NEAR HEATED SURFACES, OPEN  
FLAMES, IGNITION SOURCES.  
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON  
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE, LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is f

ormulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.