View NSN Online: https://aerobasegroup.com/nsn/6850-01-282-9908

3M - ENGINEERING SYSTEMS DIV. -- 3M BRAND TYPE 148 TONER

MSDS Safety Information

FSC: 6850 NIIN: 01-282-9908 MSDS Date: 02/20/1995 MSDS Num: BYHKS Product ID: 3M BRAND TYPE 148 TONER MFN: 03 Responsible Party Cage: 1BY21 Name: 3M CO - ENGINEERING SYSTEMS DIV. Address: 3M CENTER City: ST PAUL MN 551 44-1000 Info Phone Number: 612-733-1110 Emergency Phone Number: 612-733-1110 Review Ind: Y Published: Y
Contractor Summary
Cage: 1BY21 Name: MINNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV Address: 3M CTR City: SAINT PAUL MN 55144-1000 Phone: 612-737-4114 Cage: 9X866 Name: SUMMIT ASSOCIATES Address: 10910-H SOUTHLAKE COURT City: RICHMOND VA 23236-3914 Phone: 804-794-1434
Item Description Information
Item Manager: S9G Item Name: TONER,DIRECT ELECTROSTATIC PROCESS Specification Number: NONE Type/Grade/Class: NONE Unit of Issue: BX Quantitative Expression: 000000004EA UI Container Qty: 4 Type of Container: BOX
Ingredients
======================================

Nam

e: STYRENE ACRYLIC RESIN (MIXTURE WITH CAS# 58353-09-6) % Wt: 60-100 Other REC Limits: NONE RECOMMENDED **OSHA PEL: NOT ESTABLISHED** ACGIH TLV: NOT ESTABLISHED _____ Cas: 58353-09-6 Name: STYRENE ACRYLIC RESIN (MIXTURE WITH CAS# 25213-39-2) % Wt: 60-100 Other REC Limits: NONE RECOMMENDED **OSHA PEL: NOT ESTABLISHED** ACGIH TLV: NOT ESTABLISHED -----Cas: 39382-25-7 Name: BISPHENOL A PROPYLENE OXIDE FUMARATE % Wt: 10-30 Other REC Limits: NONE RECOMMENDED **OSHA PEL: NOT ESTABLISHED** ACGIH TLV: NOT ESTABLISHED -----Cas: 9003-07-0 RTECS #: TR5000000 Name: POLYPROPYLENE % Wt: 5-10 Other REC Limits: NONE RECOMMENDED **OSHA PEL: NOT ESTABLISHED** ACGIH TLV: NOT ESTABLISHED -----Cas: 8005-02-5 Name: SOLVENT BLACK 7 % Wt: 3-7 Other REC Limits: NONE RECOMMENDED **OSHA PEL: NOT ESTABLISHED** ACGIH TLV: NOT ESTABLISHED -----Cas: 1333-86-4 RTECS #: FF5800000 Name: CARBON BLACK % Wt: 3-7 Ot

her REC Limits: NONE RECOMMENDED **OSHA PEL: NOT ESTABLISHED** ACGIH TLV: NOT ESTABLISHED _____ Cas: 112945-52-5 RTECS #: VV7310000 Name: SILICA % Wt: 0.1-1 Other REC Limits: NONE RECOMMENDED OSHA PEL: 6 MG/M3 ACGIH TLV: 10 MG/M3 _____ Health Hazards Data _____ LD50 LC50 Mixture: ORAL LD50 (RAT) IS UNKNOWN Route Of Entry Inds - Inhalation: YES Skin: YES Ingestion: YES Carcino genicity Inds - NTP: NO IARC: NO OSHA: NO Effects of Exposure: EYES: MECHANICAL EYE IRRITATION. SKIN: MECHANICAL SKIN IRRITATION. INHALATION: IRRITATION (UPPER RESPIRATORY). INGESTION: IRRITATION OF GASTROINTESTINAL TISSUES. Explanation Of Carcinogenicity: NONE Signs And Symptions Of Overexposure: EYE-REDNESS, SCRATCHING OF THE CORNEA AND TEARING. SKIN-ITCHING AND REDNESS. INHALATION-SORENESS OF THE NOSE AND THROAT , COUGHING AND SNEEZING. SWALLOWED-PAIN, VOMITING, ABDOMINAL TENDERNESS, NAUSEA, BLOOD IN VOMITUS, AND BLOOD IN FECES. Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER. First Aid: EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: IF SIGNS/SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS CONTINUE, CALL A PHYSICIAN. SWALLOWED: DRINK 2 GLASSES OF WATER. CALL A PHYSICIAN. _____ _____ Handling and Disposal _____

Spill Release Procedures: OBSERVE PRECAUTIONS FROM OTHER SECTIONS. VACUUM TO AVOID DUSTING. CAUTION! A VACUUM CLEANER COULD BE AN IGNITION SOURCE. CLEAN UP RESIDUE WITH WATER. PLACE IN CLOSED CONTAINER. CAUTION: POWDER SPILL O N FLOOR MAY CREATE A SLIP HAZARD.

Waste Disposal Methods: INCINERATE IN A INDUSTRIAL OR COMMERCIAL FACILITY. DISPOSE OF WASTE PRODUCT IN A SANITARY LANDFILL.

Handling And Storage Precautions: STO

RE AWAY FROM HEAT, SPARKS, OPEN FLAMES, AND OTHER SOURCES OF IGNITION. Other Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME & amp; OTHER IGNITION SOURCES. _____ Fire and Explosion Hazard Information _____ Extinguishing Media: WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures: NOT DETERMINED. Unusual Fire/Explosion Hazard: DUST CLOUDS OF THIS MATERIAL IN COMBINATION WITH AN IGNITION SOURCE MAY BE EXPLOSIVE. Control Measures _____ Respiratory Protection: AVOID PROLONGED BREATHING OF DUST. Ventilation: USE IN WELL-VENTILATED AREA. Protective Gloves: AVOID PROLONGED OR REPEATED SKIN CONTAC Eye Protection: AVOID EYE CONTACT. Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: WASH HANDS AFTER HANDLING AND BEFORE EATING. Suppl emental Safety and Health: NONE ______ **Physical/Chemical Properties** _____ HCC: V7 Spec Gravity: 0.30-0.50 Solubility in Water: NIL Appearance and Odor: FINE BLACK POWDER, ESSENTIALLY ODORLESS. ______ **Reactivity Data** ______ Stability Indicator: YES Stability Condition To Avoid: ELEVATED TEMPERATURE ST ORAGE MAY CAUSE CLUMPING OF TONER OWDER. Materials To Avoid: NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, HYDROCARBONS, STYRENE MONOMER AND CARBON PARTICULATES. Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: NONE _____

Toxicological Information

Ecolog

ical Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Cage: 1BY21 Trans ID NO: 121864 Product ID: 3M BRAND TYPE 148 TONER MSDS Prepared Date: 02/20/1995 Review Date: 03/27/1996 MFN: 3 Net Unit Weight: 2.8 LBS AF MMAC Code: NR Multiple KIT Number: 0 Review IND: Y Unit Of Issue: BX Container QTY: 4 Type Of Container: BOX

Detail DOT Information

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail IMO Information

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA P

SN Code: ZZZ IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: 3M BRAND TYPE 148 TONER Cage: 1BY21 Company Name: MI NNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV Street: 3M CTR City: SAINT PAUL MN Zipcode: 55144-1000 Health Emergency Phone: 612-733-1110 Label Required IND: Y Date Of Label Review: 03/27/1996 Status Code: C Label Date: 03/27/1996 Origination Code: F Chronic Hazard IND: Y Signal Word: CAUTION Health Hazard: Slight Contact Hazard: Slight Fire Hazard: None Reactivity Hazard: None Hazard And Precautions: STORE AWAY FROM HEAT, SPARKS, OPEN FLAMES, AND OTHER SOURCES OF IGNITION. IN CAS E OF SPILL: OBSERVE PRECAUTIONS FROM OTHER SECTIONS. VACUUM TO AVOID DUSTING. CAUTION! A VACUUM CLEANER COULD BE AN IGNI TION SOURCE. CLEAN UP RESIDUE WITH WATER. PLACE IN CLOSED CONTAINER. CAUTION: POWDER SPILL ON FLOOR MAY CREATE A SLIP HAZARD. FIRST AID: EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. GET IMMEDI ATE MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: IF SIGNS/SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS CONTINUE, CALL A PHYSICIAN. SWALLOWED: DRINK 2 G LASSES OF WATER. CALL A PHYSICIAN. _____

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Departm

ent of Defense

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or othe

r government situation.