

3M - ENGINEERING SYSTEMS DIV. -- 3M BRAND TYPE 148 TONER

=====
MSDS Safety Information
=====

FSC: 6850
NIIN: 01-282-9908
MSDS Date: 02/20/1995
MSDS Num: BYHKS
Product ID: 3M BRAND TYPE 148 TONER
MFN: 03
Responsible Party
Cage: 1BY21
Name: 3M CO - ENGINEERING SYSTEMS DIV.
Address: 3M CENTER
City: ST PAUL MN 551
44-1000
Info Phone Number: 612-733-1110
Emergency Phone Number: 612-733-1110
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 1BY21
Name: MINNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV
Address: 3M CTR
City: SAINT PAUL MN 55144-1000
Phone: 612-737-4114
Cage: 9X866
Name: SUMMIT ASSOCIATES
Address: 10910-H SOUTHLAKE COURT
City: RICHMOND VA 23236-3914
Phone: 804-794-1434

=====
Item Description Information
=====

Item Manager: S9G
Item Name: TONER,DIRECT ELECTROSTATIC PROCESS
Specification Number: NONE
Type/Grade/Class: NONE
Unit of Issue: BX
Quantitative Expression: 00000000004EA
UI Container Qty: 4
Type of Container: BOX

=====
Ingredients
=====

Cas: 25213-39-2
Nam

e: STYRENE ACRYLIC RESIN (MIXTURE WITH CAS# 58353-09-6)

% Wt: 60-100

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 58353-09-6

Name: STYRENE ACRYLIC RESIN (MIXTURE WITH CAS# 25213-39-2)

% Wt: 60-100

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 39382-25-7

Name: BISPHENOL A PROPYLENE OXIDE FUMARATE

% Wt: 10-30

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 9003-07-0

RTECS #: TR5000000

Name: POLYPROPYLENE

% Wt: 5-10

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 8005-02-5

Name: SOLVENT BLACK 7

% Wt: 3-7

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 1333-86-4

RTECS #: FF5800000

Name: CARBON BLACK

% Wt: 3-7

Ot

her REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 112945-52-5

RTECS #: VV7310000

Name: SILICA

% Wt: 0.1-1

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 6 MG/M3

ACGIH TLV: 10 MG/M3

=====
Health Hazards Data
=====

LD50 LC50 Mixture: ORAL LD50 (RAT) IS UNKNOWN

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcino

genicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYES: MECHANICAL EYE IRRITATION. SKIN: MECHANICAL SKIN IRRITATION. INHALATION: IRRITATION (UPPER RESPIRATORY). INGESTION: IRRITATION OF GASTROINTESTINAL TISSUES.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: EYE-REDNESS, SCRATCHING OF THE CORNEA AND TEARING. SKIN-ITCHING AND REDNESS. INHALATION-SORENESS OF THE NOSE AND THROAT , COUGHING AND SNEEZING. SWALLOWED-PAIN, VOMITING, ABDOMINAL TENDERNESS, NAUSEA, BLOOD IN VOMITUS, AND BLOOD IN FECES.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: IF SIGNS/SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS CONTINUE, CALL A PHYSICIAN. SWALLOWED: DRINK 2 GLASSES OF WATER. CALL A PHYSICIAN.

=====
Handling
and Disposal
=====

Spill Release Procedures: OBSERVE PRECAUTIONS FROM OTHER SECTIONS. VACUUM TO AVOID DUSTING. CAUTION! A VACUUM CLEANER COULD BE AN IGNITION SOURCE. CLEAN UP RESIDUE WITH WATER. PLACE IN CLOSED CONTAINER. CAUTION: POWDER SPILL ON FLOOR MAY CREATE A SLIP HAZARD.

Waste Disposal Methods: INCINERATE IN A INDUSTRIAL OR COMMERCIAL FACILITY. DISPOSE OF WASTE PRODUCT IN A SANITARY LANDFILL.

Handling And Storage Precautions: STO

RE AWAY FROM HEAT, SPARKS, OPEN FLAMES,
AND OTHER SOURCES OF IGNITION.

Other Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME & OTHER IGNITION
SOURCES.

=====
Fire and Explosion Hazard Information
=====

Extinguishing Media: WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures: NOT DETERMINED.

Unusual Fire/Explosion Hazard: DUST CLOUDS OF THIS MATERIAL IN COMBINATION WITH

AN IGNITION SOURCE MAY BE EXPLOSIVE.

=====
Control Measures
=====

Respiratory Protection: AVOID PROLONGED BREATHING OF DUST.

Ventilation: USE IN WELL-VENTILATED AREA.

Protective Gloves: AVOID PROLONGED OR REPEATED SKIN CONTACT

Eye Protection: AVOID EYE CONTACT.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH HANDS AFTER HANDLING AND BEFORE EATING.

Suppl

emental Safety and Health: NONE

=====
Physical/Chemical Properties
=====

HCC: V7

Spec Gravity: 0.30-0.50

Solubility in Water: NIL

Appearance and Odor: FINE BLACK POWDER, ESSENTIALLY ODORLESS.

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: ELEVATED TEMPERATURE ST

ORAGE MAY CAUSE CLUMPING

OF TONER POWDER.

Materials To Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE,

HYDROCARBONS, STYRENE MONOMER AND CARBON PARTICULATES.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NONE

=====
Toxicological Information
=====

=====
Ecolog

ical Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Cage: 1BY21
Trans ID NO: 121864
Product ID: 3M BRAND TYPE 148 TONER
MSDS Prepared Date: 02/20/1995
Review Date: 03/27/1996
MFN: 3
Net Unit Weight: 2.8 LBS
AF MMAC Code: NR
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: BX
Container QTY: 4
Type Of Container: BOX

Detail DOT Information

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail IMO Information

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA P

SN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
HAZCOM Label
=====

Product ID: 3M BRAND TYPE 148 TONER

Cage: 1BY21

Company Name: MI

NNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV

Street: 3M CTR

City: SAINT PAUL MN

Zipcode: 55144-1000

Health Emergency Phone: 612-733-1110

Label Required IND: Y

Date Of Label Review: 03/27/1996

Status Code: C

Label Date: 03/27/1996

Origination Code: F

Chronic Hazard IND: Y

Signal Word: CAUTION

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: STORE AWAY FROM HEAT, SPARKS, OPEN FLAMES, AND OTHER SOURCES OF IGNITION. IN CAS

E OF SPILL: OBSERVE PRECAUTIONS FROM OTHER

SECTIONS. VACUUM TO AVOID DUSTING. CAUTION! A VACUUM CLEANER COULD BE AN IGNITION SOURCE. CLEAN UP RESIDUE WITH WATER. PLACE IN CLOSED CONTAINER. CAUTION: POWDER SPILL ON FLOOR MAY CREATE A SLIP HAZARD. FIRST AID: EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: IF SIGNS/SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS CONTINUE, CALL A PHYSICIAN.

SWALLOWED: DRINK 2 GLASSES OF WATER. CALL A PHYSICIAN.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Departm

ent of Defense

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.