View NSN Online: https://aerobasegroup.com/nsn/6850-01-416-6363

Product ID:SAFETY STRIP 1000 MSDS Date:07/07/1993 FSC:6850 NIIN:01-416-6363 **MSDS Number: BYRYK** === Responsible Party === Company Name: BRULIN AND CO INC Address:2920 DR ANDREW J BROWN AVE Box:270 **City:INDIANAPOLIS** State:IN ZIP:46205-0270 Country:US Info Phone Num:317-923-3211 OR 800-428-7149 **Emergency Pho** ne Num:317-923-3211 CAGE:94058 === Contractor Identification === Company Name: BRULIN AND CO INC Address:2920 DR ANDREW J BROWN AVE Box:270 **City:INDIANAPOLIS** State:IN ZIP:46205-0270 Country:US Phone:317-923-3211 CAGE:94058

Ingred Name:2-BUTOXYETHANOL CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: 15% Other REC Limits:NONE RECOMMENDED

Ingred Name:MONOETHANOLAMINE CAS:141-43-5 RTECS #:KJ5775000 Fraction by Wt: 0.9-1.1% Other RE Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:DIRECT CONTACT MAY CAUSE MODERATE EYE
IRRITATION. EXCESSIVE INHALATION MAY CAUSE RESPIRATORY IRRITATION.
MODERATELY TOXIC IF INGESTE. PROLONGED OR REEATED SKIN CONTACT MAY
CAUSE IRRITATION. CHRONIC SK IN EXOSURE MAY CAUSE DERMATITIS.
OVEREXPOSU
RE BY AIR &/OR PROLONGED SKIN CONTACT MAY CAUSE TEMPORARY
BLURRING OF VISION.
Explanation of Carcinogenicity:NOT CARCINOGENIC.
Effects of Overexposure:EYE CONTACT MAY CAUSE REDNESS, TEARING. SKIN
IRRITATION MAY BE SEEN AS REDNESS. EXCESSIVE INHALATION MAY CAUSE
HEADACHE, NAUSEA, DIZZINESS. INGESTION MAY CAUSE GASTROINTESTINAL
IRRITATION, ANUSEA, VOM ITING, DIARRHEA.

Medical Cond Aggravated by Exposure:NONE KNOWN.

==

First Aid:EYE-FLUSH WITH LARGE AMOUNTS OF WATER FOR 15MINS LIFTING UPPER/LOWER LIDS OCCASIONALLY. SEE HYSICIAN. INHALE-REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF DIFFICULTY BREATHING. SEE HYSICIAN. SKIN-WASH W/M ILD SOAP & WATER. REMOE CONTAMINED CLOTHING. INGEST-GIVE 2 GLASSES OF WATER & INDUCE VOMITING IMMEDIATELY BY STICKING FINGER DOWN THROAT. CALL PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH IF UNCONSCIOUS.

======

Flash Point Method:PMCC Flash Point:>200F,>93C Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICALS. Fire Fighting Procedures:WATER FOG MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM EVEN EMPTY.

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE THE AREA WELL. ABSORB ON SOLID ABSORBENT & SHOVEL INTO CONTAINER. FLUSH Handling and Storage Precautions:STORE BETWEEN 40 AND 120F. Other Precautions:NONE

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:IF TLV IS EXCEEDED, USE A NIOSH/MSHA APPROVED RESPIRATOR. CONTACT YOUR LOCAL SAFETY EQUIPMENT SUPPLIER FOR RECOMMENDATIONS. Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL &/OR LOCAL EXHAUST) VENTILATION TO MAINTA IN EXPOSURE BELOW TLV. Protective Gloves:BUTYL RUBBER Eye Protection:GOGGLES Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT. Work Hygienic Practices:AVOID BREATHING SPRAY MIST. WASH HANDS AFTER HANDLING. LAUNDER CONTAMIN CLOTHING PRIOR TO REUSE. Supplemental Safety and Health NONE

HCC:N1 Boiling Pt:B.P. Text:212F-350F Melt/Freeze Pt:M.P/F.P Text: