View NSN Online: https://aerobasegroup.com/nsn/9150-01-031-7238

Product ID:DOW CORNING GN METAL ASSEMBLY SPRAY MSDS Date:11/03/1995 FSC:9150 NIIN:01-031-7238 MSDS Number: BYSDD === Responsible Party === Company Name: DOW CORNING CORP Address:3901 SOUTH SAGINAW ROAD Box:997 City:MIDLAND State:MI ZIP:48686 Country:US Info Phone Num:517-496-6000 Emergenc y Phone Num:517-496-5900/800-424-9300(CHEMTREC) CAGE:5D028 === Contractor Identification === Company Name: DOW CORNING CORP Address:3901 S SAGINAW RD Box:997 City:MIDLAND State:MI ZIP:48686-0997 Country:US Phone:517-496-6000/517-496-6315 CAGE:5D028 Company Name: DOW CORNING CORP Address:2200 W SALZBURG RD Box:City:AUBURN State:MI ZIP:48611 Country:US Phone:517-496-4388 CAGE:71984

Ingred Name:MOLYBDENUM DISULFIDE CAS:1317-33-5 R TECS #:QA4697000 Fraction by Wt: 13% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG MO/M3 ACGIH TLV:5 MG MO/M3

Ingred Name:GRAPHITE CAS:7782-42-5 RTECS #:MD9659600 Fraction by Wt: 2% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MPPCF; Z-3 ACGIH TLV:2 MG/M3 RDUST; 9495

Ingred Name:HYDROTREATED HEAVY PETROLEUM NAPHTHA (MINERAL SPIRITS) CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 53% Other REC Limits:NONE RECOMMENDED

Ingred Name:LPG (LIQUEFIED PETROLEUM GAS) CAS:68476-85-7 RTECS #:SE75450 00 Fraction by Wt: 22% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9495

Ingred Name:MINERAL OIL, WHITE CAS:8042-47-5 RTECS #:PY8047000 Fraction by Wt: 9% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE:DIRECT CONTACT IRRIT LSIGHTLY W/REDNESS,SWELLING. SKIN:REP/PR

OL CONTACT MAY CAUSE DEFATTING LEADING TO DERM. INHAL:SHORT VAP EXPO MAY CAUSE DROWS,IRRIT NOSE/THROAT,CAUSE INJURY TO NERVOUS SYS.GAS MAY SUFFOCATE BY REDUCING AMT OF AIR(OXY) AVAILABLE FOR BREATH. ORAL:SM AMTS TRANSFER TO MOUTH BY FINGERS DURING (SUPPL) Explanation of Carcinogenicity:PER MSDS:CARCINOGENS:NONE KNOWN. Effects of Overexposure:INHAL:DROWS,IRRIT NOSE/THROAT, NERVOUS SYTEM INURY. GAS REDUCES AIR(OXY) AVAILABLE FOR BREATHING. INGEST:LG MATS MAY INJURE SLIGHTL
Y. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:EYE:IMMED FLUSH W/WATER FOR 15MINS. SKIN:REMOVE FRM SKIN.WASH THOROUGHLY W/SOAP/WATER OR WATERLESS CLEANSER.GET MED ATTN IF IRRIT/OTHER ILL EFFECTS DEVELOP/PERSIST. INHAL:REMOVE TO FRESH AIR.GET IMMED MED ATTN. ORAL:GET MED ATTN. COMMENTS:TREAT ACCORDING TO PERSON'S CONDITION & SPECIFICS OF EXPOSURE.
======================================
Flash Point:FLAMM AEROSOL Autoignition Temp:Autoignition Temp Text:N/DETR Lower Limits:N/DETERMINE Upper Limits:N/DETERMINE Extinguishing Media:CARBON DIOXIDE (CO2), WATER SPRAY, DRY CHEMICAL, FOAM. WATER CAN BE USED TO COOL FIRE EXPOSED CONTAINERS. Fire Fighting Procedures:SCBA & PROT CLOTH SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEM.EVACUATE AREA IN CASE OF OVERHEATING/FIRE.USE WATERSPRAY TO KEEP FIRE EXPO CNTNRS COOL. Unusual Fire/Expl osion Hazard:VAP ARE HEAVIER THAN AIR & CAN TRAVEL ALONG GROUND TO REMOTE IGN SOURCES.
======================================

Spill Release Procedures:OBSERVE ALL APPLICABLE LOC/STATE/FED WASTE MGMT REGS.LET PROPELLANT EVAPORATE.COLLECT/CONTAIN FOR SALVAGE/DISP.OBSERVE ALL PPE RECOMMENDATIONS.LOC/STATE/FED REPORTING REMQTS MAY APPLY TO MATL SPILL/RE LEASE INTO ENVIRO.SCBA/SUPP-AIR RESP/FULLFACE RESP Neutralizing Agent:NONE SPECIFIED BY MANUFACTU DED

RER.
======================================
Handling and Storage Precautions:KEEP CNTNR CLSD & AWAY FRM HEAT/SPARKS/OPN FLAME.AVOID EYE/SKIN CONTACT.AVOID BREATH VAP.DO NOT TAKE INTERNALLY.
Other Precautions:CORNING CORP ENVIRO MGMT 517-496-6315 IF ADDN INFO REQUIRED.NO SARA SEC313 CHEM PRESENT.
======================================
Respiratory Protection:USE RESP PROT UNLESS ADEQUATE LOC EXHAU VENTI PROVIDED OR AIR S AMPLING DATA SHOW EXPO WHITHIN RECOMMENDED EXPO GUIDELINES.INDUSTRIAL HYGIENE PERSONNEL CAN ASSIST IN JUDGING ADEQUACY OF EXISTING ENGINE ERING CONTROLS.ORG VAP/DUST/MIST TYPE. Ventilation:LOCAL EXHAUST/GENERAL VENTILATION:RECOMMENDED. Protective Gloves:NEOPRENE,NITRILE,SILVER SHIELD,4H(R). Eye Protection:SAFETY GLASSES AS MIN. Other Protective Equipment:PRECAUTIONS FOR RM TEMP HDNLG;USE @ELEVATED TEMP/AEROSOL/SPRAY APPLICATIONS MAY REQUIRE ADDED PRECAUTIONS. Work Hygienic Practices: WASH @MEALTIME/END OF SHIFT.CONTAMIN CLOTH/SHOES REMOVED ASAP/CLEAN WELL BEF REUSE. Supplemental Safety and Health HAZ DECOM PROD:NITROGEN OXIDES,METAL OXIDES. HEALTH HAZ:USE/ETC SHOULD NOT INJURE.SWALLOWING LG AMTS MAY INJURE SLIGHTLY.MATL MAY CAUSE SENS OF HEART MUSCLE IF INAHL @HI CONCE.FROSTBITE TYP BURN TO
EYE/SKIN FRM LIQ CONTACT.
HCC:V 3 Vapor Pres:N/DETERMIN Vapor Density:N/DETERMIN Spec Gravity:1.00 @25C Solubility in Water:NOT DETEMRINED. Appearance and Odor:AEROSOL SPRAY CAN, CHARCOAL GRAY, SOLVENT ODOR. Percent Volatiles by Volume:N/DETR
======================================

Stability Indicator/Materials to Avoid:YES

NONE.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products: THER BREAKDWN DURING FIRE/VERY HI HEAT CONDITONS: SULFUR OXIDE, CARBON OXIDES, TRACE OF INCOMPLETE BU

Waste Disposal Methods:DISPOSAL OF COLLECTED PROD/RESIDUES/CLEANUP MATL MAY BE GOVT REG.OBSERVE ALL APPLICABLE LOC/STATE/FED WASTE MGMT REGS.MATL AS RECEIVED CLASSIFIED AS HAZ WASTE:D001.STATE/LOC LAWS MAY IMPOSE ADDN REG R EQMTS REGARDING DISP.CALL DOW (OTHER PRECAUT)

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by eleme nts of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.