View NSN Online: https://aerobasegroup.com/nsn/6750-01-319-6473

Product ID:102 3209 DURAFLO RT DEVELOPER (WORKING SOLUTION) MSDS Date:11/15/1995 FSC:6750 NIIN:01-319-6473 MSDS Number: BYSFB === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Nu m:716-477-3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

======= Composition/Informatio

n on Ingredients ========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 80 - 85% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:SODIUM BISULFITE (SASA III) (CERCLA) CAS:7631-90-5 RTECS #:VZ2000000 Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9495 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:POTASSIUM SULFITE CAS:10117-38-1 RTECS #:WT3530000 Fraction by Wt: 1 - 5% Oth er REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SULFITE CAS:7757-83-7 RTECS #:WE2150000 Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM CARBONATE CAS:584-08-7 RTECS #:TS7750000 Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED

Ingred Name:GLUTARALDEHYDE BIS(SODIUM BISULFITE) CAS:7420-89-5 Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM CARBONATE CAS:497-19-8 RTECS #:VZ4050000 Fraction by Wt: 1 - 5% Other REC Limits:NONE RECO

MMENDED

Ingred Name:POTASSIUM HYDROXIDE (CERCLA) CAS:1310-58-3 RTECS #:TT2100000 Fraction by Wt: 100C Vapor Pres:18 @ 68F Vapor Density:O.6 Spec Gravity:1.115 pH:9.4 Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQUID, ODORLESS Percent Volatiles by Volume:80- 85

Stability Indicator/Materials to Avoid:YES STRONG ACIDS Stability Condition to Avoid:NONE Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXI DE, SULFUR DIOXIDE

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER IF PERMITTED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warra nts this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.