

CANON -- FX-2 CARTRIDGE BLACK, H11-6321-220 -- 6850-01-416-7995

===== Product Identification =====

Product ID:FX-2 CARTRIDGE BLACK, H11-6321-220

MSDS Date:12/01/1993

FSC:6850

NIIN:01-416-7995

MSDS Number: BYSJB

=== Responsible Party ===

Company Name:CANON

Address:ONE CANON PLAZA

City:LAKE SUCCESS

State:NY

ZIP:11042

Country:US

Info Phone Num:516-328-5600

Emergency Phone Num:800-424-9300(CHEMTREC)

Preparer's Name:JOSEPH PALMERI

CAGE:TO787

=== Contractor Identification ===

Company Name:AUTOMATION AIDS INC (800-234-2790)

Address:420 BABYLON RD, SUITE B

Box:UNKNOW

City:HORSHAM

State:PA

ZIP:19044

Country:US

Phone:800-817-4448

CAGE:01QM9

Company Name:CANON INC

Address:30-2 SHIMOMARUKO 3-CHOME, OHTA-KU

Box:City:TOKYO

Country:JA

Phone:03-3758-2111

CAGE:TO787

Company Name:CANON USA INC

Address:ONE CANON PLZ

Box:City:NEW HYDE PARK

State:NY

ZIP:11042

Country:US

Phone:516-328-5000; 5600

CAGE:08YZ7

=====
Composition/Information on Ingredients
=====

Ingred Name:STYRENE ACRYLATE COPOLYMER,
CAS:25153-46-2
Fraction by Wt: 45-55%

Ingred Name:IRON OXIDE
CAS:1317-61-9
Fraction by Wt: 45-55%
OSHA PEL:10 MG/M3
ACGIH TLV:5 MG/M3

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV: 10 MG/M3 (TOTAL DUST)
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:
INHALATION-EXPECTED TO BE A LOW HAZARD
FOR RECOMMENDED HANDLING. EYE-NO SPECIFIC HAZARD KNOWN. MAY CAUSE
TRANSIENT IRRITATION. SKIN-EXPECTED TO BE A LOW HAZARD FOR
RECOMMENDED HANDLING. INGESTION-EXPECTED TO BE LOW INGESTION
HAZARD.
Effects of Overexposure:BASED UPON AVAILABLE DATA, HUMAN EXPOSURE TO
TONER HAS BEEN SHOWN TO CAUSE MINIMAL RESPIRATORY IRRITATION
AS MAY OCCUR WITH LARGE AMOUNTS OF ANY NONTOXIC DUSTS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY
MANUFACTURER.

=====
First Aid Measures
=====

First Aid:INHALATION:IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL
ATTENTION IF SYMPTOMS PERSIST. EYES:ANY MATERIAL THAT CONTACTS THE
EYES SHOULD BE WASHED OUT IMMEDIATELY WITH WATER FOR AT LEAST 15
MINUTES. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR.SKIN:WASH WITH
SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR.
INGESTION:DRINK 1-2 GLASSES OF WATER. NO ADVERSE EFFECTS EXPECTED.

=====
Fire Fighting Measures
=====

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), DRY CHEMICAL.
Fire Fighting Procedures:NONE.
Unusual Fire/Explosion Hazard:TONER MATERIAL, LIKE MOST ORGANIC
MATERIAL IN POWDERED FORM, IS CAPABLE OF CREATING A DUST EXPLOSION.

=====
Accidental Release Measures
=====

Spill Release Procedures:SWEEP MATERIAL ONTO PAPER AND PLACE IN A FIBER
CARTON.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER

tability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:HAZARDOUS COMBUSTION PRODUCTS:CARBON DIOXIDE, CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR LANDFILL, CAN BE INCINERATED WHEN IN COMPLIANCE WITH LOCAL REGULATIONS. DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECTED TO NATIONAL, STATE OR LOCAL LAWS. CARTRIDGE MAY BE DISPOSED OF AS PLASTIC WASTE. SEE "CANON CLEAN EARTHCAMPAIGN."

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to thei

r

particular situation.