View NSN Online: https://aerobasegroup.com/nsn/8040-00-262-9028

Product ID: ADHESIVE M6314 MSDS Date:05/10/1990 FSC:8040 NIIN:00-262-9028 MSDS Number: BYVVJ === Responsible Party === Company Name: UNIROYAL PLASTICS CO INC ENGINEERED SYSTEMS UNIT Address:312 N HILL ST Box:2000 City:MISHAWAKA State:IN ZIP:46544-1399 Country:US Info Phone Num:2 19-256-8355/FAX 219-256-8809 Emergency Phone Num:219-256-8376 CAGE:00333 === Contractor Identification === Company Name: UNIROYAL PLASTICS CO INC ENGINEERED SYSTEMS UNIT Address:312 N HILL ST Box:2000 City:MISHAWAKA State:IN ZIP:46544-1399 Country:US Phone:219-256-8376 CAGE:00333

======= Composition/Information on Ingredients ==========

Ingred Name:RUBBER SOLVENT(NAPHTHA SOLVENT REFINED, LIGHT) CAS:64741-84-0 Fraction by Wt: 50% OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name: ZINC COMPOUND

S Fraction by Wt: 8.1% OSHA PEL:N/K ACGIH TLV:N/K

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: EXPOSURE TO VAPOR CAN CAUSE IRRITATION TO EYES, AND MUCOUS MEMBRANES. EXCESSIVE EXPOSURE CAN CAUSE HEADACHE, NAUSEA, NARCOSIS, AND NERVE DAMAGE. CONTACT WITH LIQUID CAN CAUSE EYE AND SKIN IRRITA TION AND SKIN DEFATTING. Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid:EYE:FLUSH WITH WATER FOR @ LEAST 15 MINUTES. CONTACT PHYSICIAN. SKIN: CLEAN WITH RUBBING ALCOHOL, IF AVAILABLE, FOLLOWED BY SOAP AND WATER. INHAL: REMOVE TO FRESH AIR. ADMINISTER OXYGEN OR ARTIFICIAL RE SPIRATION, IF NECESSARY. CONTACT PHYSICIAN. INGEST: CONTACT PHYSICIAN. Flash Point Method:CC Flash Point:-7F,-22C

Lower Limits:1.4% Upper Limits:7.6% Extinguishing Media:FOAM, CO\*2, DRY CHEMICAL. Fire Fighting Procedures:NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP . USE WATER SPRAY TO COOL ADJACENT SURF & EXPOS CNTNRS ONLY. PROTECT AGAINST INHAL OF COMBUSTION PRODUCTS. Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID

Spill Release Procedures:REMOVE IGNITION SOURCES. ABSORB ON INERT MATERIAL. USE NOM-SPARKING TOOLS. TRANSFER INTO SECURE CONTAINERS FOR PROPER DISPOSAL. USE PERSONAL PROTECTIVE QUIPMENT AS OUTLINED ABOVE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: AVOID ALL PERSONAL CONTACT. STORE AND USE AWAY FROM A

Waste Disposal Methods: AS A HAZARDOUS WASTE I/A/W EPA/RCRA REGS 40CFR 261.21

## (A) (1) IGNITABILITY:D001. DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.