View NSN Online: https://aerobasegroup.com/nsn/2640-00-922-6917 BARNES/ADAMS PSP INC. -- ADHESIVE 1599 -- 2640-00-922-6917 ============= Product Identification ======================== Product ID:ADHESIVE 1599

MSDS Date:10/01/1993

FSC:2640

NIIN:00-922-6917

MSDS Number: BYXKH === Responsible Party ===

Company Name: BARNES/ADAMS PSP INC.

Box:189 City:BUTLER State:PA

ZIP:16003-0189 Country:US

Info Phone Num:412-287-6711

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:MO235 === Contractor I dentification ===

Company Name: ADAMS PSP INC Address:355 UNIONVILLE RD

Box:City:BUTLER

State:PA ZIP:16003 Country:US CAGE:17705

Company Name: BARNES/ADAMS PSP INC.

Box:189 City:BUTLER State:PA

ZIP:16003-0189 Country:US

Phone:412-287-6711

CAGE:MO235

Company Name: PEMCO ADHESIVES Address:29542 MANCHESTER DR

City:ELKHART

State:IN

ZIP:46514-5000 Country:US

Phone:219-295-8384

CAGE:PEMCO

======= Composition/Information on Ingredients ========

Ingred Name: NAPHTHA, RUBBER SOLVENT

CAS:64742-

89-8

Other REC Limits: NONE RECOMMENDED

OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name: TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2 ACGIH TLV:S, 50 PPM; 9495

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: MAY CAUSE DIZZINESS, NAUSEA, VOMITING. CHRONIC: HEXANE CAN PRODUCE PERIPHERAL POLYNEUROPATHY, A PROGRESSIVE NERVOUS SYSTEM DISORDER.

Explanation of Carcinogenicity:NONE

Effects of Overexposure: DIZZINESS, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure: SENSITIVE SKIN CAN BE IRRITATED.

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN: REMOV

E CONTAMINATED CLOTHING. WASH AREA WITH SOAP

AND WATER. INHALATION: MOVE TO FRESH AIR. GIVE CPR IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM. GET MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:-4F,-20C Lower Limits:1.2 Upper Limits:6.8

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures: USE AIR SUPPLIED RESCUE EQUIPMENT FO

R ENCLOSED
AREAS. COOL FIRE EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE FROM HOT METAL
SURFACES AND OTHER SOURCES OF IGNITION.
========= Accidental Release Measures ===========
Spill Release Procedures:SMALL SPILL: ABSORB LIQUID WITH SAWDUST OR
FLOOR ABSORBENT. TAKE WET ABSORBENT TO HOOD. LARGE SPILL: ELIMINATE
ALL IGNITION SOURCES, ABSORB LIQUID WITH ABSORBENT, TRANSFER
ABSORBENT TO A CONTAINER FOR DISPOSAL. Neutrali
zing Agent:NONE SPECIFIED BY MANUFACTURER.
Zing Agentitote of Lon ILD DT WATON ACTORER.
======================================
Handling and Storage Precautions:STORE IN A COOL AREA. KEEP CONTAINERS
CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT, SPARKS, OR FLAMES.
Other Precautions: USE IN WELL VENTILATED AREAS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection: USE ORGANIC VAPOR MASK IF EXPOSURE EXCEEDS TLV/PEL'S.
Ventilation:PROVIDE SUFFICIENT VENTILATION TO MAI
NTAIN AIRBORNE
CONCENTRATIONS BELOW THE EXPOSURE GUIDELINE.
Protective Gloves:PROTECTIVE RUBBER GLOVES RECOMMENDED.
Eye Protection: USE SAFETY GOGGLES.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health
KEY1:F2. THIS ITEM IS PART OF A PUNCTURE REPAIR KIT.
========= Physical/Chemical Properties ==========
HCC:F2
Boiling Pt:B.P. Text:107F,42C
Vapor Pres:180 Vapor Density:>1
Spec Gravity:0.71
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK LIQUID. AROMATIC AND PUNGENT ODOR.
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDANTS SUCH AS LIQUID CHLORINE.
Stability Condition to Avoid:HEAT, SPARKS, FLAME, HOT METAL SURFACES,

OTHER SOURCES OF IGNITION.
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MO

NOXIDE.	
Conditions to Avoid Polymerization: WILL No	OT OCCUR

====== Disposal Considerations ==========

Waste Disposal Methods:SMALL SPILL: ALLOW TO EVAPORATE IN A HOOD OR OUTDOORS. LARGE SPILL: DEPOSIT IN LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no man ner whatsoever.

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.