

EASTMAN KODAK COMPANY, EASTERN REGIONAL DIST. CTR. -- 834 5928 HX TONER, RED --
6850-01-387-6657

===== Product Identification =====

Product ID:834 5928 HX TONER, RED

MSDS Date:06/11/1997

FSC:6850

NIIN:01-387-6657

MSDS Number: BYXLP

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY, EASTERN REGIONAL DIST. CTR.

Address:1187 W RIDGE RD

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Pho

ne Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information on Ingredient

S =====

Ingred Name:STYRENE ACRYLATE COPOLYMER
CAS:60806-47-5
Fraction by Wt: 85-90%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ACRYLIC ACID BUTYL ESTER POLYMER WITH STYRENE
CAS:25767-47-9
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:RED AZO PIGMENT
CAS:7023-61-2
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation: YES Skin: NO Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: INHAL: EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN: EXPECTED TO BE LOW HAZARD FOR RECOMMENDED HANDLING. INGEST: EXPECTED TO BE LOW INGESTION HAZARD.
Explanation of Carcinogenicity: PER MSDS: CARCINOGENICITY CLASSIFICATION: IARC/ACGIH/NTP/OSHA: NONE.
Effects of Overexposure: TRANSIENT EYE IRRITATION.
Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid: INHAL: IF SYMPTOMATIC MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MED ATTN IF SYMPTOMS PERSIST. EYES: ANY MATERIAL THAT CONTACTS EYE SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. GET MED ATTN IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP & WATER. GET MED ATTN IF SYMPTOMS OCCUR. INGEST: DRINK 1-2 GLASSES OF WATER. SEEK MED ATTN. NEVER GIVE ANYTHING BY MOUTH.

UTH TO UNCONSC PERSON.

=====
Fire Fighting Measures =====

Autoignition Temp:Autoignition Temp Text:NP

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), DRY CHEMICAL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE DUST-AIR MIXTURES. COMBUSTIBLE SOLID.

=====
Accidental Release Measures =====

Spill Release Procedures:DONT USE VACUUM CLEANER TO CLEAN UP SPILL OF POWDERED TONERS.THE VERY FNE PARTICLES CAN CAUSE FIRE OR EXPLOSION.SWEEP MATL ONTO PAPER & PLACE IN FIBER CARTON.AVOID GENERATION OF DUST.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage =====

Handling and Storage Precautions:AVOID BREATH DUST.USE W/ADEQU VENTILATION.POWDERED MATL MAY FORM EXPLO DUST-AIR MIXTURES.KEEP

AWAY FROM SOURCES OF IGN.MIN DUST GENERATION/ACCUMULATIO

Other Precautions:REF:NFPA PAMPHLET#654:"PREVENTION OF FIRE/DUST EXPLO IN CHEM/DYE/PAHRMACEUTICAL/PLAST INDUSTRIES".KEEP FROM CONTACT W/OXIDIZING MATLS.KEEP CNTNR CLSD.MATL HASNT BEEN TESTED FOR ENVIRO EFFECTS.IN SPILL SITUATION MATL MAY BE VISUALLY (SUPPLE)

=====
Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VE

NTILATION (TYPICALLY 4-6 ROOM VOL/HR) SHOULD

BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS.

Protective Gloves:IMPERVIOUS GLOVES FOR PROL/REP CONTACT

Eye Protection:GOOD INDUSTRIAL HYG PRACTICES-MIN CONTAC

Other Protective Equipment:WASHING FACILITIES.

Work Hygienic Practices:WASH THOROUGHLY AFT HNDLG.

Supplemental Safety and Health

OTHER PRECAUT:UNPLEASANT;HOWEVER ITS NOT EXPECTED TO CAUSE ANY ADVERSE ENVIRO EFFECTS.

=====
Physical/Chemical Properties =====

=====

HCC:N1

Boiling Pt:B.P. Text:NP

Melt/Freeze Pt:M.P/F.P Text:N/AVAI

Decomp Temp:Decomp Text:NP

Vapor Pres:NEGLIGIBLE

Vapor Density:NEGLIGIBLE

Spec Gravity:N/AVAI

pH:NA

Viscosity:NP

Evaporation Rate & Reference:NP

Solubility in Water:NEGLIGIBLE

Appearance and Odor:SOLID (POWDER), RED COLOR, SLIGHT ODOR

Percent Volatiles by Volume:NEGLIG

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING

AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR LANDIFLL.CAN BE INCINERATED WHEN
IN COMPLIANCE W/LOC REGS.DISCHARGE/TREATMENT/DISPO MAY BE SUBJ TO
NATIONAL/STATE/LOC LAWS.CHEM SUBJ TO REPORTING REQMTS OF SEC 313
TITLE III SARA/40CFR37 2:NONE.

Disclaimer (provided with this information by the
compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.