View NSN Online: https://aerobasegroup.com/nsn/8010-01-333-7762

Product ID:TT-E-2784 MSDS Date:08/01/1995 FSC:8010 NIIN:01-333-7762 MSDS Number: BYYKD === Responsible Party === Company Name: DEL PAINT CORP. Address:3105 E. RENO City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Info Phone Num:405-672-1431/FAX 405-672-0804 Emergency Phone Num:800-424-9300 24 HRS Preparer's Name:ON **EY FLEMING** CAGE: JO954 === Contractor Identification === Company Name: DEL PAINT CORP. Address:3105 E. RENO City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone:405-672-1431/FAX 405-672-0804 CAGE:JO954 Company Name: DEL PAINT MFG Address:3105 EAST RENO Box:City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone:405-672-1431 CAGE:39934

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

====== Hazards Iden

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CAN CAUSE IRRITATION OF RESPIRATORY PASSAGES.

Effects of Overexposure:INHALATION OF VAPOR/MIST CAN CAUSE HEADACHES, NAUSEA, IRRITATION OF NOSE/THROAT/LUNGS. EYES: CAN CAUSE SLIGHT IRRITATION. CHRONIC SKIN CONTACT CAN CAUSE SLIGHT IRRITATION. Medical Cond Aggravated by Exposure:PREEXISTING LUNG DISEASE MAY BE

AGGRAVATED BY EXPOSURE.

First Aid:EYES: FLUSH W/LARGE AMTS WATER 15 MINUTES. CONSULT DR. IF IRRITATION PERSISTS. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. INGESTION: GIVE 2 GLASSES WATER. CONSULT DR.

Flash Point Method:SCC Flash Point:>212F,>100C Lower Limits:NA **Upper Limits:NA** Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG. Fire Fighting Procedures:WEAR SCBA (PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) & FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard: MATERIAL CAN SPLATTER ABOVE 212F/100C. POLYMER FILM CAN BURN. Spill Release Procedures: KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY. USE CARE TO AVOID FALLING. CONTAIN W/INERT MAT'L (SAND/EARTH). TRANSFER LIQ/SOLID DIKING MAT'L TO SEPARATE SUITABLE CONTAINERS FOR **RECOVERY/DISPOSAL.** Neutralizing Agent:NONE

Handling and Storage Precautions: KEEP FROM FREEZING. DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER-SPRAY DURING SPRAY APPLICATION. Ventilation:NORMAL, SUCH AS FAN. Protective Gloves:RUBBER Eye Prot ection:SAFETY GLASSES OR GOGGLES. Other Protective Equipment:EYEWASH STATION. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:212 TO 644F Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C Decomp Temp:Decomp Text:350F,177C Vapor Pres:NONE Vapor Density:>AIR Spec Gravity:1.15 pH:9 MAX Viscosity:77-95 KU Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:SLIGHT Appearance and Odor:WHITE LIQUID, SLIGHT ODOR Percen t Volatiles by Volume:60.6

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NONE Hazardous Decomposition Products:ACRYLIC MONOMERS

Waste Disposal Methods:KEEP SPILLS/CLEANING RUN-OFF OUT OF SEWERS & OPEN BODIES OF WATER. CONSULT FEDERAL/STATE/LOCAL AUTHORITIES FOR PROPER DISPOSAL PROCEDURES CONCERNING HEALTH & ENVIRO NMENT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.