

Product ID:TT-E-2784 MSDS Date:08/01/1995 FSC:8010 NIIN:01-333-9821 MSDS Number: BYYLK === Responsible Party === Company Name:DEL PAINT MFG CORP Address:3105 E RENO AVE City:OKLAHOMA CITY State:OK ZIP:73117-6699 Country:US Info Phone Num:800-866-6823 Emergency Phone Num:800-866-6823 Preparer's Name:ONEY FLEMING

CAGE:EO310 === Contractor Identification === Company Name: DEL PAINT MFG Address:3105 EAST RENO Box:City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone:405-672-1431 CAGE:39934 Company Name: DEL PAINT MFG CORP Address:3105 E RENO AVE City:OKLAHOMA CITY State:OK ZIP:73117-6699 Country:US Phone:405-672-1431 CAGE:EO310

Ingred Name:PROPYLENE GLYCOL CAS:57-55-6 RTECS #:TY2000000 Fraction by Wt: 3.72% Other REC Limits:NONE RECOMME

NDED

Ingred Name:2,2,4-TRIMETHYL-1-3-PENTANEDIOL MONOISOBUTYRATE CAS:25265-77-4 RTECS #:UF6000000 Fraction by Wt: 3.43% Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYLAMINOETHANOL LOW VOC CAS:108-01-0 RTECS #:KK6125000 Fraction by Wt: 0.22% Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE CAS:26530-20-1 Fraction by Wt: 0.18% Other REC Limits:NONE RECOMMENDED

Ingred Name:NON HAZARDOUS INGREDIENTS Fraction by Wt: 92.45% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CAN CAUSE IRRITATION OF RESPIRATORY PASSAGES.

Effects of Overexposure:INHALATION OF VAPOR/MIST CAN CAUSE HEADACHES, NAUSEA, IRRITATION OF NOSE/THROAT/LUNGS. EYES: CAN CAUSE SLIGHT IRRITATION. CHRONIC SKIN CONTACT CAN CAUSE SLIGHT IRRITA TION.

Medical Cond Aggravated by Exposure:PREEXISTING LUNG DISEASE MAY BE AGGRAVATED BY EXPOSURE.

First Aid:EYES: FLUSH W/LARGE AMTS WATER 15 MINUTES. CONSULT DR. IF IRRITATION PERSISTS. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. INGESTION: GIVE 2 GLASSES WATER. CONSULT DR.

Flash Point Method:SCC Flash Point:>212F,>100C Lower Limits:NA

Upper Limits:NA Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG. Fire Fighting Procedures: WEAR SCBA (PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) & FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard: MATERIAL CAN SPLATTER ABOVE 212F/100C. POLYMER FILM CAN BURN. Spill Release Procedures: KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY. USE CARE TO AVOID FALLING. CONTAIN W/INERT MAT'L (SAND/EAR TH). TRANSFER LIQ/SOLID DIKING MAT'L TO SEPARATE SUITABLE CONTAINERS FOR **RECOVERY/DISPOSAL.** Neutralizing Agent:NONE Handling and Storage Precautions: KEEP FROM FREEZING. DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN. Respiratory Protection: APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER-SPRAY DURING SPRAY APP LICATION. Ventilation:NORMAL, SUCH AS FAN. Protective Gloves: RUBBER Eye Protection: SAFETY GLASSES OR GOGGLES. Other Protective Equipment: EYEWASH STATION. Supplemental Safety and Health NK HCC:N1 Boiling Pt:B.P. Text:212 TO 644F Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C Decomp Temp:Decomp Text:350F,177C Vapor Pres:NONE Vapor Density:>AIR Spec Gravity:1.14 VOC Pounds/Gallon:191 pH:9 MAX VOC Grams/Liter:1.59 Viscosity:77-95 KU Evap

oration Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:SLIGHT Appearance and Odor:BLUE LIQUID, SLIGHT ODOR Percent Volatiles by Volume:60.6

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NONE Hazardous Decomposition Products:ACRYLIC MONOMERS

Waste Disposal Methods: KEEP SPILLS/CLEANING RUN-OFF OUT OF SEWERS &

OPEN BODIES OF WATER. CONSULT FEDERAL/STATE/LOCAL AUTHORITIES FOR PROPER DISPOSAL PROCEDURES CONCERNING HEALTH & ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek co mpetent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.