View NSN Online: https://aerobasegroup.com/nsn/8030-01-393-9284

Product ID:PR1425 B-2 (1425B16) ACCELERATOR MSDS Date:10/27/1993 FSC:8030 NIIN:01-393-9284 Kit Part:Y MSDS Number: BYYZD === Responsible Party === Company Name: COURTAULDS AEROSPACE, INC Address:5430 SAN FERNANDO RD. Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info Phone Nu m:818-240-2060 Emergency Phone Num:800-424-9300 (CHEMTREC) CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574

Ingred Name:CALCIUM DICHROMATE (SARA 313) CAS:14307-33-6 RTECS #:HX7630000 Fraction by Wt: 25% Other REC Limits:NK \*\*(AS CR 03) OSHA PEL:STEL 0 .1 MG/M3\*\*

Ingred Name:DIMETHYL ACETAMIDE (VP = 2 MMHG) CAS:127-19-5 RTECS #:AB7700000 Fraction by Wt: 10% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM SKIN ACGIH TLV:10 PPM SKIN

Ingred Name:SILICA FUMED (AIRBORNE CONTAMINANT, FULLY ENCAPSULATED) CAS:112945-52-5 Fraction by Wt: 200F,>93C Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG. Fire Fighting Procedures:USE COMPLETE PERSONAL PROTECTION.

======= Exposure Controls/Personal Protection ==========

Suppleme ntal Safety and Health

Boiling Pt:B.P. Text:212 TO 331F Vapor Density:>AIR Spec Gravity:1.411 Appearance and Odor:BLACK PASTE Percent Volatiles by Volume:73

Stability Indicator/Materials to Avoid:YES EASILY OXIDIZABLE MATERIALS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of th

e Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.