

MAINTEX INC. -- SHOWER, TUB & TILE (HARD WATER/SCUM REMOVER) -- 7930-01-398-0856

=====
Product Identification
=====

Product ID:SHOWER, TUB & TILE (HARD WATER/SCUM REMOVER)

MSDS Date:06/11/1994

FSC:7930

NIIN:01-398-0856

MSDS Number: BYZBR

=== Responsible Party ===

Company Name:MAINTEX INC.

Address:13300 NELSON AVE.

City:CITY OF INDUSTRY

State:CA

ZIP:91746

Country:US

Info Phone Num:818-961-1988

Eme

Agency Phone Num:800-255-3924 (CHEMTEL)

Preparer's Name:ALI ABYANE

CAGE:NO277

=== Contractor Identification ===

Company Name:MAINTEX INC

Address:13300 NELSON AVE

Box:City:CITY OF INDUSTRY

State:CA

ZIP:91746

Country:US

Phone:818-961-1988

CAGE:0PWJ2

Company Name:MAINTEX INC.

Address:3614 EL MONTE AVE

Box:City:EL MONTE

State:CA

ZIP:91731

Phone:213-283-7380

CAGE:NO277

=====
Composition/Information on Ingredients
=====

Ingred Name:GLYCOLIC ACID

CAS:79-14-1

Fraction by Wt: 15-20%

O

ther REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:NOT EST.

Ingred Name:VOC = 4%
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:NOT EST.

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRIT. DAMAGE W/BRIEF CONTACT
LIQUIDS/MISTS. POS PERM INJURY W/EXTENDED CONTACT. SKIN: IRRIT BY
VAPORS. VAPOR/LIQ/MISTS CORROSIVE. INHAL: IRRIT/BURNS W/EXTENDED
CONTACT. INGEST: BURNS TISSUES. C HRONIC-SKIN: ALLERGIC REACTIONS
W/OVEREXPOSURE.
Effects of Overexposure:INGEST: ABDOMINAL PAIN, NAUSEA, VOMITING. EYES:
STINGING, WATERING.
Medical Cond Aggravated by Exposure:INHALATION/INGESTION: POSSIBLE
AGGRAVATION OF PREEXISTING LUNG DISEASE.

=====
===== First Aid Measures =====

First Aid:EYES: REMOVE CONTACTS. IMMEDIATELY FLUSH W/LOTS WATE
R >15
MINUTES. CALL DR. SKIN: WASH W/SOAP & WATER. INHALATION: IF
DISCOMFORT, GET FRESH AIR. IF BREATHING DIFFICULT, IMMEDIATELY GET
MEDICAL AID. IN GESTION: GET PLENTY WATER. DO NOT INDUCE VOMITING.
WASH OUT MOUTH AREA. CALL DR.

=====
===== Fire Fighting Measures =====

Flash Point:>250F,>121C
Extinguishing Media:WATER SPRAY, FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:POSITIVE PRESSURE SCBA W/FULL FACEPIECE FOR
FIREFIGHTERS.
Unusual Fire/E

xplosion Hazard:USE WATER FOG/SPRAY TO COOL/LOWER
PRESSURE OF FIRE-EXPOSED CONTAINERS, TO FLUSH VAPORS AWAY.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL: MOP/RINSE AREA. LG, >55 GL: WEAR RUBBER
BOOTS, GLOVES, APPROPRIATE PROTECTIVE CLOTHES. SHUT OFF LEAK IF
SAFE. DIKE/CONTAIN. TRANSFER LIQ TO PLASTIC DRUMS/CONTAINERS FOR
RECOVERY/DISPOSAL.

===== Handling and Storage =====

Handling and St

orage Precautions:KEEP AWAY FROM CHILDREN. DO NOT GET
IN/ON EYES, SKIN, CLOTHES. DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED IF PROPERLY DILUTED.

Protective Gloves:RUBBER - DECREASES DRYNESS OF SKIN.

Eye Protection:CHEM SPLASH GLASSES/FACE SHIELD ADVISED*

Other Protective Equipment:*ESPECIALLY W/CONCENTRATE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

===

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:>32F,>0C

Vapor Pres:1

Spec Gravity:1.08

pH:1-2

Evaporation Rate & Reference: