

BIOMERIEUX VITEK INC -- 26210 BAC-T-SCREEN KIT-URINE DILUENT -- 6550-01-267-2473

=====
Product Identification
=====

Product ID:26210 BAC-T-SCREEN KIT-URINE DILUENT

MSDS Date:07/01/1993

FSC:6550

NIIN:01-267-2473

Kit Part:Y

MSDS Number: BZFZT

=== Responsible Party ===

Company Name:BIOMERIEUX VITEK INC

Address:595 ANGLUM DRIVE

City:HAZELWOOD

State:MO

ZIP:63042-5000

Country:US

Info Phone Num:800-638-

4835/314-854-0344

Emergency Phone Num:314-854-0344/800-638-4835

CAGE:0Z9R8

=== Contractor Identification ===

Company Name:BIOMERIEUX VITEK INC

Address:595 ANGLUM

Box:City:HAZELWOOD

State:MO

ZIP:63042-5000

Country:US

Phone:800-638-4835/314-854-0344

CAGE:0Z9R8

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETIC ACID (GLACIAL)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 14.5%

OSHA PEL:10 PPM

ACGIH TLV:10 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====

===== **Hazards Identification**=====

LD50 LC50 Mixture:ORAL LD50(RAT): 3310 MG/KG ACETIC ACID

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACETIC ACID-INHALATION: MAY CAUSE IRRITATION TO THE MUCOUS MEMBRANES, RESPIRATORY TRACT & BURNING OF THE NOSE & THROAT. SKIN: IRRITATION & DERMATITIS. EYES: MODERATE TO SEVERE IRRIATION. INGESTION: IR RITATION TO THE MOUTH & GI TRACT.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:ACETIC ACID: IRRITATION, SNEEZING, COUGHING, BURNING, NAUSEA, VOMITING, ABDOMINAL PAIN.

Medical Cond Aggravated by Exposure:INDIVIDUALS W/PRE-EXISTING RESPIRATORY &/SKIN DISEASE.

===== **First Aid Measures**=====

First Aid:INHALATION: IMMEDIATELY REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEEDED. SKIN: FLUSH AREA W/LARGE AMOUNTS OF WATER. EYES: IMMEDIATELY FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS/CONVULSING PERSON. IF CONSCIOUS, RINSE MOUTH W/WATER/MILK. GIVE 4-8 OUNCES OF MILK/WATER TO DILUTE. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== **Fire Fighting Measures**=====

Flash Point:NONE

Lower Limits:(SEE SUPP)

Upper Limits:(SEE SUPP)

Extinguishing Media:DRY CHEMICAL, CO2, WATER SPRAY/REGULAR FOAM

Fire Fighting Procedures:WEAR POSITIVE PRESSURE SCBA & FULL PROTECTIVE

CLOTHING. COOL EXPOSED CONTAINERS W/WATER.

Unusual Fire/Explosion Hazard:GLACIAL ACETIC ACID IS COMBUSTIBLE.

ACETIC ACID VAPORS CAN FORM EXPLOSIVE MIXTURES W/AIR. EXPOSURE TO

HEAT INCREASES THE EVOLUTION OF TOXIC & CORROSIVE VAPORS.

===== **Accidental Release Measures**=====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES, RESPIRATOR, SUIT, CHEMICAL GOGGLES & FACESHIELD. COLLECT MATERIAL W/SAND/OTHER NON-COMBUS

TIBLE ABSORBENT MATERIAL & PLACE IN CLOSABLE CONTAINER
FOR DISPOSAL. WASH ARE A W/WATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AT TEMP 59-86F, AWAY FROM
INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED. USE W/ADEQUATE
VENTILATION.

Other Precautions:AVOID CONTACT W/EYES, SKIN & CLOTHING. AVOID
BREATHING VAPORS/MISTS. DON'T BREATHE GAS/FUMES/VAPOR/SPRAY. KEEP
OUT OF REACH OF CHILDREN. DON'T WEAR CONTACT LENSES

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:A FULL FACEPIECE RESPIRATOR W/ORGANIC VAPOR
CARTRIDGES. A GAS MASK W/AN ORGANIC VAPOR CANISTER. A SUPPLIED AIR
RESPIRATOR W/A FULL FACEPIECE OPERATED IN CONTINUOUS FLOW MODE. A
POSITIVE PRESSURE SCBA.

Ventilation:SUFFICIENT GENERAL/LOCAL EXHAUST TO MAINTAIN EXPOSURES
BELOW EXPOSURE LIMITS.

Protective Gloves:IMPERVIOUS/BUTYL RUBBER/TEFLON/SARANEX

Eye Protection:CHEMICAL SAFETY GOGGLES

Ot

her Protective Equipment:IMPERVIOUS CLOTHING & FOOTWEAR, EYE WASH
FOUNTAIN & QUICK DRENCH SAFETY SHOWER.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE. WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

VAPOR DENSITY: 2.1 (ACETIC ACID), FLAMMABLE LIMITS: LEL: 5.4 (ACETIC
ACID), UEL: 16 (ACETIC ACID).

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:>212F

Melt/Freeze Pt:M.P/F.P Text:99

=====
= Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

ALKALIES, OXIDIZERS, CARBONATES, OXIDES, PHOSPHATES, ACETIC ANHYDRIDE.

Stability Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:THERMAL: ACETIC ACID VAPORS, CO, CO2.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL
REGULATIONS. EMPTY CONTAINERS SHOULD BE COLLECTED FOR PROPER
DISPOSAL. CORROSIV

E UN2790.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.