

ULTRA COATINGS INC -- UC-40 SAFE STRIP 845 - 100 -- 6850-01-386-8424
===== Product Identification =====

Product ID:UC-40 SAFE STRIP 845 - 100

MSDS Date:08/01/1993

FSC:6850

NIIN:01-386-8424

Kit Part:Y

MSDS Number: BZGDF

=== Responsible Party ===

Company Name:ULTRA COATINGS INC

Address:1146 NW 52ND

City:SEATTLE

State:WA

ZIP:98107-5129

Country:US

Info Phone Num:206-781-7117

Emergency Phone Num:206-7
81-7117

CAGE:ULTTR

=== Contractor Identification ===

Company Name:ULTRA COATINGS INC

Address:1146 NW 52ND

City:SEATTLE

State:WA

ZIP:98107-5129

Country:US

Phone:206-781-7117

CAGE:ULTTR

===== Composition/Information on Ingredients =====

Ingred Name:2-BUTOXYETHANOL (ETHYLENE GLYCOL MONOBUTYL ETHER), BUTYL
CELLOSOLVE, BUTYL GLYCOL, GLYCOL ETHER EB * 96-1 *

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 15%

Other REC Limits:25 PPM (SKIN)

OSHA PEL:50 PPM (SKIN)

ACGIH TLV:25 PP

M (SKIN)

Ingred Name:ETHYL 3-ETHOXYPROPIONATE, PROPANOIC ACID, 3-ETHOXY-, ETHYL
ESTER

CAS:763-69-9

RTECS #:UF3325000

Fraction by Wt: 10-30%

Ingred Name:N-METHYL-2-PYRROLIDONE * 96-1 *

CAS:872-50-4

RTECS #:UY5790000

Fraction by Wt: 10-30%

Ingred Name:DIMETHYL GLUTARATE *96-1*

CAS:1119-40-0

Fraction by Wt: 10-20%

Ingred Name:DIMETHYL ADIPATE, METHYL ADIPATE, HEXANEDIOIC ACID DIMETHYL
ESTER

CAS:627-93-0

RTECS #:AV1645000

Fraction by Wt: 1-5%

Ingred Name:DIMETHYL SUCCINATE, DIMETH
YL BUTANEDIOATE, BUTANEDIOIC
ACID, DIMETHYL ESTER

CAS:106-65-0

RTECS #:WM7675000

Fraction by Wt: 1-5%

Other REC Limits:10 MG/CUM

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: MODERATE IRRITATION. INHALATION:
RESPIRATORY IRRITATION. INGESTION: GI IRRITATION & MODERATELY
TOXIC. SKIN: PROLONGED/REPEATED CONTACT MAY

CAUSE IRRITATION,

DERMATITIS. 2-BUTOXYETHANOL IS READIL Y ABSORBED THROUGH SKIN
CONTACT, MAY CAUSE BLOOD EFFECTS & INJURY TO LIVER & KIDNEY.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, BLURRED VISION, REDNESS, HEADACHE,
NAUSEA, DIZZINESS, GI IRRITATION, VOMITING, DIARRHEA.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: WASH
W/MILD SOAP & WATER. INHALATION: REMOVE

TO FRESH AIR. GIVE OXYGEN

IF NEEDED. INGESTION: GIVE 2 GLASSES OF WATER & INDUCE VOMITING BY STICKI NG FINGER DOWN THROAT. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>200F

Extinguishing Media:CO2, FOAM, DRY CHEMICALS

Fire Fighting Procedures:USE WATER FOG TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:NEVER USE WELDING

/CUTTING TORCH ON/NEAR

DRUM, EVEN EMPTY.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. VENTILATE AREA.

ABSORB ON SOLID ABSORBENT & SHOVEL INTO CONTAINERS. FLUSH W/WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BETWEEN 40-120F. NEVER USE WELDING/CUTTING TORCH ON/NEAR DRUM, EVEN EMPTY.

Other Precautions:AVOID BREATHING SPRAY MISTS.

=====

= Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH/MSHA APPROVED RESPIRATOR IF TLVS ARE EXCEEDED.

Ventilation:GENERAL &/LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:BUTYL RUBBER

Eye Protection:GOGGLES

Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212-350F

Melt/Freeze Pt:M.P/F.P

Text: