View NSN Online: https://aerobasegroup.com/nsn/8030-00-180-6339

RED DEVIL INC -- INDOOR-OUTDOOR SILICONE SEALANT -- 8030-00-180-6339

Product ID: INDOOR-OUTDOOR SILICONE SEALANT

MSDS Date:01/01/1987

FSC:8030

NIIN:00-180-6339

MSDS Number: BZHVV === Responsible Party === Company Name: RED DEVIL INC

Address: ONE WEBB ST

City:PRYOR State:OK ZIP:74361 Country:US

Info Phone Num:918-825-5744

Emergency Phone Num:918-825-5744

CAGE:23577

=== Contractor Identification ===

Company Name: RED DEVIL, INCORPORATED

Address: ONE WEBB STREET

Box:A

City:PRYOR State:OK ZIP:74361 Country:US

Phone:918-825-5744

CAGE:23577

======= Composition/Information on Ingredients ========

Ingred Name: AMORPHOUS SILICA

CAS:68855-54-9

Fraction by Wt: 100.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:20 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: ETHYL TRIACETOXYSILANE Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name

ACGIH ILV:NOT EST.
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE, NOSE, THROAT IRRITATION. POSSIBLE SKIN IRRITATION.
======================================
First Aid:EYES: IMMEDIATELY FLUSH W/LARGE AMOUNTS W ATER HOLDING EYELIDS OPEN. GET MEDICAL AID IF IRRITATION PERSISTS. SKIN: WIPE MATERIAL FROM SKIN W/CLOTH OR PAPER TOWEL, THEN WASH EXPOSED AREA W/SOAP & WATER. GET MEDICAL AID IF IRRIT PERSISTS. INHALATION: MOVE TO FRESH AIR. GET MED AID IF IRRIT PERSISTS. INGESTION: CONTACT POISON CONTROL/DR. IMMEDIATELY.
======================================
Flash Point:>200F,>93C; NK
========= Accidental Release Measures ==========
Spi II Release Procedures:WEAR PERSONAL PROTECTIVE EQUIPMENT. CLEAN UP W/ABSORBENT MATERIAL.
========== Handling and Storage ===========
Handling and Storage Precautions:STORE IN CLOSED CONTAINER IN DRY AREA. SON'T WEAR CONTACTS WHILE APPLYING THIS MAT'L AS ACETIC ACID VAPOR MAY BECOME TRAPPED UNDER LENSES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT NORMALLY REQUIRED Ventilation:LOCAL EXHAUST MAY BE NECESSARY

:TITANIUM DIOXIDE. CAS:13463-67-7

OSHA PEL:15 MG/M3

Other REC Limits:NONE RECOMMENDED

Protective Gloves:NOT NORMALLY REQUIRED. Eye Protection:SAFETY GLASSES Supplemental Safety and Health NK
========= Physical/Chemical Properties =========
HCC:N1
======== Stability and Reactivity Data =========
Hazardous Decomposition Products:SILICONE DIOXIDE, CARBON MONOXIDE, CARBON DIOXIDE, FORMALDEHYDE.
======= Disposal Considerations ==========
Waste Disposal Methods:IN ACCORDANCE W /FEDERAL, STATE, LOCAL REGULATIONS.

UNDER SOME HANDLING

CONDITIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.