View NSN Online: https://aerobasegroup.com/nsn/9150-00-149-7432 VELSICOL CHEMICAL CORP -- MIL-H-83282C -- 9150-00-149-7432 ============= Product Identification ======================== Product ID:MIL-H-83282C MSDS Date:12/01/1995 FSC:9150 NIIN:00-149-7432 MSDS Number: BZJDK === Responsible Party === Company Name: VELSICOL CHEMICAL CORP Address:10400 W HIGGINS SUITE 600 City:ROSEMONT State:IL ZIP:60018-3713 Country:US Info Phone Num:708-298-9000 708-298-9014(FAX) Emergency Phone Num:70 8-298-9000 Preparer's Name: N.R. NETZEL **CAGE:VELSI** === Contractor Identification === Company Name: VELSICOL CHEMICAL CORPORATION Address:10400 W HIGGINS ROAD Box:City:ROSEMONT State:IL ZIP:60018 Country:US Phone:847-298-9000 CAGE:0Z6C4 Company Name: VELSICOL CHEMICAL CORPORATION CAGE:VELSI ======= Composition/Information on Ingredients ======== Ingred Name: SYNTHETIC HYDROCARBON Other REC Limits: NONE RECOMMENDED ============ Hazards Identification =================

LD5

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES:VAPORS FROM HEATING MAY CAUSE IRRITATION.SKIN:VAPORS FROM HEATING MAY CAUSE IRRITATION.INGEST:NOT REPORTED.INHAL:VAPORS FROM HEATING MAY CAUSE RESPIRATORY IRRITATION.
Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN. Effects o
f Overexposure:NONE SPECIFIED BY MANUFACTURER. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.CALL PHYSICIAN IF IRRITATION DEVELOPS.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.NOTE TO PH YSICIAN:TREAT SYMPTOMATICALLY.
======================================
Flash Point Method:COC Flash Point:410F,210C Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.AVOID SPREADING BURNING LIQUID WITH WATER STREAM. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MA Y PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.HEAT OF FIRE MAY CAUSE CONTAINERS TO BURST.
======== Accidental Release Measures =========
Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL.
============ Handling and Storage =============
Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY

0 LC50 Mixture:TLV FOR OIL MIST IS 5MG/M3

FROM STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions: AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPIATE FOR EXPOSURE OF CONCERN. Ventilation: NO SPECIAL REQUIREMENTS. Protective Gloves: IMPERMEABLE GLOVES Eye Protection: CHEMICAL SPLASH GOGGLES Other Protective Equipment: PROVIDE A LOCAL EYE WASH STATION **AND SAFETY** SHOWER. Work Hygienic Practices: WASH HANDS. SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK Supplemental Safety and Health NONE ======== Physical/Chemical Properties ===========

HCC:V6 Boiling Pt:B.P. Text:520F,271C Vapor Pres:1 Spec Gravity: