

POLYMERIC SYSTEMS, INC -- PSI-690 PRIMER -- 8040-01-116-7851

=====
Product Identification
=====

Product ID:PSI-690 PRIMER

MSDS Date:08/26/1993

FSC:8040

NIIN:01-116-7851

MSDS Number: BZLKD

=== Responsible Party ===

Company Name:POLYMERIC SYSTEMS, INC

Address:723 WHEATLAND ST

City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Info Phone Num:215-935-1170

Emergency Phone Num:215-935-1170

Preparer's Name

:ED CLUFF

CAGE:0KND3

=== Contractor Identification ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:723 WHEATLAND STREET

Box:City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Phone:610-935-1170

CAGE:0KND3

=====
Composition/Information on Ingredients
=====

Ingred Name:2-PENTANOL, 4-METHYL-; (METHYL ISOBUTYL CARBINOL)

CAS:108-11-2

RTECS #:SA7350000

Fraction by Wt: 93%

OSHA PEL:S, 25 PPM

ACGIH TLV:S,25 PPM/40STEL

Ingred Name:ETHYL POLYSILICATE

CAS:68412-37-3

Fraction by Wt: 5%

OS

HA PEL:N/K
ACGIH TLV:N/K

Ingred Name:POLY(BUTYLTITANATE); (BUTYL POLYTITANATE)
CAS:9022-96-2
Fraction by Wt: 1%
OSHA PEL:100 PPM
ACGIH TLV:S: 50 PPM CEILING

Ingred Name:VOLATILE ORGANIC COMPOUND:6.5 LB/GAL; 780 G/L
RTECS #:9999999VO
OSHA PEL:N/K
ACGIH TLV:N/K

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:SEVERE IRRITATION TO RESPIRATORY TRACT, PULMONARY EDEMA, EYE LACRIMATION, CORNEAL EDEMA; SKIN IRRITATION AND DERMATITIS. SYMPTOMS INCLUDE IRRITATION TO SKIN, EYES AND MUCOUS MEMBRANES. MAY CAUSE DISCOMFORT, TEARING, CHOKING OR BURNING SENSATION. CHRONIC:BRONCHITIS, LARYNGITIS, DERMATITIS; CONJUNCTIVITIS.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:SKIN OR EYE DISEASES.

=====
===== First Aid Measures =====
=====

First Aid:INGESTION:CALL MD IMMEDIATELY . INHALATION:REMOVE TO FRESH AIR. SKIN:WASH WITH SOAP AND WATER. EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:CC
Flash Point:>400F,>204C
Extinguishing Media:WATER SPRAY, CO*2, DRY CHEMICALS, FOAM, SAND.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT

QUIPMENT .

Unusual Fire/Explosion Hazard:TOXIC GASES AND AEROSOLS MAY BE PRODUCED BY COMBUSTION, E.G. CO AND SIO*2.

===== Accidental Release Measures =====

Spill Release Procedures:MATERIAL RELEASES ACETIC ACID ON EXPOS TO AIR. PROVIDE ADEQ VENT DURING CLEAN UP. WEAR PROPER PROT EQUIP IF HNDLG LG AMOUNTS. TRANSFER TO A WASTE CONTAINER. LET CURE TO SOLID RUBBER, ALLOWING ALL LIBE RATED ACETIC ACID TO DISSIPATE.

Neutralizing Agent:AQUEOUS SODIUM BICARB ONATE.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED SKIN CONTACT. LIBERATED ACETIC ACID VAPORS CAUSE IRRITATION TO SKIN, EYES AND BRONCHIAL TISSUES. DO NOT INGEST.

Other Precautions:DO NOT RUB EYES WHILE WORKING WITH SEALANT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF USED IN A CLOSED SPACE WHERE VENTILATION IS INADEQUATE USE A CHEMICAL CARTRIDGE RESPIRATOR WITH FULL FACE PIECE AND ORGANIC VAPOR CARTRIDGE(S) (MSHA/NIOSH APPROVED) TO PROTECT AGAINST ACETIC ACID V APORS.

Ventilation:RECOMMENDED 10 AIR CHANGES PER HOUR.

Protective Gloves:DISPOSABLE PLASTIC.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS(SUPDAT)

Other Protective Equipment:ANSI APPROVED EMERGENCY EYE WASH AND DELUGE SHOWER .

Work Hygienic Practices:WASH BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

EYE PROT:AND FULL LENGTH FACE SHIELD .

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:270F,132C

Melt/Freeze Pt:M.P/F.P Text:-130F,-90C

Vapor Pres:3.7 @ 20C

Vapor Density:3.5

Spec Gravity:0.80 (H*2O=1)

pH:7

Evaporation Rate & Reference:>1

Solubility in Water:98%

Appearance and Odor:COLORLESS LIQUID WITH A PLEASANT, SWEET ODOR.

Percent Volatiles by Volume:96

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID PROLONGED CONTACT WITH MOISTU

RE DURING STORAGE.

Stability Condition to Avoid:NOT APPLICABLE.

Hazardous Decomposition Products:ACETIC ACID FROM MOISTURE CONTACT. CO
AND VOLATILE ORGANICS AND SILICA AEROSOLS FROM THERMAL DEGRADATION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL
REGULATIONS . NOT AN EPA HAZARDOUS WASTE. DISPOSE OF IN ACCORDANCE
WITH APPROPRIATE GOVERNMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.