View NSN Online: https://aerobasegroup.com/nsn/6685-00-291-0991

## 

Product ID:MERCURY MSDS Date:04/03/1991 FSC:6685 NIIN:00-291-0991 MSDS Number: BZNRK === Responsible Party === Company Name: PALMER INSTRUMENTS INC Address:234 WEAVERVILLE HWY City:ASHEVILLE State:NC ZIP:28804 Country:US Info Phone Num:704-645-6059 Emergency Phone Num:704-645-6059 CAGE:23471 === Contractor Ide ntification === Company Name: PALMER INSTRUMENTS INC. Address:234 WEAVERVILLE HWY. Box:City:ASHEVILLE State:NC ZIP:28804 Country:US Phone:704-658-3131 CAGE:23471 Ingred Name: MERCURY (SARA 313) (CERCLA); (METALLIC MERCURY) (QUICKSILVER) CAS:7439-97-6 RTECS #:0V4550000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED OSHA PEL:C, 0.1 MG/M3; Z-2 ACGIH TLV:S,0.025 MG/M3; A4;96

=========

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ELEMENTAL HG,LIQ/VAP,TOXIC DUE TO LIQ SOLUBILITY,LACK OF CHARGE,MEMBRANE PERMEABILITY.INHAL 80%VAP DIFFUSE RAPIDLY THRU ALVEOLAR MEMBRANES INTO BLOOD,SYSTEMATICALLY TRANSP TO BODY TISSUE/BRAIN.HI VAP CONCEN EXPO FOR BRIEF PER CAUSE

PNEUITIS, CHEST

PAINS, DYSPNEA, COUGH, STOMATITIS, GINGIVITS, SALV. ABSORBED SLOWLY (SIGN/SYMP)

Effects of Overexposure:THRU SKIN.CHRONIC SYSM:CNS W/TREMORS,VAR NEUROPSYCHIATRIC DIST.GI UPTAKE OF HG LOW(5%).SKIN:IRRIT/SENS/NEUROTOXIN/NEPHROTOXIN.RED,IRRIT,SEN DERM,ABSORBED THRU INTACT SKIN CAUSING ANURIA.EYE:IRRIT,CORR ,CORNEAL INJURY/BURNS,VISUAL

DIST.INGEST:NEUROTOXIC/NEPHROTOXIC,VIOLENT PAIN,PROFUSE VOMIT,SEVER PURG,PERI VASCU (SUPPL)

Medical Cond Aggravated by Expos

ure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYE:FLUSH W/RUNNING WATER FOR 15MINS,INCLUDE UNDER EYELIDS. SKIN:REMOVE CONTAMIN CLOTH.WASH W/SOAP/WATER. INHAL:REMOVE TO FRESH AIR.RESTORE &/OR SUPPORT BREATH AS NEEDED.ADMIN OXY FOR CHEM PNEUMONITIS . INGEST:GASTRIC LAVAGE W/5%SOLN OF SODIUM FORMALDEHYDE SULFOXYLATE FOLLOW W/2%NAHCO2,FINALLY LEAVE 250CC OF SODIUM FORMALDEHYDE SULFOXYLATE IN STOMACH.GET MED AS SIST.

Extinguishing Media:DRY CHEM,CARBON DIOXIDE,WATER SPRAY,FOAM.LG FIRES:USE WATERSPRAY,FOG OR ALCOHOL FOAM.
Fire Fighting Procedures:FIREFIGHTING:MOVE CNTNRS FRM AREA IF POSSIBLE.COOL CNTNRS EXPO TO FLAMES W/WATER FRM SIDE TIL WELL AFT FIRE IS OUT.USE AGENTS SUITABLE FOR TYPE OF FIRE.
Unusual Fire/Explosion Hazard:USE WATER IN FLOODING AMTS AS FOG. AVOID BREATHING CORROSIVE & POISONOUS VAPORS. KEEP UPWIND. Spill Release Procedures: HG EVAPORATE VERY SLOWLY.SPILL HG FORMS TINY GLOBULES EVAPORATE FASTER THAN SINGLE POOL, DEVELOPING VAP CONCEN.DO NOT TOUCH.STOP W/O RISK.TAKEUP W/SAND/OTHER ABSORB MATL.PLACE INTO CNTNR.HG SPILL KIT M AY BE USED.LG SPILL DIKE.ISOLATE AREA/DENY ENTRY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Sto rage Precautions:STORE IN CLSD UNBREAKABLE CNTNR(POLYETHYLENE)IN COOL DRY WELL-VENTI AREA AWAY FROM HEAT SOURCES.PROTECT CNTNR FRM PHYS DMG. Other Precautions: PROVIDE PREPLACEMENT/PERIODIC MED EXAMS FOR REG EXPO TO HG W/EMPHASIS DIRECTED TO CNS/SKIN/LUNGS/LIVER/KIDNEYS/GI TRACT. Respiratory Protection: SELF-CONTAINED BREATHING APPARATUS CAN BE USED UP TO 5MG/M3 W/FULL FACEPIECE ABOVE 1MG/M3.POSITIVE PRESSURE-TYP AIR SUPPLIED BREATH EQPMT RECOMMENDED ABOV 5MG/M3. Ventilation: ADEQU EXHAU VENTI TO MEET TLV REQMTS. OPERATIONS REQUIRING HG SURFACE REDUCE TEMP TO LIMIT VAP/MIN VAP EXPO W/LOC EXHAUST Protective Gloves: RUBB GLOVES Eve Protection: CHEM SAF GLASSES. Other Protective Equipment: PROTECTIVE CLOTH APPROPRIATE FOR WORK SITUATION. Work Hygienic Practices: SEPARATE WORK/STREET CLOTH.STORE WORKCLOTH IN SPEC LOCKERS.SHOWER BEF CHANGING TO STREAT CLOTHES. Supplemental Safety and Health INCOMP MATL:METHYLSILANCE,OXY,OXIDANTS(BR,PEROXYFORMIC ACID,CHLORINE BIOXIDE, NITRIC ACID, TETRACARBONYLNICKEL, NITROMETHANE, SILVER PERCHLORATE). HEALTH HAZ:DEATH FRM UREMIA.INHAL:IRRIT,SENS,NEUROTOXIC.I MMED DYSPNEA, FEVER, NAU, VOMIT, DIARRH, METALLIC TASTE, BRONCH, PULM EDEMA, PNEUMOTHORAX, ACIDOSIS, RENAL DMG/FAILURE, MERCURIALIS 

HCC:T6 Boiling Pt:B.P. Text:675F,357C Melt/Freeze Pt:M.P/F.P Text:-38F,-39C Vapor Pres:0.0012@ 20C Vapor Density:7.0 Spec Gravity:13.6 Solubility in Water:INSOLUBLE Appearance and Odor:SILVER-WHITE, HEAVY MOBILE LIQUID METAL.

 VIOLENT RX:ACETYLINIC CMPDS;AMMONIA;BORON;DIIODOPHOSHPIDE;ETHYLENE OXIDE;METALS(AL,K,LI,NA,RU),METHYLAZIDE,(SUPPLEMENTA)
 Stability Condition to Avoid:DOES NOT IGNIT EREADILY.FLAMM,POIS GASES MAYACCUMULATE IN TANKS/HOPPER CARS.MAY IGNIT COMBUST(WOOD,PAPER,OIL).
 Hazardous Decomposition Pr oducts:THERMAL DECOMPOSTION PRODUCTS INCLUDE TOXIC MERCURY VAPOR & OXYGEN.

Waste Disposal Methods:NONE SPECIFIED BY MANUFACTURER. HMIS:DISPOSE IAW ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.CONSULT PROPER AUTHORITIES FOR ADVICE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Am erica in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.