

DOW CORNING CORP -- DOW CORNING 200 FLUID,350 CST -- 9150-00-851-4257
===== Product Identification =====

Product ID:DOW CORNING 200 FLUID,350 CST

MSDS Date:07/24/1998

FSC:9150

NIIN:00-851-4257

MSDS Number: BZNSC

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:

517-496-5900

Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:POLY (DIMETHYLSILOXANE)

CAS:63148-6

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION, TEMPORARY REDNESS AND DISCOMFORT. SKIN:NO ADVERSE EFFECTS EXPECTED. INGEST: SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT. INHALE: NO ADVERSE EFFECTS LIKELY TO OC CUR DURING SHORT EXPOSURE(8 HRS OR LESS).

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:EYES:SYMPTOMS ARE REDNESS AND DRYNESS SIMILAR TO WINDBURN.

Medical Cond Aggravated by Exposure:PERSONS WITH ALLERGIC CONDITIONS MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
First Aid Measures
=====

First Aid:SKIN:WIPE OFF AND WASH WITH WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:NO FIRST AID SHOULD BE NEEDED.INGEST:NO FIRST AID SHOULD BE NEEDED.

=====
Fire Fighting Measures
=====

Flash Point Method:OC

Flash Point:>100.6C, 213.F

Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:MANUFACTURER STATES NONE KNOWN.

=====
Accidental Release Measures
=====

==

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS. SILICONE MATERIALS, EVEN IN SMALL QUANTITIES, MAY PRESENT A SLIP HAZARD.

Neutralizing Agent:NOT APPLICABLE.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE

E.KEEP AWAY FROM
HEAT,SPARKS,FLAMES AND INCOMPATIBLE MATERIALS.

Other Precautions:THIS PRODUCT IS SENSITIVE TO CONTAMINATION AT HIGHER
TEMPERATURES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.

Ventilation:USE GENERAL DILUTION VENTILATION.SEE SUPPLIMENTAL DATA.

Protective Gloves:WASHING AT MEALTIME IS SUFFICIENT.

Eye Protection:SAFETY GLASSES AT A MINIMUM

Other Protective Equipment:PROVIDE A LOCAL EYE WASH STAT
ION AND SAFETY

SHOWER.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS
PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres: