View NSN Online: https://aerobasegroup.com/nsn/9150-00-935-4127

Product ID:PRELUBE 6 MSDS Date:06/01/1993 FSC:9150 NIIN:00-935-4127 MSDS Number: BZNSH === Responsible Party === Company Name: GRIGNARD CO INC Address:60 GRANT AVE City:CARTERET State:NJ ZIP:07008-2720 Country:US Info Phone Num:201-541-6661 Emergency Phone Num:201-541-6661 CAGE:27843 === Contractor Identification = == Company Name: GRIGNARD CO INC Address:900 PORT READING AVE Box:City:PORT READING State:NJ ZIP:07064-1044 Country:US Phone:732-541-6661/FAX: 731-541-1916 CAGE:27843 Company Name: HOLLAND J HENRY CORP (804-460-3300) Box:UNKNOW CAGE:8D826

Ingred Name:VEHICLE (MINERAL OIL) CAS:64742-53-6 RTECS #:PY8036000 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name: ADDITIVE (BARIUM SULF

ONATE) CAS:61790-48-5 RTECS #:CR0700000 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.5 MG/M3 ACGIH TLV:0.5 MG/M3

Ingred Name:OTHERS (ACETIC ACID ETHENYL ESTER POLYMER WITH ETHENE) CAS:24937-78-8 Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: NA. CHRONIC: NA. Explanation of Carcinogenicity:NA

Effects of Overexposure: PROLONGED OR REPEATED USE MAY CAUSE MILD SKIN IRRITATION.

Medical Cond Aggravated by Exposure:NA -NONE- THSI PRODUCT IS JUDGED TO BE NEITHER A "CORROSIVE" NOR AN "IRRITANT" BY OSHA CRITERIA.

First Aid:INHALATION-VAPOR INHALATION UNDER AMBIENT CONDITIONS IS NORMALLY NOT A PROBLEM. EYES-FLUSH WITH CLEAR WATER UNTIL IRRITATION SUBSIDES. SKIN-WASH THOROUGHLY WITH SOAP AND WATER. INGEST ION-DO NOT INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY.

ION-DO NOT INDUCE VOIVITTING, CALL A PHYSICIAN IIVIIVIEDIATELT.

Flash Point Method:COC Flash Point:360F,182C Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM. Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIPMENT. Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDANTS.

Spill Release Procedures: RECOVER FREE LIQUID, ADD ABSORBENT TO SPIL

L AREA.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: KEEP CONTAINER CLOSED. KEEP AWAY FROM HEAT AND OPEN FLAMES.

Other Precautions: AVOID BREATHING OIL MIST. REMOVE OIL IMPREGNATED CLOTHING. WASH THOROUGHLY AFTER EXPOSURE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NORMALLY NOT NEEDED. Ventilation:LOCAL EXHAUST-NO CAPTURE HOT FU MES. Protective Gloves:NORMALLY NOT NEEDED. Eye Protection:NORMALLY NOT NEEDED. Other Protective Equipment:OIL IMPERVIOUS APRON IF NEEDED. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health NONE

HCC:V6 Boiling Pt:B.P. Text:NA Melt/Freeze Pt:M.P/F.P Text:NA Vapor Pres:0.01 @100F Vapor Density:12 Spec Gravity:0.930 Solubility in Water:NONE Appearance and Odor:LIGHT COLOR, BLAND ODOR

STRONG OXIDIZERS LIKE LIQUID CHLORINE AND CONCENTRATED OXYGEN. Stability Condition to Avoid:HIGH TEMPERATURE AND FLAMES Hazardous Decomposition Products:CARBON MONOXIDE IN THE CASE OF INCOMPLETE COMBUSTION.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This informa

tion is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.