View NSN Online: https://aerobasegroup.com/nsn/6525-01-168-0528

EASTMAN KODAK COMPANY -- 102 8869;KODAK READYMATIC DENTAL DEL AND REPL;KAN471440 -- 6725-01-168-0528

Product ID:102 8869;KODAK READYMATIC DENTAL DEL AND REPL;KAN471440 MSDS Date:10/25/1995 FSC:6725 NIIN:01-168-0528 MSDS Number: BZPKR === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-477-3194 MSDS:800-242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 85-90% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIU

M SULFITE CAS:7757-83-7 RTECS #:WE2150000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFITE CAS:10117-38-1 RTECS #:WT3530000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:DIETHYLENE GLYCOL CAS:111-46-6 RTECS #:ID5950000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA) CAS:123-31-9 RTECS #:MX3500000 Fraction by Wt: 2% Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M 3; 9596 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

LD50 LC50 Mixture:TLV FOR HYDROQUINONE IS 2MG/M3 TWA Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHAL:LOW HAZARD FOR EXPECTED HANDLING,HOWEVER CONTACT WITH STRONG ACIDS OR IF HEATED MAY RELEASE SULFUR DIOXIDE WHICH MAY CAUSE RESPIRATORY SENSITIZATION.EYES:MAY CAUSE TRANSCIENT IRRITATION.SKIN:MAY CAUSE ALLERGIC SKIN REACTION.INGEST:LOW INGESTION HAZARD. Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA. Effects of Overexposure:EYES:IRRITATION.INHAL:WHEEZING,CHEST TIGHTNESS.SKIN:RASH. Medical Cond Aggravated by Exposure:PERSONS WITH SENSITIVITY TO SULFITES OR WITH ASTHMA MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING. GET PROMPT QUALIFIED MEDICAL ATTENTION.IF CONSCIOUS,GIVE 1-2 GLASSES OF WATER.

Flash Point:NONE Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:USE A SELF-CONTAI NED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard: FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.

Spill Release Procedures:FLUSH SMALL SPILLS TO SEWER WITH PLENTY OF WATER.SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIP PERINESS. Neutralizing Agent:NOT REPORTED.

\_\_\_\_\_

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM OXIDIZING MATERIALS.

Other Precautions:FOLLOW LABEL DIRECTIONS.AVOID BREATHING VAPORS.AVOID SKIN AND EYE CONTACT.REGULAR USE OF A NON-ALKALINE(ACIDIC) SKIN CLEANER MAY REDUCE THE CHANCE OF AN ALLERGIC SKIN REACTION.

====== Exposure Controls/Personal Protection ==========

Respiratory Protecti
on:NOT NEEDED IN NORMAL SERVICE.
Ventilation:USE GENERAL DILUTION VENTILATION(TYPICALLY 10 AIR CHANGES/HR).
Protective Gloves:IMPERVIOUS GLOVES.
Eye Protection:SAFETY GLASSES WITH SIDESHIELDS.
Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.
Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health NONE

======= Physical/Che

HCC:B3 Boiling Pt:B.P. Text:>212F,>100C Vapor Pres:24 Vapor Density:0.6 Spec Gravity:1.09 pH:10.1 Solubility in Water:COMPLETE Appearance and Odor:LIQUID;ODORLESS;COLORLESS Percent Volatiles by Volume:90

Stability Indicator/Materials to Avoid:YES STRONG ACIDS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:SULFUR DIOXIDE.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document sho

uld seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.