

GE CANADA, INC -- SILICONE SEALANT P/C RTV133 -- 8040-01-168-0077

=====
Product Identification
=====

Product ID:SILICONE SEALANT P/C RTV133

MSDS Date:03/15/1995

FSC:8040

NIIN:01-168-0077

MSDS Number: BZSXC

=== Responsible Party ===

Company Name:GE CANADA, INC

Address:2300 MEADOWVALE BLVD

City:MISSISSAUGA

State:ON

Country:CA

Info Phone Num:416-858-5108/518-237-3330

Emergency Phone Num:416-858-5108

/518-237-3330

Preparer's Name:DA POLSINELLI

CAGE:NO114

=== Contractor Identification ===

Company Name:GE CANADA, INC

Address:2300 MEADOWVALE BLVD

City:MISSISSAUGA

State:ON

Country:CA

Phone:416-858-5108/518-237-3330

CAGE:NO114

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

=====
Composition/Information on Ingredients
=====

Ingred Name:HAZAR

DOUS TRADE SECRET COMPONENT (ACUTE ORA LD50 11,300
MG/KG RAT)

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

Ingred Name:TRADE SECRET COMPONENT

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

Ingred Name:QUARTZ (NONHAZ)

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1 MG/M3

ACGIH TLV:0.1 MG/M3

Ingred Name:TRADE SECRET COMPONENT

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ing

red Name:VINYLSTOPPED PHENYLMETHYL POLYMER (NONHAZ)

CAS:68951-96-2

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYL POLYSILOXANE SILANDL/ST (NONHAZ)

CAS:70131-67-8

Fraction by Wt: 30-60%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORL>3160MG/KG;INHL>535MG/L;DERM3540MG/KG

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGESTION: MOUTH, THROAT & STOMACH

IRRITATION. MAY BE HARMFUL IF SWALLOWED. SKIN: UNCURED PRODUCT
CONTACT MAY IRRITATE SKIN. MAY CAUSE MILD SKIN IRRITATION.

INHALATION: CAUSES MILD RESPIRATORY IRRITATION. APPLIES ONLY IN
UNCURED STATE. EYE: UNCURED PRODUCT IRRITATES EYES. VAPOR &/OR
LIQUID CAUSES IRRITATION.

Explanation of Carcinogenicity:FORMALDEHYDE, CARCINOGEN, RELEASED
>300F.

Effects of Overexposure:TARGET ORGANS: PRODUCT CONTAINS A COMPONENT
WHERE FATAL TOXICITY HAS BEEN SHOWN IN REPRODUCTIVE ST

UDIES ON

ANIMALS. METHANOL RELEASED DURING CURING. FORMALDEHYDE RELEASED
>300F - SKIN/RESP SENSITIZER , TOXIC EYE/THROAT IRRITANT,
CARCINOGEN.

=====
First Aid Measures
=====

First Aid:INGESTION: RINSE MOUTH WITH WATER SEVERAL TIMES. SKIN: TO
CLEAN FROM SKIN, REMOVE COMPLETELY WITH A DRY CLOTH OR PAPER TOWEL,
BEFORE WASHING WITH DETERGENT AND WATER. INHALATION: MOVE PERSON TO
FRESH AIR. EYES: IN CASE OF CONTACT, IMMEDIATELY FLUSH E
YES WITH
PLENTY OF WATER AT LEAST 15 MINUTES. GET MEDICAL AID IF IRRITATION
PERSISTS.

=====
Fire Fighting Measures
=====

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA
Fire Fighting Procedures:NONE KNOWN

=====
Accidental Release Measures
=====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL
AND PUT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACES WITH
DETERGENT AND WATER TO REDUCE SLIPP
ING HAZARD. WEAR PROPER
PROTECTIVE EQUIPMENT AS SPECIFIED IN THE PROTECTIVE EQUIPMENT
SECTION.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID CONTACT W/SKIN & EYES.USE ONLY
IN WELL VENTED AREA.REMOVE CONTACT LENSES BEFORE USING
SEALANT.PRODUCT RELEASES METHANOL DURING APPLIC & CURING.
Other Precautions:DON'T HANDLE LENSES TILL ALL SEALANT HAS BEEN CLEANED
FROM FINGERTIPS, NAILS & CUTICLES. RESIDUAL SEALANT MAY REM
AIN ON
FINGERS FOR SEVERAL DAYS & TRANSFER TO LENSES & CAUSE SEVERE EYE
IRRITATION. UNCLEANED PRODUCT MAY IRRITATE SKIN & EYES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE IN A WELL VENTILATED AREA.
Ventilation:USE ONLY IN WELL VENTILATED AREA.
Protective Gloves:CLOTH GLOVES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYEWASH STATIONS. USE IN A WELL VENTILATED
AREA. LOCALIZED VENTILATION SHOULD BE USED TO CONTROL DUST L

EVELS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:NE

Vapor Density:NE

Spec Gravity:1.23 (WATER=1)

pH:NA

Evaporation Rate & Reference: