View NSN Online: https://aerobasegroup.com/nsn/8040-00-262-9005

TACC INTL -- MA212 SOLVENTBORNE NEOPRENE ADHESIVE -- 8040-00-262-9005

Product ID:MA212 SOLVENTBORNE NEOPRENE ADHESIVE

MSDS Date:07/08/1994

FSC:8040

NIIN:00-262-9005

MSDS Number: BZYVP === Responsible Party === Company Name:TACC INTL

Address: AIR STATION INDUSTRIAL PK

Box:535

City:ROCKLAND

State:MA ZIP:02370 Country:US

Info Phone Num:617-878-7015

Emergency Phone N um:617-878-7015

CAGE:GO489

=== Contractor Identification ===

Company Name: TACC INTERNATIONAL CORP Address: AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA ZIP:02370 Country:US

Phone:781-878-7015

CAGE:0HZU1

Company Name: TACC INTL

Address:AIR STATION INDUSTRIAL PK

Box:535

City:ROCKLAND

State:MA ZIP:02370 Country:US

Phone:617-878-7015

CAGE:GO489

====== Composition/Information on Ingredients ========

Ingred Name:TOLUENE (IARC CARC- GROUP 3) *96-2*

CAS:108-88-3 RTECS #:XS525 0000

Other REC Limits:375 MG/CUM

OSHA PEL:100 PPM ACGIH TLV:100 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: HEXANE, N-HEXANE

CAS:110-54-3

RTECS #:MN9275000 Fraction by Wt: 20-50% Other REC Limits:50 PPM OSHA PEL:1800 MG/CUM ACGIH TLV:176 MG/CUM

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: ACETONE; DIMETHYL KETONE; 2-PROPANONE

CAS:67-64-1

RTECS #:AL3150000 Fraction by Wt: 5-20% OSHA PEL:2400 MG/CUM ACGIH TLV:750 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ET

HYL KETONE, 2-BUTANONE *96-2*

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 5-20%

Other REC Limits:590 MG/CUM

OSHA PEL:200 PPM ACGIH TLV:590 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

========== Hazards Identification ===============

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: MAY CAUSE UPPER

RESPIRATORY DRYNESS/IRRITATION, MENTAL DEPRESSION/NARCOSIS.

OVEREXPOSURE TO SOLVENTS COULD LEAD TO PERMANENT EFFECTS TO THE NERVOUS SYSTEM, BODY ORGANS/THE BRAIN. EYES: IR RITATION. SKIN: REMOVAL OF SKIN OILS, IRRITATION, DERMATITIS, SENSITIZATION. INGESTION: MAY BE HARMFUL/FATAL. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: HEADACHE, DIZZINESS, NAUSEA, DRYNESS, IRRITATION, DROWSINESS, NARCOSIS, DIFFICULTY IN BREATHING First Aid: INHALATION: GET FRESH A IR. SKIN: WASH W/MILD SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES. Flash Point Method:TCC Flash Point:0F Lower Limits: 1.1 Upper Limits:12.8 Extinguishing Media: FOAM, DRY CHEMICAL, CO2, WATER SPRAY/FOG Fire Fighting Procedures: AVOID BREATHING SMOKE. USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREA. WATER TENDS TO SPREAD BURNING LIQUID IF LARGE AMOUNTS USED. Unusual Fi re/Explosion Hazard: VAPORS MAY IGNITE EXPLOSIVELY/CAUSE FLASH FIRES. ELIMINATE IGNITION SOURCES. NO SMOKING. USE ADEQUATE CROSS VENTILATION SUFFICIENT TO REMOVE ODOR & VAPORS. ========= Accidental Release Measures ============= Spill Release Procedures: SMALL: MAY BE ABSORBED INTO AN APPROPRIATE ABSORBANT. ============ Handling and Storage =========================== Handling and Storage Precautions: STORE AT 60-95F OUT OF SUN. GROUND ALL **EQUIPMENT WHEN HA** NDLING FLAMMABLE SOLVENTBORNE MATERIALS. Other Precautions: USE ADEQUATE VENTILATION TO AVOID BREATHING VAPOR WHEN COVER IS REMOVED. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: IF VAPORS EXCEED TLV, USE SELF CONTAINED ORGANIC MASK NIOSH APPROVED. Ventilation: SUFFICIENT TO KEEP WORKROOM CONCENTRATION 1 Spec Gravity:0.37755 Evaporation Rate & Dr. Reference: FASTER THAN N-BU AC Appearance and Odor: NEUTRAL, TYPICAL ODOR Percent Volatiles by Volu

	•	70	\sim
m	ıe:	/ <	.6

O. 1	D D .	
 Stability and	Reactivity Data	=======================================

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS & BASES Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY Hazardous Decomposition Products:CO, CO2

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE. FLAMMABLE UN1 133.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular s ituation.