View NSN Online: https://aerobasegroup.com/nsn/6810-00-281-7452

Product ID:MERCURY MSDS Date:05/01/1994 FSC:6810 NIIN:00-281-7452 MSDS Number: CBQHT === Responsible Party === Company Name: COLUMBUS CHEMICAL INDUSTRIES INC Address:N 4335 TEMKIN RD City:COLUMBUS State:WI ZIP:53925 Country:US Info Phone Num:414-623-2140 / FAX 414-623-2577 Emergency Phone Num:414-62 3-2140 CAGE:5Y144 === Contractor Identification === Company Name: COLUMBUS CHEMICAL INDUSTRIES INC Address:N 4335 TEMKIN RD Box:8 City:COLUMBUS State:WI ZIP:53925-0008 Country:US Phone:920-623-2140 CAGE:5Y144 Ingred Name: MERCURY (SARA 313) (CERCLA) CAS:7439-97-6 RTECS #:0V4550000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED OSHA PEL:C, 0.1 MG/M3; Z-2 ACGIH TLV:S,0.025 MG/M3; A4;96 EPA Rpt Qty:1 LB

=

DOT Rpt Qty:1 LB

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: INHALATION OF VAPORS/MISTS MAY CAUSE IRRITATION, SENSITIZATION AND NEUROTOXICITY. SKIN CONTACT MAY CAUSE IRRITATION, SENSITIZATION, NEUROTOXICITY AND NEPHROTOXICITY. EYE CONTACT MAY CAUSE IRRIT ATION. CORNEAL INJURY OR BURNS. INGESTION MAY CAUSE NEUROTOXICITY AND NEPHROTOXICITY. CHRONIC: SEE SUPPLEMENTAL..... Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effects of Overexposure: INHALED-DYSPNEA, COUGH, FEVER, NAUSEA, VOMITING, DIARRHEA, S TOMATITIS, SALIVATION, METALLIC TASTE, BRONCHITIS, PNEUOMONIA, PULMONARY EDEMA, ACIDOSIS, RENAL DAMAGE.SKIN-REDNESS, IRRITATION; SEE INHALED(ABSORPTION).EY ES-IRRITATION,BU **RNS.INGESTED-NECROSIS** OFMOUTH, THROAT, ESOPHAGUS, STOMACH; VIOLENT PAIN, PROFUSE VOMITING, DEATH. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid: EYES-FLUSH WITH WATER FOR 15 MINUTES, LIFT LIDS. SKIN-REMOVE

CONTAMINATED CLOTHES.WASH WITH MILD SOAP & WATER.INHALED-REMOVE FRESH AIR.ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED.INGESTED-S EEK MEDCIAL ATTENTION.GASTRIC LAVAGE W /5%

SOLUTION OF SODIUM FORMALDEHYDE SULFOXYLATE, FOLLOWED BY 2% SODIUM BICARBONATE & FINALLY LEAVE 230 CC OF SODIUM FORMALDEHYDE SULFOXYLATE IN STOMACH.

Flash Point:NONE

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & FULL FIRE FIGHTER'S PROTECTIVE GEAR. USE WATER TO COOL FIRE EXPOSED CONTAINERS. MOVE CONTAINERS FROM AREA IF POSSIBLE. Unusual Fire/Explosion Hazard: USE WATER IN FLOODING AMOUNTS AS A FOG. AVOID BRETAHING CORROSIVE AND POISONOUS VAPORS. KEEP UPWIND.

Spill Release Procedures:DO NOT TOUCH SPILLED MATERIAL. ISOLATE & DENY ENTRY. WEAR PROPER PERSONAL PROTECTIVE CLOTHING. STOP LEAK IF NO RISK. TAKE UP WITH SAND OR OTHER ABSORBENT AND PLACE IN CONTAINERS FOR LATER DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTUR ER.

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE IN CLOSED, UNBREAKABLE CONTAINERS AWAY FROM SOURCES OF HEAT. PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:MERCURY EVAPORATES VERY SLOWLY. SPILLED MERCURY FORMS MANY TINY GLOBULES THAT WILL EVAPORATE FASTER THAN A SINGLE POOL AND CAN DEVELOP A SIGNIFIGANT CONCENTRATION OF VAPORS IN AN UNVENTILATED AREA. SU CH VAPORS ARE POISONOUS.

=========

=== Exposure Controls/Personal Protection =========

Respiratory Protection: IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation: USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: RUBBER.

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: EYE WASH STATION & SAFETY S

HOWER. PROVIDE

PREPLACEMENT AND PERIODIC MEDICAL EXAMS FOR THOSE EXPOSED ON REGULAR BASIS.

Work Hygienic Practices: WASH HANDS AFTER HANDLING & BEFORE EATING, DRINKING, USING TOILET OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

CHRONIC: PROLONGED OR REPEATED EXPOSURE MAY CAUSE VISUAL DISTURBANCES, MERCURIALISM., DERMATITIS, ANURIA. NOTE: PHYSICAL EXAMS SHOULD PLACE EMPHASIS ON CNS, SKIN, LUNGS, LIVER, KIDNEYS & GI TRACT.

HCC:T6 Boiling Pt:=357.2C, 675.F Melt/Freeze Pt:=-38.9C, -38.F Vapor Pres:0.0012 Vapor Density:7.0 Spec Gravity:13.6 Solubility in Water: INSOLUBLE Appearance and Odor:SILVER-WHITE, HEAVY, MOBILE, LIQUID METAL. Stability Indicator/Materials to Avoid:YES ACETYILINIC CMDS, AMMONIA, BORON, DIIODOPHOSPHIDE, ETHYLENE OXIDE, METALS, METHYL AZIDE, METHYLSILANE, OXYGEN, OXI DIZERS Stability Condition to Avoid: DOES NOT READILY IGNITE. FLAMMABLE POISONOUS GASES MAY ACCUMULATE IN TANKS AND HOPPER CARS. MAY IGNITE COMBUSTIBLES. Hazardous Decomposition Products: THERMAL DECOMPOSITION PRODUCTS INCLUDE TOXIC MERCURY VAPORS AND OXYGEN. Waste Disposal Methods: DLA-HMIS: DISPOSE OF IN ACCORDANCE WITH LOCAL,

Waste Disposal Methods:DLA-HMIS: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS. EPA/RCRA HAZWASTE NUMBER=D009.

Disc

laimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.