

ROGERSOL INC FORMER HARRY H CO -- RUBBER REJUVENATOR 184,12-01840 --
6850-01-038-3749

===== Product Identification =====

Product ID:RUBBER REJUVENATOR 184,12-01840

MSDS Date:02/28/1992

FSC:6850

NIIN:01-038-3749

MSDS Number: CBQNS

=== Responsible Party ===

Company Name:ROGERSOL INC FORMER HARRY H CO

Address:5538 NORTHWEST HWY

City:CHICAGO

State:IL

ZIP:60630

Country:US

Info Phone Num:312-735-5100

E

mergency Phone Num:312-735-5100/800-424-9300(CHEMTREC)

CAGE:23953

=== Contractor Identification ===

Company Name:ROGERSOL INC FORMER HARRY H CO

Address:5538 NORTHWEST HWY

Box:City:CHICAGO

State:IL

ZIP:60630

Country:US

Phone:312-735-5100

CAGE:23953

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA 313) (CERCLA)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 5 - 15%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:750PPM/1000STEL;9596

EPA

Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 10 - 20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 200 PPM
ACGIH TLV:S,200PPM/250STEL; 96
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VM & P NAPHTHA/ALIPHATIC NAPHTHA (INCLUDING TOLUENE:
10-20%)
CAS:64742-89-8
Fraction by Wt: 30 - 40%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Na
me:TOLUENE (SARA 313) (CERCLA)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: SEE # 3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-BUTOXYETHANOL/ETHYLENE GLYCOL N-BUTYL ETHER
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 30 - 40%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9596

Ingred Name:ETHYL ACETATE (CERCLA)
CAS:141-78-6
RTECS #:AH5425000
Fraction by Wt: 10 - 20%
Oth

er REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9596

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VOLATILE ORGANIC CONTENT AS LISTED ON MSDS: 6.82 LBS/GAL.

RTECS #:9999999VC

Other REC Limits:NOT RELEVANT

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) 470 MG/KG (EGBE)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:

NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS, LIVER, KIDNEY, LUNG. ACUTE- TOXIC BY INHALATION, DERMAL ABSORPTION AND INGESTION. EYE AND SKIN IRRITANT. INGESTION MAY CAUSE BLINDNESS AND DEATH. INHALATION MAY CAUSE CNS DEPRESSION AND NAUSEA. CHRONIC- MAY CAUSE DAMAGE TO SKIN, LUNG, CNS, LIVER AND KIDNEY. MAY CAUSE DERMATITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, DROWSINESS

, MENTAL RETARDATION, FATIGUE, BLURRED VISION, BLINDNESS, CONFUSION, DERMATITIS

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, LIVER, KIDNEYS, CNS MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. S

KIN:WASH WITH

SOAP & WATER. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NECESSAR Y. ORAL:DO NOT INDUCE VOMITING EXCEPT ON ADVICE OF COMPETENT MEDICAL PERSONNEL. IF CONSCIOUS, RINSE MOUTH WITH WATER. KEEP PERSON WARM & QUIET. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:20.0F,-6.7C

Extinguishing Media:WATER SPRAY/FOG, DRY CHEMICAL, CARBON DIOXIDE, FOAM

. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES

OF IGNITION. VENTILATE AREA. CONTAIN AND PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH, VERMICULITE. GROUND ALL HANDLING EQUIPMENTS. PREVENT LIQUID FROM ENTERING SEWERS OR WATERWAYS.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA, AWAY FROM HEAT, FLAMES, SPARKS & OXIDIZERS. CONTAINERS SHOULD BE GROUNDED WHEN CONTENTS ARE BEING TRANSFERRED.

O

ther Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT WELD, SOLDER OR DRILL SUCH CONTAINERS. THEY MAY EXPLODE AND CAUSE INJURY/DEATH. KEEP OUT OF REACH OF CHILDREN. DO NOT INGEST. DO NOT GET IN EYES OR ON SKIN. DO NOT BREATHE VAPOR

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR OR AIR-PURIFYING RESPIRATOR. I

N EMERGENCY, WEAR A NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NEOPRENE, BUTYL

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:WEAR PROTECTIVE CLOTHING IN CASE OF REPEATED OR PROLONGED CONTACT. PROVIDE EYE WASH & SAFETY SHOWER.

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICE

S AND
RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING,
DRINKING/SMOKING.
Supplemental Safety and Health
FORMULA AND PERCENTAGE CHANGED. FOR PREVIOUS FORMULATIONS, SEE PNI A OR
B, SAME NSN.

===== Physical/Chemical Properties =====

HCC:F5
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:B.P. Text:134F - 273F
Vapor Pres:3.72 @ 68F
Vapor Density:2.52
Spec Gravity:0.845
Evaporation Rate & Reference:3.0 (N-BUTYL ACETATE=1)
Solubility in Water:NIL
Appearance
and Odor:CLEAR, WATER WHITE LIQUID - SHARP ODOR
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, SPARKS, FLAMES
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE
AND FEDERAL REGULATIONS
. RECOMMENDED PROCEDURE IS BY INCINERATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of

this information to their particular situation.