

QUICK START PRODUCTS LTD -- DIESEL STARTING FLUID,LP-535/5537 -- 2910-01-245-3903

=====  
Product Identification  
=====

Product ID:DIESEL STARTING FLUID,LP-535/5537

MSDS Date:12/09/1995

FSC:2910

NIIN:01-245-3903

MSDS Number: CBQVB

=== Responsible Party ===

Company Name:QUICK START PRODUCTS LTD

Address:HIGHWAY 251 SOUTH

City:ROCHELLE

State:IL

ZIP:61068

Country:US

Info Phone Num:815-895-4545; 815-562-

5414

Emergency Phone Num:815-895-4545

CAGE:78280

=== Contractor Identification ===

Company Name:ARLO CORP (201-575-4676)

Box:UNKNOW

CAGE:9R205

Company Name:QUICK START PRODUCTS LTD

Address:HIGHWAY 251 SOUTH

Box:City:ROCHELLE

State:IL

ZIP:61068

Country:US

Phone:815-562-5414

CAGE:78280

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYL ETHER (CERCLA)

CAS:60-29-7

RTECS #:KI5775000

Fraction by Wt: 91%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:

400PPM/500STEL; 9596

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:ETHYLENE (SARA 313)

CAS:74-85-1

RTECS #:KU5340000

Fraction by Wt: 6.5%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:ASPHYXIAN; 9596

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9596

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL/BHT (BUTYLATED HYDROXYTOLUENE)

CAS:128-37-0

RTECS #:GO7875000

Fraction by Wt: 1% PPM

Other

REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3; 9596

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:TLV FOR DIETHYL ETHER IS 400 PPM.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY.

ACUTE- EYES:MAY CAUSE IRRITATION/REDNESS. SKIN:IRRITATION &  
DEFATTING WITH PROLONGED/REPEATED CONTACT. INHALE:MAY CAUSE

DIZZINESS, INTOXICATION, UNCONCIOUSNESS. M AY CAUSE NARCOTIC  
EFFECTS. ORAL:HIGHLY UNLIKELY TO OCCUR. CHRONIC- UNKNOWN.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, TEARING, REDNESS, DRYNESS OF SKIN  
AND DEFATTING, DIZZINESS, HEADACHE

Medical Cond Aggravated by Exposure:PERSONS WITH CHRONIC RESPIRATORY OR  
SKIN DISEASES MAY BE AT AN INCREASED RISK FROM EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL A

ATTENTION IF SYMPTOMS PERSIST. SKIN:REMOVE  
CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. EYE:FLUSH WITH  
WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. INHALED:REMOVE TO FRESH  
AIR. PROVIDE OXYGEN/CPR IF NEEDED. ORAL:IF CONSCIOUS, DRINK  
WATER/MILK. INDUCE VOMITING ONLY IF DIRECTED BY MEDICAL PERSONNEL.  
CALL A PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:-49F,-45C

Lower Limit

s:1.9%

Upper Limits:48%

Extinguishing Media:USE FOAM, DRY CHEMICAL OR CARBON DIOXIDE. WATER MAY  
BE INEFFECTIVE BUT SHOULD BE USED TO COOL FIRE-EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED  
SELF-CONTAINED BREATHING APPARATUS. RUN OFF TO SEWERS MAY CREATE  
FIRE OR EXPLOSION.

Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. OVERHEATED, CLOSED  
CONTAINERS COULD EXPLODE DUE TO INTERNAL PRESSURE BUILDUP. VAPORS  
MAY TRAVEL TO AN IGNITION SOURCE AND FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES  
OF IGNITION. VENTILATE AREA. CONTAIN AND PICK UP SPILL WITH  
NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH, VERMICULITE. GROUND  
ALL HANDLING EQUIPMENTS. PREVENT LIQUID FROM ENTERING SEWERS OR  
WATERWAYS.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage

Precautions:STORE IN COOL, WELL VENTILATED AREA

AWAY FROM SPARKS, FLAME, OTHER SOURCES OF IGNITION & INCOMPATIBLE  
MATERIALS. DO NOT STORE ABOVE 175F.

Other Precautions:PROTECT CONTAINER FROM PHYSICAL DAMAGE. AVOID  
BREATHING VAPOR/MIST. AVOID CONTACT WITH EYES & SKIN. FOR  
INDUSTRIAL USE ONLY. VAPORS CAN BE IGNITED EASILY. KEEP AWAY FROM  
REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF TL

V IS EXCEEDED OR

FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR OR AIR-PURIFYING RESPIRATOR. IN EMERGENCY, WEAR A NIOSH-APPROVED POSITIVE-PRES SURE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:USE EXPLOSION-PROOF VENTILATION EQUIPMENT.

Protective Gloves:NITRILE GLOVES FOR REPEATED CONTACT

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING, APRON, AND BOOTS IF SPILLS OR

SPLASHING CAN OCCUR.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:G2

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:94.0F,34.4C

Vapor Pres:5548

Vapor Density:2.6

Spec Gravity:0.695

Evaporation Rate & Reference:6.9 (N-BUTYL ACETATE=1)

Solubility in Water:MODERATE

Appearance and Odor:COLORLESS LIQUID - STRONG E

THEREAL ODOR (SWEET PUNGENT)

Percent Volatiles by Volume:>99

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:SPARKS, HOT SURFACES, FLAME, DRYNESS.

TENDS TO PRODUCE EXPLOSIVE PEROXIDE ON LONG STANDING IN PRESENCE OF AIR & LIGHT.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES

===== Disposal Considerations =====

=====

Waste Disposal Methods:DISPOSAL OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT PUNCTURE, MUTILATE OR INCINERATE CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.