View NSN Online: https://aerobasegroup.com/nsn/8040-01-283-0688

VIMASCO CORP -- NUCLEAR GRADE VINYL WEATHER BARRIER, WC-1 NG, WHITE 8010-01-283-0688 Product ID:NUCLEAR GRADE VINYL WEATHER BARRIER, WC-1 NG, WHITE MSDS Date:02/12/1992 FSC:8010 NIIN:01-283-0688 MSDS Number: CBQVX === Responsible Party === Company Name: VIMASCO CORP Box:516 City:NITRO State:WV ZIP:25143 Country:US Info Phone Num:304-755-3328 **Emergency Phone Nu** m:304-755-3328 Preparer's Name: JOHN TIDQUIST CAGE:14947 === Contractor Identification === Company Name: VIMASCO CORP Box:516 City:NITRO State:WV ZIP:25143 Country:US Phone:304-755-3328 CAGE:14947 Ingred Name: PHENOL, ISOPROPYLATED, PHOSPHATE (3:1) VP: 0.25 @ 320F CAS:68937-41-7 RTECS #:SL5890000 Fraction by Wt: 212F,>100C Extinguishing Media: FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG. **Fire Fighting Proced**

ures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . PRODUCT WILL NOT BURN UNTIL WATER HAS BOILED OR EVAPORATED. Unusual Fire/Explosion Hazard:NONE KNOWN.
======================================
Spill Release Procedures:FOLLOW HNDLG PROCS. VENT AREA. CNTN LIQ W/INERT MATLS SUCH AS SAND. ABSORB LIQS USING INERT MATL & SHOVEL INTO CNTNRS. PVNT PROD FROM ENTERING STREAMS/DRINKING WATER SUPPLIES. BEFORE DRYING PROD MAY B E WASHED AWAY W/ WATER; AFTER DRYING, (SUPDAT) Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
 Handling and Storage Precautions: AVOID BREATHING VAPORS & APPLICATION TO HOT SURFACES AS VAPORS MAY BE IRRITATING. KEEP CNTNR CLSD. USE W/ADEQ VENT. STORE INDOORS AT TEMPS OF 45-90F. Other Precautions: FOR INDUSTRY/PROFESSIONAL USE ONLY. NOT INTENDED FOR RETAIL SALE OR USE BY INDIVIDUAL CONSUMERS. DO NOT REUSE CONTAINER FOR POTA BLES OR EDIBLES.
======================================
Respiratory Protection: IN RESTRICTED VENT AREAS, USE NIOSH/MSHA APPRVD CHEM VAP RESP. IN APPLICATIONS WHERE MISTS/SPRAY MAY BE GENERATED, AVOID INHAL OF AIRBORNE PARTICULATES BY USING NIOSH/MSHA APPRVD RESP W/ORG VAP CARTRI DGE W/PREFILTER FOR MIST OR DUST. Ventilation: GENERAL (MECHANICAL) ROOM VENTILATION WITH LOCAL EXHAUST. Protective Gloves: IMPERVIOUS GLOVES. Eye Protection: ANSI APPRVD CHEM WORK ERS GOGGLES.
Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER . Work Hygienic Practices: THOROUGHLY CLEANSE HANDS AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health HAZ DECOMP PRODS: OF PHOSPHORUS OXIDE. SPILL PROC: REMOVE W/PAINT SCRAPER OR STRONG SOLVENT.
======================================
Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:25.0F,-3.9C Vapor Pres:SEE INGS Vapor Density:L TR/AIR Spec Gravity:1.22 pH:8-9 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:APPRECIABLE Appearance and Odor:VISCOUS, WHITE PASTE WITH MILD LATEX ODOR. Percent Volatiles by Volume:50

Stability Indicator/Materials to Avoid:YES MATERIALS INCOMPATIBLE WITH WATER. Stability Condition to Avoid:NONE KNOWN. Hazardous Decomposition Products:THERMAL DECOMP WILL YIELD CARBON MONOXIDE, CARBON DIOXIDE, TRACE AMTS OF AMMONIA & FORMALDEHYDE & ACIDIC VAPOR (SUPDAT)

Waste Disposal Methods: IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. REVIEW HAZARD SECTION OF MSDS BEFORE ATTEMPTING CLEANUP. EMPTY CONTAINERS ARE NON HAZARDOUS UNDER RCRA AS INDUSTRIAL WASTE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Departme nt

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.