View NSN Online: https://aerobasegroup.com/nsn/9150-00-250-0928

UNI-KEM INTERNATIONAL CORPORATION/MFR OXYCHEM -- PETROLATUM MEETING FED SPEC VV-P-236A -- 9150-00-250-0928

Product ID:PETROLATUM MEETING FED SPEC VV-P-236A

MSDS Date:12/29/1995

FSC:9150

NIIN:00-250-0928

MSDS Number: CBRXW === Responsible Party ===

Company Name: UNI-KEM INTERNATIONAL CORPORATION/MFR OXYCHEM

Address:513 HICKORY AVENUE

Box:23384 City:HARAHAN

State:L

Α

ZIP:70183 Country:US

Info Phone Num:504-738-1623/713-623-2246

Emergency Phone Num:504-738-1623 Preparer's Name:J. M. INCHAMTEGUI

CAGE:4S446

=== Contractor Identification ===

Company Name: UNI-KEM INTERNATIONAL Address: 1001 HARIMAW COURT EAST

Box:City:METAIRIE

State:LA ZIP:70001 Country:US

Phone:504-835-7600/FAX:504-835-7608

CAGE:4S446

======= Composition/Information on Ingredients ========

Ingred Name:PETROLATUM

CAS:8009-03-8

RTECS #:SE6780000 Fraction by Wt: 100% Other REC Limit

## LD50 LC50 Mixture:TLV UNKNOWN. Routes of Entry: Inhalation: NO Skin: YES Ingestion: YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE:IRRITANT. Effects of Overexposure:EYE IRRITATION. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER. First Aid:INGEST:GIVE LARGE AMTS OF MILK OR W ATER. CONTACT PHYSICIAN. SKIN:WASH THOROUGHLY AFTER HANDLING. EYE:IMMED FLUSH EYES WITH PLENTY OF WATER. CONTACT PHYSICIAN. Flash Point Method:COC Flash Point:390F,199C Autoignition Temp: Autoignition Temp Text: ND Lower Limits:NA Upper Limits:NA Extinguishing Media: FOAM, CO2, OR DRY CHEMICAL. Fire Fighting Procedures: RESPIRATORY PROTECTION WHEN FIGHTING FIRES WHERE EXPOSURE TO VAPORS OR GASES IS POSSIBLE. Unusual F ire/Explosion Hazard:TOXIC GASES CAN BE EVOLVED IN FIRES OF THIS PRODUCT, AS WITH ALL PETROLEUM DERIVATIVES. ========= Accidental Release Measures ============ Spill Release Procedures: PICK UP EXCESS WITH SHOVEL AND PLACE IN SEPARATE CONTAINER. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. =========== Handling and Storage ============================

s:NONE RECOMMENDED

Handling and Storage Precautions:STORE AWAY FROM HEAT, SPARKS, FIRE OR FLAMES. KEEP OUT OF REACH OF CHI

LDREN. Other Precautions:NOT INTENDED FOR USE ON HUMAN BODY. HARMFUL IF SWALLOWED.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE. Ventilation:LOCAL EXHAUST:NONE. Protective Gloves:NONE SPECIFIED BY MANUFACTURER. Eye Protection:NONE Other Protective Equipment:NONE REQUIRED. Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health
========= Physical/Chemical Properties =========
HCC:V6 Boili ng Pt:B.P. Text:NA Melt/Freeze Pt:M.P/F.P Text:NP Decomp Temp:Decomp Text:NP Vapor Pres:NA Vapor Density:NA Spec Gravity:NA PH:NA Viscosity:NA Evaporation Rate & amp; Reference:NA Solubility in Water:NIL Appearance and Odor:SEMI-SOLID, SOFT PETROLATUM, ALMOST NO ODOR. Percent Volatiles by Volume:NIL Corrosion Rate:NP
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE. Ha zardous Decomposition Products:CO2, SMOKE, SOOT.
======= Disposal Considerations ==========
Waste Disposal Methods:MATERIAL SHOLLI DIRE PLACED IN CONTAINER AND

Waste Disposal Methods:MATERIAL SHOULD BE PLACED IN CONTAINER AND DISPOSED OF ACCORDING TO LOCAL, STATE, FED REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informa

tion to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.