View NSN Online: https://aerobasegroup.com/nsn/6750-00-964-9017

EASTMAN KODAK COMPANY -- 197 1746 KODAK FIXER, CONCENTRATE -- 6750-00-964-9017

Product ID:197 1746 KODAK FIXER, CONCENTRATE MSDS Date:11/08/1995 FSC:6750 NIIN:00-964-9017 MSDS Number: CBSDD === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET **City:ROCHESTER** State:NY ZIP:14650 Country:US Info Phone Num:716-477-3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

=

Ingred Name:SODIUM THIOSULFATE CAS:7772-98-7 RTECS #:XN6476000 Fraction by Wt: 70-75% Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM ALUM, DODECAHYDRATE CAS:7784-25-0 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM ACETATE CAS:127-09-3 RTECS #:AJ4300010 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM METABISULFITE CAS:7681-57-4 RTECS #:UX8225000 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 ACGIH TLV: 5 MG/M3; 9596

Ingred Name:BORON OXIDE CAS:1303-86-2 RTECS #:ED7900000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9596

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: EXPECTED TO BE LOW HAZARD FOR RECOMMENDED HANDLING. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN: LOW HAZARD FOR RECOMMENDED HANDLING. INGESTION: EXPECTED TO BE A L OW INGESTION HAZARD. Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effects of Overexposure:INGESTION-SOME ASTHMATICS OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA. Medical Cond Aggravated by Exposure:SOME ASTHMATIC S OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULTY BREATHING.

First Aid:INHALATION-IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. EYES-ANY MATERIAL THAT CONTACTS THE EYE SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYM PTOMS OCCUR. SKIN-WASH WITH SOAP & WATER. GET MEDCIAL ATTENTION IF SYMPTOMS OCCUR. INGESTED-DRINK 1-2 GLASSES OF WATER. SEEK M

EDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS. Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE

DUST-AIR MIXTURE. REDUCING AGENT. GREATLY INCREASES THE BURNING

RATE OF COMBUSTIBLE MATERIALS.

Spill Release Procedures: FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. OTHERWISE, SWEEP UP AND PLACE IN A CONTAINER FOR CHEMICAL WASTE. COLLECT IN A NONCOMBUSTIBLE CONTAINER FOR PROMPT DISPOSAL. CLEAN SURFACE THOROUGHLY TO REMO VE RESIDUAL CONTAMINATION. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES. DO NOT STORE OR SHIP TOGETHER WITH COMBUSTIBLE MATERIALS.

Other Precautions: AVOID BREATHING DUST. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. USE WITH ADEUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. KEEP FROM CONTACT WITH OXIDIZING MATERIALS, HIGHLY OXYGENATED OR HALO GENATED SOLVENTS, ORGANIC COMPOUNDS, ETC

======= Exposure Controls/Personal Protection

==

Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS, AN APPROVED RESPIRATOR MUST BE WORN. RESPIRATOR TYPE: DUST.

Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS Protective Gloves: IMPERVIOUS GLOVES SHOULD BE WORN.

Eye Protection: WEAR SAFETY GLASSES WITH SIDE SHIELDS.

Other Protective Equipment: EYE BATH, SAFETY SHOWER,

WASHING FACILITIES.

Work Hygienic Practices: IT IS GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE EYE CONTACT. WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health

WARNING! REDUCING AGENT. KEEP OUT OF REACH OF CHILDREN.

HCC:N1

Vapor Pres:NEGLIGIBLE Solubility in Water:APPRECIABLE. Appearance and Odor:SOLID (POWDER), WHITE COLOR, ODORLESS. Percent Volatiles by Volume:NEGLIE

======== Stability and Reactiv

ity Data ================================

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, BASES, SODIUM HYPOCHLORITE, STRONG OXIDIZING AGENTS, COMBUSTIBLE MATERIALS, HALOGENATED MATERIALS, AMMONIA Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:AMMONIA, CHLORAMINE. CARBON DIOXIDE,

CARBON MONOXIDE, OXIDES OF SULFUR, OXIDES OF NITROGEN.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS E VEN AFTER CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or

implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.