

DYNAMOLD, INC. -- MR-502 CATALYST (MAGNETIC RUBBER INSPECTION MATERIAL) --
6850-01-037-9015

=====
Product Identification
=====

Product ID:MR-502 CATALYST (MAGNETIC RUBBER INSPECTION MATERIAL)

MSDS Date:06/01/1995

FSC:6850

NIIN:01-037-9015

Kit Part:Y

MSDS Number: CBSFQ

=== Responsible Party ===

Company Name:DYNAMOLD, INC.

Address:2905 SHAMROCK AVE

Box:9617

City:FORT WORTH

State:TX

ZIP:76107

Info P

hone Num:817-335-0862

Emergency Phone Num:817-335-0862

CAGE:30256

=== Contractor Identification ===

Company Name:DYNAMOLD SOLVENTS, INC.

Address:2905 SHAMROCK AVE

Box:9617

City:FORT WORTH

State:TX

ZIP:76107

Country:US

Phone:817-335-0862

CAGE:30256

=====
Composition/Information on Ingredients
=====

Ingred Name:DIBUTYLTIN DILAURATE

CAS:77-58-7

RTECS #:WH7000000

Fraction by Wt: 0.05-2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1 MG SN/M3 SKIN

ACGIH TLV:0.1 MG SN/M3

=====

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN CONTACT IS NOT KNOWN TO CAUSE IRRIT. EYE CONTACT MAY CAUSE TRANSIENT EYE IRRIT.

Explanation of Carcinogenicity:PER MSDS:CHEM/COMPONENT LISTED AS CARCINOGEN OR POTENTIAL CARCINOGE:NONE.

Effects of Overexposure:TRANSIENT EYE IRRITATION.

M

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:INHAL:REMOVE TO FRESH AIR IMMED.GIVE OXY/ART RESP AS NEEDED.GET EMERG MED ATTN.PROMPT ATTN ESSENTIAL.EYE:IMMED RINSE W/CLEAN WATER 15-20MINS.RETRACT EYELIDS.IRRIT OCCURS GET EMERG MED ATTN.SKIN:REMOVE CONTAMIN CLOTH AS NEEDED.WASH SKIN WELL W/MILD SOAP/WATER.STICKY USE WATERLESS CLEANER 1ST.INGEST:LG QUANT GIVE LUKEWARM WATER(PIN

T) IF COMPLETELY CONSC/ALERT.DON'T INDUC VOMIT.GETEMERG MED ATTN.

=====
Fire Fighting Measures
=====

Flash Point Method:COC

Flash Point:265F,129C

Autoignition Temp:Autoignition Temp Text:NP

Lower Limits:NP

Upper Limits:NP

Extinguishing Media:DRY CHEMICAL, CO2, WATER SPRAY.

Fire Fighting Procedures:DON'T ENTER FIRE AREA W/O PROPER PROT.FIGHT FRM SAFE DIST/PROT LOCA.USE H2OSPRAY/FOG FOR COOLING.DRY CHEM CO PERMISSIBLE.NOTIFY AUTHOR IF ENTER SEWER/PUB H2O.

Unusual Fire/Explosion Hazard:HEAT MAY BUILD PRESSURE/RUPTURE CLSD CNTNR SPREAD FIRE INCR RISK OF BURN/INJURY.AVOID EXTREME HEAT/FIRE.

=====
Accidental Release Measures
=====

Spill Release Procedures:UTILIZE PPE.LIMIT ACCESS TO QUAL PERSON.SOAK UP W/INERT SOLIDS.PLACE IN LABEL/SEAL CNTNR.PREVENT FLOW TO SEWERS.NOTIFY FIRE/ENVIRO AUTHORITIES.COVER SLIPPERY SURFACE W/GRANULAR SOLID.CONTAIN SPILL TO PREVENT ESCAPE INTO ENVIRO.

Neutralizing Agent:

