

HEXAGON ENTERPRISES INC -- MIL-L-23699 E -- 9150-00-180-6266

=====  
Product Identification  
=====

Product ID:MIL-L-23699 E  
MSDS Date:05/15/1991  
FSC:9150  
NIIN:00-180-6266  
MSDS Number: CBSYG  
=== Responsible Party ===  
Company Name:HEXAGON ENTERPRISES INC  
Address:60 MIDVALE RD  
City:MOUNTAIN LAKES  
State:NJ  
ZIP:07046  
Country:US  
Info Phone Num:201-263-2600  
Emergency Phone Num:201-263-2600/800-424-9300(CHE  
MTREC)  
CAGE:0BJL6  
=== Contractor Identification ===  
Company Name:HEXAGON ENTERPRISES INC  
Address:60 MIDVALE RD  
Box:City:MOUNTAIN LAKES  
State:NJ  
ZIP:07046  
Country:US  
Phone:201-263-2600, CHEMTREC 800-424-9300  
CAGE:0BJL6

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS  
Fraction by Wt: 100%  
Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY  
TRACT. ACUTE- MAY CAUSE EYES & SKIN IRRITATION. PROLONGED/REPEATED  
SKIN CONTACT CAUSES DEFATTING. INHALATION OF VAPORS/OIL MIST MAY  
CAUSE IRRITATION. INGESTION MAY CAUSE NAUSEA. ASPIRATION HAZARD.  
CHRONIC- UNKNOWN.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, NAUSEA

Medical Con

d Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN

DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH  
AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15  
MINUTES. HOLD EYELIDS OPEN. SKIN:WIPE OFF EXCESS. WASH SKIN WITH  
SOAP & WA TER. ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, RINSE  
MOUTH. SEEK MEDICAL AT  
TENTION. DO NOT DRINK. IF SPONTANEOUS  
VOMITING OCCURS, MONITOR FOR BREATHING DIFFICULTY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:475F,246C

Extinguishing Media:USE FOAM, DRY CHEMICAL OR CARBON DIOXIDE. WATER MAY  
BE INEFFECTIVE BUT SHOULD BE USED TO COOL FIRE-EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND  
NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion H

azard:CONTAINER MAY BURST.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. RECOVER FREE OIL IF POSSIBLE.  
ABSORB SPILL WITH INERT MATERIAL SUCH AS SAND, CLAY, EARTH &  
SHOVELD INTO CONTAINERS FOR LATER DISPOSAL. PREVENT RUN-OFF TO  
ENTER WATERWAYS, SEWERS. ALL R ESPONSE ACTIVITIES MUST COMPLY WITH  
HAZWOPER.

Neutralizing Agent:NOT RELEVANT

=====  
===== Handling and Storage =====

Handling and

Storage Precautions:STORE AWAY FROM HEAT. KEEP CONTAINERS  
CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH  
THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD  
LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND  
LAUNDRER BEFORE RE-USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF EXPOSURE MAY OR DOES  
EXCEED OCCUPAT  
IONAL EXPOSURE LIMITS, WEAR A NIOSH-APPROVED ORGANIC  
VAPOR RESPIRATOR.

Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL  
BELOW APPLICABLE STANDARD(S).

Protective Gloves:NITRILE OR NEOPRENE RECOMMENDED

Eye Protection:SAFETY GLASSES, FACE SHIELD RECOMMENDED

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.  
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND  
RECOMMENDED PROCEDURES

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A, SAME NSN.

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Melt/Freeze Pt:M.P/F.P Text:>-75F,>-59C

Vapor Pres: