

FISKE BROTHERS REFINING CO -- LUBRIPLATE 930/AA/AAA; 930-2 -- 9150-00-953-1694

===== Product Identification =====

Product ID:LUBRIPLATE 930/AA/AAA; 930-2

MSDS Date:01/01/1996

FSC:9150

NIIN:00-953-1694

MSDS Number: CBTBX

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:8038

City:TOLEDO

State:OH

ZIP:43605-3843

Country:US

Info Phone Num:419-691-2491 / FA

X 419-693-3806

Emergency Phone Num:419-691-2491

Preparer's Name:ROBERT J. SIBILIA

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:HERMAN YENCIES INC

Address:577 MAIN STREET

Box:688

City:PASSAIC

State:NJ

ZIP:07055

Country:US

Phone:973-777-7200 /FAX: 973-777-0954

CAGE:0B260

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:

RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-355-8041

CAGE:6A908

=====
===== Composition/Information on Ingredients =====
=====

Ingred Name:MANUFACTURER CLAIMS ONLY NON-HAZARDOUS INGREDIENTS W/O SPECIFYING ANY INDIVIDUAL INGREDIENT.

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:TLV: 5 MG/M3 FOR OIL MIST IN AIR.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acu

te and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY

CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED IN TO THE LUNGS DURING INGESTION MAY CAUSEMILD TO SEVERE PULMONARY INJURY.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:HUMAN HEALTH

RISKS VARY FROM PERSON TO PERSON.

AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====
=====

First Aid:EYES: FLUSH WITH CLEAR WATER FOR 15 MIN. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHES & WASH WITH SOAP AND WARM WATER. IF INJECTED UNDER SKIN, CONSULY PHYSICIAN IMMED IATELY. INHAL

ATION: IF OVERCOME BY VAPOR FROM HOT

PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE & CALL A PHYSICIAN.

INGESTION: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:COC

Flash Point:400F,204C

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, OR WATER SPRAY (FOG).

Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPL

IED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD,
AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE
PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF
SEWER AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS
ENTERED
SEWERS AND WATER CO URSES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DO NOT HNADLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG
OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDER BEFORE REUSE.
CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:L

OCAL EXHAUST VENTILATION TO CAPTURE FUMES AND VAPORS.

Protective Gloves:USE OIL-RESISTANT GLOVES, IF NEEDED.

Eye Protection:IF CHANCE OF EYE CONTACT, WEAR GOGGLES.

Other Protective Equipment:USE OIL-RESISTANT APRON, IF NEEDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Melt/Freeze Pt:M.P/F.P Text

:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.94-0.97

Evaporation Rate & Reference: