

FLAMEMASTER CORP -- CS3202 PART B -- 8030-00-275-8110

===== Product Identification =====

Product ID:CS3202 PART B

MSDS Date:12/30/1994

FSC:8030

NIIN:00-275-8110

Kit Part:Y

MSDS Number: CBTMH

=== Responsible Party ===

Company Name:FLAMEMASTER CORP

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352

Country:US

Info Phone Num:818-982-1650

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:1443

9

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

===== Composition/Information on Ingredients =====

Ingred Name:LEAD DIOXIDE (IN THIS PRODUCT AIRBORNE PARTICLES WON'T
RESULT FROM NORMAL USE)

CAS:1309-60-0

RTECS #:OG0700000

Fraction by Wt: 64.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.05 MG/M3

ACGIH TLV:0.15 MG/M3

Ingred Na

me:LEAD OXIDE (IN THIS PRODUCT AIRBORNE PARTICLES WON'T RESULT FROM NORMAL USE)

CAS:1317-36-8

RTECS #:OG1750000

Fraction by Wt: 6.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.05 MG/M3

ACGIH TLV:0.15 MG/M3

Ingred Name:VOC = 1.0 G/L

RTECS #:9999999VO

Fraction by Wt: NA

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: WEAKNESS, STOOPEL. CHRONIC:

KIDNEY DAMAGE, ANEMIA, REPRODUCTIVE EFFECTS.

Effects of Overexposure:HEADACHE, MUSCLE, JOINT PAIN. NEUROMUSCULAR DYSFUNCTION.

Medical Cond Aggravated by Exposure:ANEMIA, KIDNEY DISEASE, PREGNANCY.

=====
===== First Aid Measures =====

First Aid:INGESTION: INDUCE VOMITING. CONSULT DR IMMEDIATELY. EYES: FLUSH W/LARGE AMTS WATER & CONTACT DR.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:>200F,>93C

Lower Limits:NONCOMBUST

Upper Limits:NONCOMBUST

Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER.

Fire Fighting Procedures:USE SCBA W/FULL FACEPIECE IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:FIRE HAZARD EXISTS IF CONTACT

W/OXIDIZABLE MATERIALS AT HIGH TEMPERATURES OCCURS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP & TRA

