

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- ENAMEL, ALKYD, GLOSS, LO VOC GREEN 14050, ID 774404 -- 8010-00-753-4549

=====
Product Identification
=====

Product ID:ENAMEL, ALKYD, GLOSS, LO VOC GREEN 14050, ID 774404

MSDS Date:12/21/1996

FSC:8010

NIIN:00-753-4549

MSDS Number: CBTQY

=== Responsible Party ===

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

Sta

te:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLSION

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ACETATE (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)
(LFL 1.7; UFL 7.6)

CAS:123-86-4

RTECS #:AF7350000

Fr

action by Wt: 10.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:150 PPM;STEL 200 PPM
ACGIH TLV:150 PPM;STEL 200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C)
(LFL 1.0; UFL 7.0)

CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 10.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM;STEL 150 PPM
ACGIH TLV:100 PPM;STEL 150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOAMYL KETONE (SOLVENT)
CAS:110-12-3

RTECS #:MP3850000
Fraction by Wt: 5.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM; 240 MG/M3
ACGIH TLV:50 PPM; 240 MG/M3

Ingred Name:CRISTALLINE SILICA TRIPOLI
CAS:1317-95-9
Fraction by Wt: