

COURTAULDS AEROSPACE -- PR-1422 B-1/2, 1422B146 PART A, ACCELERATOR --  
8030-01-154-9254

=====  
===== Product Identification =====

Product ID:PR-1422 B-1/2, 1422B146 PART A, ACCELERATOR

MSDS Date:10/21/1993

FSC:8030

NIIN:01-154-9254

Kit Part:Y

MSDS Number: CBTVC

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE

Address:5430 SAN FERNANDO RD.

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

I

nfo Phone Num:818-240-2060

Emergency Phone Num:800-228-5635/800-424-9300 CHEMTREC

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====  
===== Composition/Information on Ingredients =====

Ingred Name:DIMETHYL ACETAMIDE (DMAC) (VP = 2.0)

CAS:127-19-5

RTECS #:AB7700000

Fraction by Wt: 15.0%

Other REC Limits:NO

NE SPECIFIED  
OSHA PEL:10 PPM, SKIN  
ACGIH TLV:10 PPM, SKIN

Ingred Name:CALCIUM DICHROMATE (SARA 313)  
CAS:14307-33-6  
RTECS #:HX7630000  
Fraction by Wt: 15.0%  
Other REC Limits:STEL .1 AS CR03  
OSHA PEL:NOT EST.  
ACGIH TLV:.05 MG/M3 (AS CR)

Ingred Name:MAGNESIUM DICHROMATE (SARA 313)  
CAS:13423-61-5  
Fraction by Wt: 15.0%  
Other REC Limits:STEL 0.1 AS CRO3  
ACGIH TLV:0.05 MG/M3 AS CR

Ingred Name:SILICON DIOXIDE (AMORPHOUS) (NON-HAZARDOUS)  
CAS:67762-90-7  
Other REC Limits:NONE RECOMMENDED

Ingred Name:WATER (NON-HAZARDOUS)  
CAS:7732-18-5  
RTECS #:ZC0110000  
Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDRATED ALUMINUM SILICATE (NON-HAZARDOUS)  
CAS:1335-30-4  
Other REC Limits:NONE RECOMMENDED

Ingred Name:MAGNESIUM ALUMINUM SILICATE (NON-HAZARDOUS)  
CAS:8031-18-3  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and

Chronic:EYES: BURNING, TEARING, REDDENING,  
POSSIBLE TRANSIENT CORNEAL INJURY. SKIN: HARMFUL RAPID ABSORPTION.  
INHALATION: MAY CAUSE LIVER/KIDNEY DAMAGE. PROLONGED EXPOSURE TO  
HEXAVALENT CHROMIUM COMPOUNDS OVE R PEL: PENETRATING ULCERS OF  
SKIN/MUCOUS MEMBRANE/PERFORATION OF CARTILAGINOUS NASAL SEPTUM.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES, CONSULT  
PHYSICIAN. SKIN: WASH WITH SOAP AND WATE  
R. IF SYMPTOMS PERSIST,  
CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS  
ARE PRESENT C ONSULT A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:145F,63C  
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER FOG.  
Fire Fighting Procedures:USE COMPLETE PERSONAL PROTECTION.  
Unusual Fire/Explosion Hazard:NONE KNOWN.

=====  
===== Accidental Release Measures =====

=====

Spill Release Procedures:DIKE & COVER SPILL WITH A NON-OXIDIZABLE  
ABSORBENT. SCOOP INTO CONTAINER. SPRINKLE SODIUM THIOSULFATE ON  
RESIDUE. WORK INTO RESIDUE. SCOOP INTO DISPOSAL CONTAINER. CLEAN  
AREA WITH WATER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING AND  
BEFORE SMOKING OR EATING. AVOID INGESTION. DUE TO TOXICITY BY SKIN  
ABSORPTION, AVOID ALL SKIN CONTACT.

Other Precautions:NO  
NE

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING OR APPLYING IN ANY CIRCUMSTANCES  
LIKELY TO PRODUCE AIRBORNE LEVELS OF HAZARDOUS INGREDIENTS IN  
EXCESS OF TLV, USE AN ORGANIC VAPOR CARTRIDGE OR VAPOR SUPPLIED  
RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPOR BELOW PEL.

Protective Gloves:NITRILE, BUTYL OR NATURAL RUBBER GLOVES.

Eye Protection:CHEM GOGGLES, FULL FACE SHIELD IF SPLASH

Other Protective Equipment:GLOV

ES NOT ADEQUATE FOR IMMERSION. PROTECT SKIN (SPLASH) W/NITRILE BUTYL, NAT'L RUBBER, POLYETHYLENE APRON OR COVERALLS.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 331F

Vapor Density:>AIR

Spec Gravity:1.4

Appearance and Odor:BLACK PASTE.

Percent Volatiles by Volume:61.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

EASILY OXIDIZABLE MATERIALS.

RIALS.

Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN;

CHROMIUM COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:EPA WASTE NO. D-007 HAZARDOUS WASTE. DISPOSE OF SPILLAGE IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner wh

atsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.