

RUST-OLEUM CORP -- DAMP PROOF RED PRIMER, 769 -- 8010-00-055-9034

=====  
Product Identification  
=====

Product ID:DAMP PROOF RED PRIMER, 769

MSDS Date:01/22/1990

FSC:8010

NIIN:00-055-9034

MSDS Number: CCBDQ

=== Responsible Party ===

Company Name:RUST-OLEUM CORP

Address:11 HAWTHORN PARKWAY

City:VERNON HILLS

State:IL

ZIP:60061

Country:US

Info Phone Num:312-367-7700

Emergency Phone Num:312-367-7700

CA

GE:08882

=== Contractor Identification ===

Company Name:RUST-OLEUM CORP

Address:11 HAWTHORN PARKWAY

Box:City:VERNON HILLS

State:IL

ZIP:60061-1583

Country:US

Phone:847-367-7700

CAGE:08882

=====  
Composition/Information on Ingredients  
=====

Ingred Name:STODDARD SOLVENT;(MINERAL SPIRITS)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 25%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY M

MANUFACTURER.

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: ACUTE: INHAL: HARMFUL IN INHALED. MAY AFFECT BRAIN/NERV SYS, CAUSING DIZZ, HDCH/NAUS. RPTD OVEREXP MAY LEAD PROGRESSIVELY TO STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS/COMA. CAUSES NOSE & THROAT IRRITATION. SKIN/EYE: CAUSES EYE & SKIN IRRIT WHICH MAY LEAD DERMATITIS W/RPTD OVEREXP. INGEST: GI IRRIT, (EFTS OF OVEREXP)

Exp

Explanation of Carcinogenicity: NOT RELEVANT.

Effects of Overexposure: HLTH HAZ: NAUSEA, VOMITING & DIARRHEA. CHRONIC: REPORTS HAVE SHOWN REPEATED & PRLNGD OCCUP OVEREXP TO SOLVENTS W/PERM BRAIN & NERVOUS SYSTEM DMG.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

=====  
First Aid Measures  
=====

First Aid: INHAL: REMOVE FROM EXPOS, RESTORE BRTHG & NOTIFY MD. SPRAY(EYES): FLUSH IMMED W/LGE AMOUNTS OF WATER FOR AT LEAST 15 MINS. NOTIFY MD. SPLASH(SKIN): WASH AFFECTED AREA W/SOAP & WATER, REMOVE CONTAMD CL OTHING & WASH BEFORE REUSE. INGEST: DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET & GET MED ATTN. ASPIR OF MATL INTO LUNGS CAN CAUSE CHEM PNEUM WHICH CAN BE FATAL.

=====  
Fire Fighting Measures  
=====

Flash Point: 104F, 40C  
Extinguishing Media: NFPA CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM).  
Fire Fighting Procedures: WEAR NIOSH/MSHA APPRVD SCBA & FULL P ROT EQUIP. WATER SPRAY MAY BE INEFTIVE. WATER MAY BE USED TO COOL CLSD CNTNRS TO PVNT PRESS BUILD-UP & POSS(SUPDAT)  
Unusual Fire/Explosion Hazard: KEEP CNTNRS TIGHTLY CLSD. ISOLATE FROM HEAT, ELEC EQUIP, SPARKS & OPEN FLAME. CLSD CNTNRS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION, VENT AREA & REMOVE WITH INERT ABSORBENT AND NON-

SPARKING TOOLS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE >120F. STORE LARGE QTYS IN BUILDINGS DESIGNED & PROT FOR STOR OF NFPA CLASS II COMBUST LIQS. CNTNRS SHOULD BE GROUNDED WHEN POURING.

Other Precautions:EMPTY CNTNRS MAY BE HAZ.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED CHEMICAL CARTRIDGE

RESPIRATOR(TC23C) TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY AND ORGANIC VAPORS DURING SPRAY APPLICATION. IN CONFINED AREAS: USE NIOSH/MSHA APPROVED SUPPLIED-AIR RESPIRATORS OR HOODS(TC19C).

Ventilation:PROVIDE GENL DILUTION/LOCAL EXHAUST VENTILATION IN VOL & PATTERN TO KEEP TLV OF HAZARDOUS INGS BELOW ACCEPTABLE LIMITS.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS.

Other Protective Equipment:EMERGENCY EYEWASH & DELUGE SHOWER MEETING

ANSI DESIGN CRITERIA.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

USERS OF THE "L" VERSION OF HMIS TO CONSULT THE "LR" VERSION FOR FURTHER INFORMATION. FIRE FIGHT PROC: AUTOIGNITION OR EXPLOSION. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>307F,>153C

Vapor Density:HVR/AIR

Spec Gravity:1.38

Evaporation Rate & Reference:SLOWER(ETHER=1)

Appearance

and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:47

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:BY OPEN FLAME: CARBON MONOXIDE AND CARBON DIOXIDE.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & F

EDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.