View NSN Online: https://aerobasegroup.com/nsn/6140-01-152-3995

## EAGLE-PICHER INDUSTRIES INC -- CAREFREE RECHARGABLE BATTERY -- 6140-01-152-3995

Product ID:CAREFREE RECHARGABLE BATTERY

MSDS Date:03/12/1991

FSC:6140

NIIN:01-152-3995

MSDS Number: CCBGL === Responsible Party ===

Company Name: EAGLE-PICHER INDUSTRIES INC

Address:BETHEL ROAD

Box:130

City:SENECA

State:MO ZIP:64865

Country:US

Info Phone Num:417-776-2256

**Emergency Pho** 

ne Num:417-776-2256

CAGE:0B3X4

=== Contractor Identification ===

Company Name: EAGLE-PICHER INDUSTRIES INC

Address:14212 BETHEL ROAD

Box:130

City:SENECA

State:MO ZIP:64865

Country:US

Phone:417-776-2256

CAGE:0B3X4

======= Composition/Information on Ingredients ========

Ingred Name:LEAD (SARA 313) (CERCLA)

CAS:7439-92-1

RTECS #:OF7525000 Fraction by Wt: 50%

OSHA PEL:SEE 1910.1025 ACGIH TLV:0.15MG/M3 DUST

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: LEAD; (LEAD OXIDES) (SARA 313) (C

ERCLA)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 25%
OSHA PEL:SEE 1910.1025
ACGIH TLV:0.15MG/M3 DUST
EPA Rpt Qty:1 LB

Ingred Name: SULFURIC ACID; (38% SULFURIC ACID, 1.28 S.G.) (SARA

302/313) (CERCLA)

CAS:7664-93-9

DOT Rpt Qty:1 LB

RTECS #:WS5600000 Fraction by Wt: 18% OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3/3 STEL

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

========== Hazards Identification ================

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry

: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:SEVERE BURNS AND EYE DAMAGE FROM SULFURIC ACID ELECTROLYTE. ILLNESS FROM SULFUR OXIDE FUMES. SIGNS & SYMPS:IRRITATION AND ACID BURNS. PUNGENT ODOR AND RESPIRATORY IRRITATION. CHRONIC:LEAD APPEARS ON N AVY OCCUPATIONAL CHEMICAL REPRODUCTIVE HAZARDS LIST. SEEK CONSULTATION FROM APPROPRIATE HEALTH (EFTS OF OVEREXP)

**Explanation of Carcinogenicity:SULFU** 

RIC ACID: IARC MONOGRAPHS ON EVAL OF

CARCIN RISK OF CHEMS TO MAN, VOL 54, PG 41, 1992:GROUP 1.

ANIMAL: PULM IRRIT.

Effects of Overexposure:HLTH HAZS:PROFESSIONALS CONCERNING LATEST HAZARD LIST INFORMATION AND SAFE HANDLING AND USE INFORMATION . Medical Cond Aggravated by Exposure:NOT APPLICABLE.

First Aid:EYES:IMMEDIATELY FLUSH W/POTABLE WATER FOR A MINIMUM OF 15 MINUTES, SEEK ASSISTANCE FROM MD . INHALATION:FOR

SULFUR OXIDE FUMES, DISCONNECT BATTERIES, EVACUATE AND VENTILATE. SKIN:FLUSH AREAS CO NTAMINATED BY SULFURIC ACID ELECTROLYTEWITH WATER. INGESTION:DRINK LARGE QUANTITIES OF WATER OR MILK, FOLLOWED BY MILK OF MAGNESIA, BEATEN EGGS OR VEGETABLE OIL.
======================================
Extinguishing Media:WATER, FOAM, DRY.  Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL  PROTECTIVE EQUIPMENT . NOT APPLICABLE.  Unusual Fire/Explosio  Hazard:KEEP LIGHTED CIGARETTES, SPARKS AND  FLAMES AWAY. EXPLOSION CAN RESULT FROM IMPROPER CHARGING AND IGNIT
OF CHARGING GASES & IF CHARGED IN GAS TIGHT ENCLOSURES.
========= Accidental Release Measures ============
Spill Release Procedures:AVOID CONTACT WITH SULFURIC ACID ELECTROLYTE FROM BATTERY. FLUSH WITH WATER. Neutralizing Agent:NEUTRALIZE WITH SOLUTION OF BAKING SODA IN WATER.
======================================
Handling and Storage Precautions:BATTERIES WITH RELEASED ELECTROLYTES SHALL BE SEALED IN POLYETHYLENE BAGS. KEEP BATTERIES AWAY FROM CHILDREN. Other Precautions:DO NOT CRACK BATTERY CASES. DO NOT OVERCHARGE. DO NOT SHORT CIRCUIT BATTERY TERMINALS. KEEP LIGHTED CIGARETTES, SPARKS, AND FLAMES AWAY FROM CHARGING BATTERIES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . N OT APPLICABLE. Ventilation:OTHER:NATURAL CONVECTION. Protective Gloves:USE RUBBER GLOVES IF CASE IS CRACKED. Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS . Other Protective Equipment:ANSI APPROVED EMERGENCY EYE WASH AND DELUGE SHOWER . NOT APPLICABLE. Work Hygienic Practices:NOT APPLICABLE.
Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER.
========= Physical/Chemical Properties ===========

HCC:C3

Appearance and Odor:NOT APPLICABLE.

======= Stab

ility	and	Reactivity	/ Data	============
11111	anu	Neactivity	/ Dala	

Stability Indicator/Materials to Avoid:YES
SOLVENTS MAY DISSOLVE BATTERY CASE MATERIAL.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:SEVERE OVERCHARGE AND OVERHEATING MAY
CAUSE SULFUR OXIDE FUMES.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS . DISPOSE WITH AUTOMOTIVE BATTERY SCRAP. DO NOT

## INCINERATE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their pa

rticular situation.