

VELSICOL CHEMICAL CORP -- MIL-L-3150C(AMMENDMENT 2) -- 9150-00-231-2361

=====
Product Identification
=====

Product ID:MIL-L-3150C(AMMENDMENT 2)

MSDS Date:12/01/1995

FSC:9150

NIIN:00-231-2361

MSDS Number: CCBYY

=== Responsible Party ===

Company Name:VELSICOL CHEMICAL CORP

Address:10400 W HIGGINS SUITE 600

City:ROSEMONT

State:IL

ZIP:60018-3713

Country:US

Info Phone Num:708-298-9000 708-298-9014(F

AX)

Emergency Phone Num:708-298-9000

Preparer's Name:N.R.NETZEL

CAGE:VELSI

=== Contractor Identification ===

Company Name:VELSICOL CHEMICAL CORPORATION

Address:10400 W HIGGINS ROAD

Box:City:ROSEMONT

State:IL

ZIP:60018

Country:US

Phone:847-298-9000

CAGE:0Z6C4

Company Name:VELSICOL CHEMICAL CORPORATION

CAGE:VELSI

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROTREATED NAPHTHENIC OIL

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identificat
=====

ion =====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5MG/M3

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:MISTS FROM EXCESSIVE HEATING MAY CAUSE IRRITATION.SKIN:LOW DERMAL TOXICITY.MISTS FROM EXCESSIVE HEATING MAY CAUSE IRRITATION.INGEST:LOW ORAL TOXICITY.MAY CAUSE GI TRACT IRRITATION.INHAL:MISTS FRO M EXCESSIVE HEATING MAY CAUSE RESPIRATORY IRRITATION.

Explanation of

Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INGEST:VOMITING,NAUSEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.CALL PHYSICIAN IF IRRITATION DEVELOPS.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFIC

IAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.NOTE TO PHYSICIAN:TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:400F,204C

Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.AVOID SPREADING BURNING LIQUID WITH WATER STREAM.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.

COOL FIRE EXPOSED

CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.HEAT OF FIRE MAY CAUSE CONTAINERS TO BURST.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.

=====

=== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, OPEN FLAMES AND STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation:USE GENERAL DILUTION VENTILATION.

Protective Gloves:IMPERMEABLE GLOVES.

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:0.01 @300F

Vapor Density:>1

Spec Gravity:0.93

Evaporation Rate & Reference: