

VELSICOL CHEMICAL CORP -- VV-L-800C -- 9150-00-458-0075

=====
Product Identification
=====

Product ID:VV-L-800C

MSDS Date:01/01/1996

FSC:9150

NIIN:00-458-0075

MSDS Number: CCCBF

=== Responsible Party ===

Company Name:VELSICOL CHEMICAL CORP

Address:10400 W HIGGINS SUITE 600

City:ROSEMONT

State:IL

ZIP:60018-3713

Country:US

Info Phone Num:708-298-9000 708-298-9014(FAX)

Emergency Phone Num:708-298-

9000

Preparer's Name:N.R.NETZEL

CAGE:VELSI

=== Contractor Identification ===

Company Name:VELSICOL CHEMICAL CORPORATION

Address:10400 W HIGGINS ROAD

Box:City:ROSEMONT

State:IL

ZIP:60018

Country:US

Phone:847-298-9000

CAGE:0Z6C4

Company Name:VELSICOL CHEMICAL CORPORATION

CAGE:VELSI

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM SULFONIC ACID SALT

CAS:68608-26-4

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIETHYLENE GLYCOL MONO-N-H

EXYL-2-ETHER
CAS:112-59-4
RTECS #:KL2625000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5MG/M3
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:LOW
DERMAL TOXICITY.MAY CAUSE IRRITATION.INGEST:LOW ORAL TOXICITY.MAY
CAUSE GI TRACT IRRITATION.INHAL:MAY
CAUSE RESPIRATORY IRRITATION.
Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT
IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.
Effects of Overexposure:INGEST:VOMITING.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND
WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.CALL PHYSICIAN IF
IRRITATION DEVELOPS.INHAL:REMOVE TO
FRESH AIR.GIVE OXYGEN OR
ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING.GET
PROMPT QUALIFIED MEDICAL ATTENTION.NOTE TO PHYSICIAN:TREAT
SYMPTOMATICALLY.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:275F,135C
Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.AVOID
SPREADING BURNING LIQUID WITH WATER STREAM.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED
SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT
ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE
CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.

=====
===== Handli

ng and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, OPEN FLAMES AND STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation

:USE GENERAL DILUTION VENTILATION.

Protective Gloves:IMPERMEABLE GLOVES.

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt

:B.P. Text:430F,221C

Vapor Pres:1

Spec Gravity: