

BLACKHAWK AUTOMOTIVE INC -- AWS CLASS E7018 (84-053) (COVERED ELECTRODE FOR SMAW)  
-- 3439-01-039-6408

===== Product Identification =====

Product ID:AWS CLASS E7018 (84-053) (COVERED ELECTRODE FOR SMAW)

MSDS Date:09/15/1988

FSC:3439

NIIN:01-039-6408

MSDS Number: CCCDL

=== Responsible Party ===

Company Name:BLACKHAWK AUTOMOTIVE INC

Box:1606

City:WAUKESHA

State:WI

ZIP:53187

Country:US

Info Phone Num

:414-542-6611

Emergency Phone Num:414-542-6611

CAGE:EO393

=== Contractor Identification ===

Company Name:BLACKHAWK AUTOMOTIVE INC

Box:1606

City:WAUKESHA

State:WI

ZIP:53187

Country:US

Phone:414-542-6611

CAGE:EO393

Company Name:NAPA, A DIVISION OF LINCOLN AUTOMOTIVE

Address:ONE LINCOLN WAY

Box:City:ST. LOUIS

State:MO

ZIP:63120-1578

Country:US

Phone:414-255-5520

CAGE:050Q3

===== Composition/Information on Ingredients =====

Ingred Name:30-40

CAS:7439-89-6

RTECS #:NO4565500

Other

REC Limits:NONE RECOMMENDED

Ingred Name:MANGANESE (SARA 313)

CAS:7439-96-5

RTECS #:OO9275000

Fraction by Wt: 1-11%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:C, 5 MG/M3 (FUME)

ACGIH TLV:0.2 MG/M3; 9596

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 2-12%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:SILICA DIOXIDE

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 1-11%

Other REC Limits:NONE RECOMMENDED

OSHA

PEL:6 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:SODIUM SILICATE

CAS:1344-09-8

Fraction by Wt: 2-12%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SILICATE

CAS:1312-76-1

Fraction by Wt: 2-12%

Other REC Limits:NONE RECOMMENDED

Ingred Name:FELDSPAR

CAS:68476-25-5

Fraction by Wt: 1-11%

Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE

CAS:1309-38-2

RTECS #:OM4800000

Fraction by Wt: 1-11%

Other REC Limits:NONE RECOMMENDED

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65

-3  
RTECS #:EV9580000  
Fraction by Wt: 18-28%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:FLUORSPAR  
CAS:14542-23-5  
Fraction by Wt: 10-20%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM HYDROXIDE (CERCLA)  
CAS:1310-58-3  
RTECS #:TT2100000  
Fraction by Wt: 0.1-1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:C 2 MG/M3  
ACGIH TLV:C 2 MG/M3; 9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====  
=====

LD50 LC50 Mixture:TLV-TWA WELD FUME:5MG/M3.  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:WELDING FUMES/GASES CAN BE DANGEROUS TO HEALTH.SHORT-TERM(ACUTE)OVEREXPO TO WELDING FUMES MAY RESULT IN DISCOMFORT SUCH AS DIZZ,NAU,DRYNESS/IRRIT OF NOSE/THROAT/EYES.LONG TERM:SIDEROSIS(IRON DEPOSIT I N LUNGS)WHICH AFFECT PULM FUNCTION.ARC RAYS CAN INJURE EYE/BURN SKIN.ELECTRIC SHO CK CAN KILL.  
Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NO FOR ALL INGREDIENTS PRESENT.  
Effects of Overexposure:DIZZINESS, NAUSEA, DRYNESS OR IRRIT OF NOSE/THROAT/EYES. ARC RAYS:INJURE EYE, BURN SKIN. ELECTRIC SHOCK CAN KILL. SIDEROSIS (RION DEPOSIT IN LUNGS) WHICH AFFECTS PULM FUNCITON.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====  
=====

First Aid:CALL FOR MEDICAL AID. EMPLOY FIRS

T AID TECHNIQUES RECOMMENDED  
BY AMERICAN RED CROSS.

===== Fire Fighting Measures =====

Flash Point:NA  
Autoignition Temp:Autoignition Temp Text:NA  
Lower Limits:NA  
Upper Limits:NA  
Extinguishing Media:NONE SPECIFIED BY MANUFACTURER.  
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.  
Unusual Fire/Explosion Hazard:NON-FLAMMABLE. WELDING ARC & SPARKS CAN  
IGNITE COMBUSTIBLES. REFER TO AMERICAN NATL STD 249.1 FOR FIRE  
PREVENTION DURING WELDING.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:READ/UNDERSTAND MFG INSTRUCT/PRECAUT  
LABEL.FILTER LENSES:RULE OF THUMB:START W/SHADE TOO DARK TO SEE  
WELD ZONE, THEN GO TO NEXT LIGHTER GIVES SUFF VIEW  
Other Precautions:RECOMMENDED WAY TO DETERMINE FUME/GAS COMP/QUANT  
WORKERS EXPO:TAKE AIR SMPL INSIDE WELDER HELM  
ET/WORKER BREATH  
ZONE.ANSI/AWS F1.1 AVAILABLE FROM AMER WELD SOC,POB 351040,MIA,FL  
33135.SEE AMER NAT STD Z-49.1 & OSHA 29CFR 1910.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED  
RESP WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR  
VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.  
Ventilation:USE ENOUGH VENTI,LOC EXHASUT @ARC OR BOTH TO KEEP  
FUMES/GASES BELOW TLV IN WORKER BREAT  
H ZONE/GENERAL AREA.  
Protective Gloves:WELDER GLOVES.  
Eye Protection:FCSHIELD W/FILT LENSES(SEE HNDLG PRCAUT)  
Other Protective Equipment:HELMET;SCREENS/FLASH GOGG IF NECESSARY TO  
SHIELD OTHERS.HEAD/HAND/BODY PROT FROM RADIATION/SPARK/ELECTR  
SHOCK.  
Work Hygienic Practices:TRAIN WELDER TO KEEP HEAD OUT OF FUMES/NOT  
TOUCH LIVE ELCTRICAL PARTS/INSULATE HIMSELF FROM WORK/GROUND.  
Supplemental Safety and Health  
HAZ DECOMP PROD:USED.ALSO COAT ON METAL BEING WELDED,#OF  
WELDER/VOL,QUAL/AMT

OF VENTI, POSITION OF WELDER HEAD W/FUME  
PLUME, PRESENCE OF ATM CONTAMIN. DECOMP PROD: ORIGINATING FROM  
VOLATIZ/RX/OXIDAT OF MA TL+BASE METAL, COAT, ETC. PRESENT AS COMPLEX  
CMPDS-NOT METALS. REASONABILITY: FLOURIDES, FE  
OXIDES, MN, SI, CO, CO2, OZONE, NOX.

===== Physical/Chemical Properties =====

HCC: V7

Boiling Pt: B.P. Text: NA

Melt/Freeze Pt: M.P/F.P Text: NA

Decomp Temp: Decomp Text: NA

Vapor Pres: NA

Vapor Density: NA

Spec Gravity: NA

pH: NA

Viscosity: NA

Evaporation Rate

& Reference: NA

Solubility in Water: NA

Appearance and Odor: NA

Percent Volatiles by Volume: NA

Corrosion Rate: NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: WELD FUME/GAS CAN'T BE CLASSIFIED

SIMPLY. COMPO/QUANT DEPENDENT UPON METAL BEING WELD/PROCEDURES  
FOLLOWED/ELECTRODE(SUPP)

=====

=== Disposal Considerations =====

Waste Disposal Methods: NONE SPECIFIED BY MANUFACTURER. HMIS: DISPOSE OF  
ANY GRINDING DUST OR WASTE RESIDUES IN ACCORDANCE W/EPA OR LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.