

SILOO (BOUGHT BY CRC CHEMICALS USA) -- SCREWLOOSE 3A,B,C -- 6850-01-043-8511

=====  
Product Identification  
=====

Product ID:SCREWLOOSE 3A,B,C

MSDS Date:08/01/1990

FSC:6850

NIIN:01-043-8511

MSDS Number: CCCDN

=== Responsible Party ===

Company Name:SILOO (BOUGHT BY CRC CHEMICALS USA)

Box:2549

City:WARMINSTER

State:PA

ZIP:18974

Country:US

Info Phone Num:215-674-4300

Emergency Phone Num:215-674-4300

P

reparer's Name:A.B. REED

CAGE:EO289

=== Contractor Identification ===

Company Name:NAPA, A DIVISION OF LINCOLN AUTOMOTIVE

Address:ONE LINCOLN WAY

Box:City:ST. LOUIS

State:MO

ZIP:63120-1578

Country:US

Phone:414-255-5520

CAGE:050Q3

Company Name:SILOO

Box:2549

City:WARMINSTER

State:PA

ZIP:18974

Country:US

Phone:215-674-4300

CAGE:54037

Company Name:SILOO (BOUGHT BY CRC CHEMICALS USA)

Box:2549

City:WARMINSTER

State:PA

ZIP:18974

Country:US

Phone:215-674-4300

CAGE:EO289

=====  
Composition/Info

Information on Ingredients =====

Ingredient Name:PETROLEUM DISTILLATE  
CAS:64742-47-8  
RTECS #:OA5504000  
Fraction by Wt: 89%  
Other REC Limits:NONE RECOMMENDED

Ingredient Name:PARAFFINIC OIL BASE  
CAS:64742-54-7  
RTECS #:PY8035500  
Fraction by Wt: 11%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingredient Name:ADDITIVE PRIMARILY FATTY ACIDS & FATTY ACID ESTERS.  
Fraction by Wt: NP  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE:MAY CAUSE BURNING & IRRITATION  
OF EYES. SKIN CONTACT WILL CAUSE DRYNESS. INHALATION OF MIST MAY  
CAUSE BREATHING PROBLEMS. VAPORS MAY ALSO CAUSE HEADACHES OR  
NAUSEA. CHRONIC:PROLONGED EXPOSURE TO SKIN MAY CAUSE DEVELOPMENT  
OF DERMATITIS.  
Explanation of Carcinogenicity:PER MSDS:CHEM LISTED AS CARCINOGEN/POT  
CARCINOGEN:NTP/IARC/OSHA:NO.  
Effects of Overexposure:BURNING & IRRIT OF EYE. SKIN DRYNESS. BREATHING  
PROBLEMS. HEADACHES, NAUSEA, DERMATITIS.  
Medical Conditions Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:IF SYMPTOMS PERSIST CALL PHYSICIAN. INHAL:REMOVE TO FRESH  
AIR. APPLY ARTIFICIAL RESPIRATION IF NECESSARY. EYE:FLUSH W/LG AMTS OF  
WATER. SKIN:WASH W/WATER

. REMOVE CONTAMINATED CLOTHING. INGEST:DO  
NOT INDUCE V OMIT. CALL PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point Method:COC  
Flash Point:175F,79C  
Autoignition Temp:Autoignition Temp Text:NP  
Lower Limits:NA  
Upper Limits:NA  
Extinguishing Media:CO2, FOAM, DRY CHEMICAL.  
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.  
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ANY SOURCES OF IGNITION. VENTILATE  
AREA. USE ABSORBENT TO PICK UP WASTE MATERIAL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL DRY PLACE.  
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS FOR CONC  
AB  
OVE TLV.  
Ventilation:ADEQUATE VENTILATION TO MAINTAIN VAPOR CONC BELOW TLV.  
Protective Gloves:SOLVENT RESISTANT.  
Eye Protection:SAFETY GLASSES.  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. HMIS:LAUNDER  
CONTAMIN CLOTHING BEFORE REUSE.  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:V4  
Boiling Pt:B.P. Text:380F,193C  
Melt/Freeze Pt:M.P/F.P Text:NA  
Decomp Temp:Decomp Te

xt:NP  
Vapor Pres:NA  
Vapor Density:>AIR  
Spec Gravity:0.80  
pH:NP  
Viscosity:NP  
Evaporation Rate & Reference:NA  
Solubility in Water:NEGLIGIBLE.  
Appearance and Odor:AMBER LIQUID, PETROLEUM ODOR.  
Percent Volatiles by Volume:91  
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. HMIS:ALL  
IGNITION SOURCES.  
Hazardous Decomposition Products:CO2, CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISCARDED FILLED CANS OR PARTIALLY USED CANS ARE  
HAZARDOUS WASTE-OBSERVE LOCAL, STATE AND FEDERAL REGULATIONS.  
CONTAINS NO CHEMS FOUND IN SEC 313 OF SARA TITLE III.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.