View NSN Online: https://aerobasegroup.com/nsn/4210-01-250-6424

Product ID:NITROGEN MSDS Date:12/01/1992 FSC:4210 NIIN:01-250-6424 MSDS Number: CCCGK === Responsible Party === Company Name: PRAXAIR INC Address:39 OLD RIDGEBURY RD City:DANBURY State:CT ZIP:06817-0001 Country:US Info Phone Num:203-794-5782 Emergency Phone Num:203-794-5782 CAGE:0LV01 === Contractor Identification === С ompany Name: ALL-SAFE INC Address:4767 LANGTON RD Box:116 City:HIILIARD State:OH ZIP:43026 Country:US Phone:614-876-4041 CAGE:2X264 Company Name: PRAXAIR, INC. Address:39 OLD RIDGEBURY RD Box:City:DANBURY State:CT ZIP:06810-5113 Country:US Phone:800-772-9247; 800-PRAXAIR CAGE:0LV01

Ingred Name:NITROGEN CAS:7727-37-9 RTECS #:QW9700000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED ACGIH TLV:ASPHYXIANT; 9596

LD50 LC50 Mixture:NOT GIVEN FOR PRODUCT AS A WHOLE Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ASPHYXIANT. INHALATION OF MODERATE CONCENTRATIONS MAY CAUSE HEADACHE, DROWSINESS, DIZZINESS, EXCITATION, EXCESS SALIVATION, VOMITING, UNCONSCIOUSNESS. LACK OF OXYGEN CAN CAUSE DEATH. NO HARMFUL EFFECT S EXPECTED FROM SKIN CONTACT WITH GAS. SKIN CONTACT WITH LIQUID MAY CAUSE FROSTBITE.

Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:HEADACHE, DROWSINESS, DIZZINESS, EXCITATION, EXCESS SALIVATION, VOMITING, UNCONSCIOUSNESS, DEATH, FROSTBITE. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:FOR

EXPOSURE TO LIQUID, IMMEDIATELY WARM FROSTBITE AREA WITH WARM WATER (NOT TO EXCEED 105F). CALL A PHYSICIAN. IF INHALED, REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. GIVE OXYG EN IF BREATHING IS DIFFICULT. CALL A PHYSICIAN. IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH EYES WITH WATER. SEE A PHYSICIAN IMMEDIATELY.

Flash Point:NONFLAMMABLE
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Exti
nguishing Media:NONFLAMMABLE. USE EXTINGUISHING MEDIA SUITABLE FOR SURROUNDING FIRE.
Fire Fighting Procedures:EVACUATE ALL PERSONNEL FROM DANGER AREA.
IMMEDIATELY DELUGE CONTAINERS SITH WATER SPRAY FROM MAXIMUM DISTANCE UNTIL COOL, THEN MOVE AWAY FROM FIRE AREA.
Unusual Fire/Explosion Hazard:CONTAINER MAY RUPTURE DUE TO HEAT OF FIRE. NO PART OF CONTAINER SHOULD BE SUBJECTED TO TEMPERATURES HIGHER THAN 52C. MOST CONTAINERS ARE DESIGNED TO VENT.

====== Accidental

Release Measures ===============

Spill Release Procedures: EVACUATE ALL PERSONNEL FROM DANGER AREA. USE SELF-CONTAINED BREATHING APPARATUS WHERE NEEDED. SHUT OFF LEAK IF WITHOUT RISK. VENTILATE AREA OF LEAK OR MOVE LEAKING CONTAINER TO WELL-VENTILATED AREA. T EST FOR OXYGEN PROIOR TO REENTRY. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: HIGH PRESSURE GAS. USE PIPING AND

EQUIPMENT DESIGNED TO WITHSTAND PRESSURES TO BE ENCOUNTERED. CAN CAUSE RAPID SUFFOCATION TO DUE OXYGEN DEFICIENCY. Other Precautions:NEVER WORK ON A PRESSURIZED SYSTEM. IF THERE IS A LEAK, CLOSE THE CYLINDER VALVE, BLOW DOWN THE SYSTEM BY VENTING TO A SAFE PLACE, THEN REPAIR LEAK. STORE AND USE WITH ADEQUATE VENTILATION. CLOSE VALV E WHEN NOT IN USE AND WHEN EMPTY.

Respiratory Protection:NONE REQUIRED UNDER N

ORMAL USE. HOWEVER, AIR

SUPPLIED RESPIRATORS ARE REQUIRED WHILE WORKING IN CONFINED SPACES WITH THIS PRODUCT. THE RESPIRATORY PROTECTION USE MUST CONFORM WITH OSHA RULES AS SPECIF IED IN 29 CFR 1910.134.

Ventilation: USE LOCAL EXHAUST SYSTEM, IF NECESSARY, TO PREVENT THE BUILD UP OF AN OXYGEN DEFICIENT ATMOSPHERE.

Protective Gloves: PREFERRED FOR CYLINDER HANDLING

Eye Protection: SELECT IAW OSHA 29 CFR 1910.133.

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health

WHEN TWO OR MORE GASES OR LIQUIFIED GASES ARE MIXED, THEIR HAZARDOUS PROPERTIES MAY COMBINE TO CREATE ADDITIONAL, UNEXPECTED HAZARDS. OBTAIN AND EVALUATE THE SAFETY INFORMATION FOR EACH COMPONENT BEFO RE YOU PRODUCE THE MIXTURE.

HCC:G3

Boiling Pt:B.P. Text:385F,196C Melt/Freeze Pt:M.P/F.P Text:-346F,-210C Vapor Pres:GAS Vapor Density:0.967 Spec Gravity:GAS Evaporation Rate & amp; Reference:NOT GIVEN Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS, ODORLESS GAS Percent Volatiles by Volume:100%

Stability Indicator/Materials to Avoid:YES LITHIUM, STANIUM, OZONE. Stability Condition to A void:EXTREME TEM[ERATURES Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for u se by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.