

CAAP CO INC -- CAAPCOAT AS-P108 BLACK ANTISTATIC POLYURETHANE RAIN EROSION- --
8010-00-459-1756

=====
Product Identification
=====

Product ID:CAAPCOAT AS-P108 BLACK ANTISTATIC POLYURETHANE RAIN EROSION-

MSDS Date:01/01/1995

FSC:8010

NIIN:00-459-1756

MSDS Number: CCGFK

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM ROAD

City:MILFORD

State:CT

ZIP:06460

Country:US

Info Pho

ne Num:203-877-0375

Emergency Phone Num:203-877-0375

Preparer's Name:CHRISTINE L SLEDGE

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *96-3*

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 54.7%

Other REC Limits:100 PPM

OSHA PEL:100 PPM

ACGIH TLV:100 PPM, SKIN
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:COLUMBIA CARBON, CARBON BLACK, LAMPBLACK, BLACK PEARLS
(IARC CARC GROUP 3) - *96-3*

CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 1.6%
Other REC Limits:3.5 MG/CUM (NIOSH)
OSHA PEL:3.5 MG/CUM
ACGIH TLV:3.5 MG/CUM

Ingred Name:1,3-DIISOCYANATOMETHYL-BENZENE, DIISOCYANATOTOLUENE, (IARC
GROUP2B,NTP SUSPECTED CARCINOGEN,IARC ANIMAL SUFFICIENT*96-3*

CAS:26471-62-5
RTECS #:HQ9490000
Fraction by Wt: 0-0.5%
EP
A Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:POLYPROPYLENE GLYCOL, POLY(1,4-BUTYLENE)GLYCOL, TOLUENE
DIISOCYANATE POLYMER

CAS:65636-36-4
Fraction by Wt: 43.7%

Ingred Name:VOLATILE ORGANIC CONTENT: 471 GM/L; (3.93 LBS/GAL)
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION & BURNING.

MAY CAUSE DAMAGE. SKIN: IRRITATION, BURNING. REPEATED/PROLONGED
EXPOSURE MAY CAUSE DERMATITIS, POSSIBLE SENSITIZATION. INHALATION:
MAY CAUSE THROAT & RESPIRATORY IRRITATION. MAY CAUSE NEURAL
IMPAIRMENT.

Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, DEFATTING, BURNING, HEADACHE,
DIZZINESS, LOSS OF APPETITE, NAUSEA
Medical Cond Aggravated by Exposure:PRE-EXISTING ALLERGIES, EYE, SKIN &
RESPIRATORY DISORDERS.

=====
===== First Aid Me

asures =====

First Aid:EYES: FLUSH W/WATER. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR, GIVE CPR IF NECESSARY. INGESTION: DON'T INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIS HIPS TO PREVENT BREATHING VOMITUS INTO LUNGS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:80F

Lower Limits:1

Upper Limits:7

Extinguishing Media:CO2

, FOAM, DRY CHEMICAL

Fire Fighting Procedures:WATER MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. WEAR SELF CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING; SOLVENT RESISTANT COATS/BOOTS/GLOVES/HELMET.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. WEAR SOLVENT RESISTANT GLOVES/BOOTS & SCBA IN PRESSURE DEMAND MODE/POSITIVE PRESSURE AIR-SUPPLIED RESPIRATOR. CONTAIN W/DIKES OF ABSORBENT & SOAK UP. CLEAN

UP & CONTAIN. SWEEP & WET MOP AREA W/SOAP & WATER. VENTILATE AREA.

===== Handling and Storage =====

Other Precautions:ONLY PROPERLY TRAINED & PROTECTED PERSONNEL SHOULD BE IN THE IMMEDIATE SPRAY AREA. VENTILATION SYSTEMS SHOULD BE DESIGNED TO DRAW AIR PAST THE OPERATOR, THEN PAST THE SOURCE OF VAPOR & THEN TO THE EXH AUST., NOT THE REVERSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF USE CONDITIONS GENERATE VAPORS/MISTS, WEAR A NIOSH APPROVED RESPIRATOR FOR THOSE EMISSION LEVELS AT POINT OF USE. OTHER RESPIRATORS: A FULL FACEPIECE/A PURIFYING CARTRIDGE RESPIRATOR EQUIPPED FOR ORGANIC VAPORS/MISTS, SCBA.

Ventilation:SPRAY BOOTH FOR SPRAY APPLICATIONS. EXHAUST: SUFFICIENT TO KEEP AIRBORNE CONCENTRATIONS 100F, HOT SURFACES & ALL IGNITION SOURCES

Hazardous Decomposition Products:BY COMBUSTION: CO, CO2, OXIDES OF NITROGEN, TRACES OF HYDROGEN CYANIDE & UNIDENTIFI

ED COMPOUNDS IN
BLACK SMOKE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN A LICENSED INCINERATOR. WHEN THE AS-P108 & CATALYST ARE MIXED TOGETHER & THE SOLVENT IS EVAPORATED, THE SOLID END PRODUCT IS A NON-HAZARDOUS LANDFILL ITEM. DISPOSE OF IAW/LOCAL, STATE & FEDERAL REGULATIONS. FLAMMABLE LIQUID UN1263.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by e

lements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.