

SCOT INC. -- 6036200 INITIATOR,ONE-WAY TRANSFER EXPLOSIVE ACTUATED -- 1377-01-167-6621
===== Product Identification =====

Product ID:6036200 INITIATOR,ONE-WAY TRANSFER EXPLOSIVE ACTUATED

MSDS Date:11/27/1991

FSC:1377

NIIN:01-167-6621

MSDS Number: CCGLB

=== Responsible Party ===

Company Name:SCOT INC.

Address:2525 CURTISS ST

City:DOWNERS GROVE

State:IL

ZIP:60515-0705

Country:US

Info Phone Num:708-

969-0620

Emergency Phone Num:800-535-5053

Preparer's Name:NICHOLAS F TURCIC

CAGE:MO896

=== Contractor Identification ===

Company Name:SCOT INC

Address:2525 CURTISS ST

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-0705

Country:US

Phone:630-969-0620

CAGE:93455

Company Name:SCOT INC.

Address:2525 CURTISS ST

City:DOWNERS GROVE

State:IL

ZIP:60515-0705

Country:US

Phone:708-969-0620

CAGE:MO896

===== Composition/Information on Ingredients =====

Ingred Name:LEAD AZIDE

CAS:13424-46-9

RTECS

#:OF8650000
Fraction by Wt: 40%

Ingred Name:HNS HEXANITROSTILBENE
Fraction by Wt: 60%

Ingred Name:ALUMINUM HOUSING

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:NONE

=====
First Aid Measures
=====

First Aid:OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Extinguishing Media:USE WATER ONLY. FOR LARGE FIRES, FLOOD AREA W/WATER FROM A DISTANCE.

Fire Fighting Procedures:MOVE CONTAINER W/O RISK. APPLY COOLING WATER TO SIDES, UNTIL FIRE IS OUT. IN CARGO AREA, USE UNMANNED HOSE HOLDER/MONITOR NOZZLES. WITHDRAW & LET FIRE BURN.

Unusual Fire/Explosion Hazard:IF INITIATOR IS INITIATED SOME LIGHT METALLIC FRAGMENTATION WOULD OCCUR W/A HOT DISCHARGE THAT WOULD POSE A FIRE HAZARD. (SEE SUPP)

=====
Accidental Release Measures
=====

Spill Release Procedures:USE FLOODING QUANTITIES OF WATER AS FOG. COOL CONTAINERS W/FLOODING AMOUNTS OF WATER, APPLY FROM AS FAR A DISTANCE AS POSSIBLE. EVACUATE TO A RADIUS OF 1500 FEET.

=====
Handling and Storage
=====

Handling and Storage Precautions:USE CAUTION IN HANDLING ACTUATED DEVICE SURFACE TEMP MAY BE 200F.
Other Precautions:KEEP FIRE AWAY.

=====
Exposure Controls/Personal Protection
=====

n =====

Supplemental Safety and Health

MODERATE EXPLOSION HAZARD WHEN SHOCKED/EXPOSED TO HEAT.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NOXIOUS GASES

Stability Condition to Avoid: HEAT, FLAME, SHOCK

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSAL OF WASTE IS PERFORMED BY QUALIFIED
DEMOLITION PERSONNEL IAW/FEDERAL, STATE & LOCAL REGULATIONS.
EXPLOSIVE CLAS

S C UN0173.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.