View NSN Online: https://aerobasegroup.com/nsn/9150-00-687-4241

Product ID:MIL-L-46000C;PQ-9870B MSDS Date:12/01/1995 FSC:9150 NIIN:00-687-4241 MSDS Number: CCHTV === Responsible Party === Company Name: VELSICOL CHEMICAL CORP Address:10400 W HIGGINS SUITE 600 City:ROSEMONT State:IL ZIP:60018-3713 Country:US Info Phone Num:708-298-9000 708-298-9014(FAX) Emer gency Phone Num:708-298-9000 Preparer's Name:N.R.NETZEL CAGE:VELSI === Contractor Identification === Company Name: VELSICOL CHEMICAL CORPORATION Address:10400 W HIGGINS ROAD Box:City:ROSEMONT State:IL ZIP:60018 Country:US Phone:847-298-9000 CAGE:0Z6C4 Company Name: VELSICOL CHEMICAL CORPORATION CAGE:VELSI

Ingred Name:PETROLEUM HYDROCARBON Other REC Limits:NONE RECOMMENDED

======= Hazards Identification =======

================

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5MG/M3 Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES:VAPORS FROM HEATING MAY CAUSE IRRITATION.SKIN:VAPORS FROM HEATING MAY CAUSE IRRITATION.INGEST:NOT REPORTED.INHAL:VAPORS FROM HEATING MAY CAUSE RESPIRATORY IRRITATION. Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY NTP, IARC OR OSHA AS A CAR CINOGEN. Effects of Overexposure:INHAL:NAUSEA,VOMITING. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.CALL PHYSICIAN IF IRRITATION DEVELOPS.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.N OTE TO PHYSICIAN:TREAT SYMPTOMATICALLY.

Flash Point Method:COC

Flash Point:>450F,>232C

Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.AVOID SPREADING BURNING LIQUID WITH WATER STREAM.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT

OF FIRE MAY PRODUCE

HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.HEAT OF FIRE MAY CAUSE CONTAINERS TO BURST.

Spill Release Procedures: VENTILATE AREA.SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY); PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL.

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED P LACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM HEAT,SPARKS,FLAMES AND STRONG OXIDIZERS. Other Precautions:AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPIATE FOR EXPOSURE OF CONCERN. Ventilation:NO SPECIAL REQUIREMENTS. Protective Gloves:IMPERMEABLE GLOVES Eye Protection:CHEMICAL SPLASH GOGGLES Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER. Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA. Supplemental Safety and Health NONE

HCC:V6

Boiling Pt:B.P. Text:>660F,>349C Melt/Freeze Pt:M.P/F.P Text:340F,171C Vapor Pres:NON VOLATL Vapor Density:NOT VOLATL Spec Gravity: