

HEWLETT-PACKARD CO,CORPORATE HQ -- HP LASER JET TONER CARTRIDGE C3903A --
7045-01-422-9592

===== Product Identification =====

Product ID:HP LASER JET TONER CARTRIDGE C3903A

MSDS Date:01/21/1995

FSC:7045

NIIN:01-422-9592

MSDS Number: CCJJJ

=== Responsible Party ===

Company Name:HEWLETT-PACKARD CO,CORPORATE HQ

Address:3000 HANOVER ST

City:PALO ALTO

State:CA

ZIP:94304-1112

Country:US

Info Phone Num:

415-857-1501/FOR MSDS 800-468-8347

Emergency Phone Num:415-857-1501

CAGE:28480

=== Contractor Identification ===

Company Name:HEWLETT-PACKARD CO, CORPORATE HQ

Address:3000 MINUTEMAN RD

Box:City:ANDOVER

State:MA

ZIP:01810-1032

Country:US

Phone:404-648-8754/FAX: 800-947-3299

CAGE:28480

===== Composition/Information on Ingredients =====

Ingred Name:IRON OXIDE, MAGNETITE 95-3

CAS:1317-61-9

Fraction by Wt: 45-55%

Ingred Name:STYRENE ACRYLATE COPOLYMER,

Fraction by Wt: 45-55%

=

=====
Hazards Identification
=====

LD50 LC50 Mixture:ORAL LD50(RATS): >5000 MG/KG
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: MINIMAL RESPIRATORY TRACT
IRRITATION MAY OCCUR AS W/EXPOSURE TO LARGE AMOUNTS OF ANY
NON-TOXIC DUST. EYES: MAY CAUSE IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION.
Medical Cond Aggravate
d by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:INGESTION: DILUTE STOMACH CONTENTS W/SEVERAL GLASSES OF
WATER. INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/RUNNING WATER
FOR 15 MINS. SKIN: WASH W/SOAP & WATER.

=====
Fire Fighting Measures
=====

Extinguishing Media:CO2, WATER, DRY CHEMICALS
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NON-FLAMMABLE SOLID. TON
ER MATERIAL, LIKE
MOST ORGANIC MATERIAL IN POWDER FORM, IS CAPABLE OF CREATING A DUST
EXPLOSION.

=====
Accidental Release Measures
=====

Spill Release Procedures:NO TONER SPILLAGE OCCURS IN NORMAL OPERATION
OR HANDLING. IF IT SHOULD OCCUR, AVOID INHALATION OF THE DUST.
SWEEP MATERIAL ONTO PAPER & CAREFULLY TRANSFER TO A SEALABLE WASTE
CONTAINER.

=====
Handling and Storage
=====

Handling and Storage Precautions
:KEEP AWAY FROM CONTACT W/OXIDIZING
MATERIALS.
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT REQUIRED UNDER INTENDED USE.
Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT UNDER
INTENDED USE.
Protective Gloves:NOT REQUIRED UNDER INTENDED USE
Eye Protection:NOT REQUIRED UNDER INTENDED USE
Other Protective Equipment:NOT REQUIRED UNDER INTENDED USE.
Supplemental Safety and Health
HP L

ASER JET 5P PRINTER.

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:100-150C

Spec Gravity:1.4-1.8

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK FINE POWDER W/SLIGHT PLASTIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:COMBUSTION WILL PRODUCE CARBON DIOXIDE AND, POSSIBLE TOXIC CHEMICALS SUCH AS CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:THIS PRODUCT IS CONSTRUCTED FROM PLASTICS & METALS. THE WASTE TONER COULD BE CONSIDERED AS PLASTIC WASTE. DISPOSAL SHOULD BE SUBJECT TO FEDERAL, STATE & LOCAL REGULATIONS.

=====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of

Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.