

AKRON PAINT AND VARNISH INC -- WALKWAY NONSLIP BLACK G-9126 -- 8010-00-641-0427

=====  
Product Identification  
=====

Product ID:WALKWAY NONSLIP BLACK G-9126

MSDS Date:04/10/1995

FSC:8010

NIIN:00-641-0427

MSDS Number: CCJWH

=== Responsible Party ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PKY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Info Phone Num:330-773-8911

Emergency

Phone Num:330-773-8911

CAGE:70228

=== Contractor Identification ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Phone:216-773-8911

CAGE:70228

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CRYSTALLINE SILICA (CHRONIC HEALTH EFFECTS POSSIBLE IF  
INHALED AS A DUST).

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 42.45%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.1 MP/F3

ACGIH TLV:0.1 M

Ingred Name:VM&P NAPHTHA RULE 66 (VP = 15 @ 100F)

CAS:64742-89-8

Fraction by Wt: 28.12%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: CAN CAUSE  
REDNESS,IRRIT,SWELLING,BLURRED VISION. SKIN:PROLONGED/REPEATED  
CONTACT CAN CAUSE MODERATE IRRIT, DE  
FATTING, DERMATITIS.  
BREATHING:EXCESSIVE INHALATION OF VAPORS AND/OR SPRAY MIST CAN C  
AUSE RESPIRATORY IRRITATION,  
DIZZINESS/WEAKNESS/FATIGUE/NAUSEA/HEADACHE/UNCONSCIOUSNESS.  
Explanation of Carcinogenicity:LIMITED EVIDENCE OF CARCINOGENICITY TO  
HUMANS IARC CLASS 2A.  
Effects of Overexposure:ASPHYXIATION. INGEST: GASTROINTESTINAL  
IRRITATION/NAUSEA/VOMITING/DIARRHEA. ASPIRATION OF MATERIAL INTO  
LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

=====  
First Aid Measures  
=====

First Aid:EYES:FLUSH W/LRG AMTS WATER 15 MIN.LIFT LIDS, GET IMMED MED  
AID.SKIN:WASH W/SOAP/WATER REMOVE CONTAM CLOTHES WASH BEFORE  
REUSE.CONSULT DR.IF IRRIT PERSISTS.INGEST:DON'T INDUCE VOMITING.CAN  
CAUSE CHEM PNEUMONITIS/CAN BE FATAL.GIVE 1-2 GLASSES WATER TO  
DILUTE.INHAL:GET FRESH AIR.IF TROUBLE BREATHING GIVE OXYGEN.IF  
BREATHING STOPS GIVE ARTIF RESP.KEEP WARM/QUIET.GET MED AID.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:50.0F,10.0C  
Lower Limits:0.9  
Upper Limits:7.0  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG. USE  
WATER FOR COOLING MATERIAL IN VICINITY OF FIRE.  
Fire Fighting Procedures:USE SCBA W/A FULL FACEPIECE OPERATED IN  
PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE. WEAR PROTECTIVE  
CLOTHING.  
Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR, TRAVEL ALONG  
GROUND TO IGNITION SOURCE SOME DISTANCE FROM HANDLING

POINT.

IGNITION SOURCES:PILOT LIGHTS/SMOKING/HEATERS/ELECTRIC\*

===== Accidental Release Measures =====

Spill Release Procedures:SMALL:ABSORB

W/RAGS/ABSORBENT/VERMICULITE/OTHER; TRANSFER TO HOOD.

LARGE:ELIMINATE IGNIT SOURCES. DIKE AREA-PREVENT SPREADING.

VENTILATE INDOOR AREA. PUMP LIQUID INTO SALVAGE TANK REMAINING  
LIQUID TAK EN UP W/SAND/ABSORB/OTHER. SHOVEL \*\*

===== Handling and Storage =====

Handling and

Storage Precautions:DON'T DROP CNTNRS.NO HEAT/SPARKS/OPEN

FLAME.STORE LRG QTY IN BLDG COMPLY W/OSHA 1910.106.DONT PRESSURE TO  
EMPTY.NO BREATHE SAND DUST.READ MFG PRECAUTN

Other Precautions:\*MOTORS/ELEC SWITCH SPARKS/STATIC DISCHARGE.NO

TORCH-CUT EMPTY CNTNRS.VAPORS IN EMPTY CNTNR MAY EXPLODE.APPLIC TO  
HOT SURFACES-SPECIAL PRECAUS.DURING EMERG COND OVEREXPOSE TO DECOMP

PRODS-HEALTH HAZAR D.SYMPTS NOT IMMED APPARENT.GET MED AID.

===== Exposure Controls/Personal Protec

tion =====

Respiratory Protection:UNRESTRICTED VENTILATION APPROVED

CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE COMBINATION OF  
PARTICULATES/VAPOR. IN CONFINED AREAS, APPROVED AIR LINE TYPE  
RESPIRATORS/HOODS.

Ventilation:SUFFICIENT VENT TO KEEP AIR

Spec Gravity:1.33493

Evaporation Rate & Reference:6.71 (N-BUTYL ACETATE)

Appearance and Odor:BLACK LIQUID.

Percent Volatiles by Volume:51.6

===== Stability and Reactivity Data =====

Stability Ind

icator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZERS (EG: NITRIC ACID).

Stability Condition to Avoid:KEEP AWAY FROM HEAT AND OPEN FLAME.

Hazardous Decomposition Products:MAY FORM CARBON MONOXIDE AND DIOXIDE,  
VARIOUS HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE AND  
FEDERAL REGULATIONS. \*\*INTO CNTNRS. PREVENT RUN-OFF TO  
SEWERS/BODIES OF WATER. NOTIFY PROPER AUTHORITIE

S AS REQUIRED BY  
LOCAL, STATE AND FEDERAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.